

Slipproof 1300

anti slip treatment for ceramic tiles & granite

Product Data

Slipproof 1300 is an invisible non-slip treatment for ceramic tiles and granite. Slipproof 1300 anti-slip treatment is a one component product designed for easy usage and one application last up to 5 years or more. Slipproof 1300 is not a coating but an effective proven product that alters the chemistry of the base material through reaction and creates a permanent process. After proper application of Slipproof 1300 the treated surface's coefficient increase significantly especially on wet floors. Can be use on most ceramic tiles, re-constituted granites, and honed granite

Method of Application

- All areas must washed with Alfa 750 diluted up to 10 parts water or lesser. Repeat at least 2 times for old floor tiles.
- Use directly from container / drum. No Dilution!
- Use adequate protection like rubber gloves and proper eye protection, before usage
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Pour Slipproof 1300 onto floor and spread over area with a brush. Must be totally wet.
- Agitate floor by brush area over and over with the brush.
- Work on area not more then 2-3 m2 each time
- Allow 5-10 minutes reaction time. Repeat on area that is not to satisfaction.
- Do not allow more then 20 minutes each time, and always prevent hydration and is especially good to damp hot surface before application.
- Wash off with Alfa 750 (diluted) as above and follow back rinsing with clean water
- Check during application if acceptable, otherwise repeat application.
- For darker ceramic tiles / stones, it be may require to use Crystalshine 1800 or Colorpoxy 1810 to restore lightened surface.

Coverage Guide

1 litre / coat = 8m2

Type of Surfaces

Ceramic tiles / unpolished granite

Packing

Plastic container in 1 litre, 4 litres and 25 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement / grouts prior to any treatment.

Applications of Slipproof 1300 must be used according to the guided time and must not be left to dry. Always neutralize with Alfa 750 and follow by plenty of clean water as recommended according to manufacture instructions and method. No dilution, or mixture with other products which might cause the performance of Slipproof 1300 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application.

Note: Color of surface may change is expected for sensitive tiles or stones, especially dark colored tiles might lightened or turn whitish. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.euroseal sealers.com

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat.

EUROSEAL SEALERSwww.euroseal sealers.com