

Anti-Skid 1350

waterbased anti-skid floor coating

Product Data

Anti-Skid 1350 is a water based floor coating that increase the co-efficient of friction on the treated surfaces and is suitable for both dry and wet situation. Designed specifically for Polished Marble, Polished Granite and Polished Compressed Stones and many other surfaces that requires little or no change to the surface texture or shine. Anti-Skid 1350 has good water and stain repellent properties. Coated floors should be cleaned or maintained by mopping with Clean & Shine 880 or PH Rinse 800 and re-treated when and if necessary.

Method of Application

- All floors must be washed, cleaner and must be dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a flat cotton mop / sponge / cloth.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 even application coat should be sufficient in most cases.
- Clean or buff off excess Anti-Skid 1350 before it is dries or cured, with a clean cloth.

Coverage Guide

1 litre / coat = 30m²

Type of Surfaces

Polished marble / granite / compressed stones

Packing

Plastic Bottles in 1 litre, 4 litres and 25 litres

Specifications

All natural stones and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement & grouts prior to any treatment. Applications of -Skid 1350 must be applied in manner using either a flat mop / sponge or cloth. Spread evenly for not more than 2m² for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Anti-Skid 1350 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application

EUROSEAL SEALERS

www.eurosealsealers.com