

Colorpoxy 1810

colored enhancer for marble & granite

Product Data

Colorpoxy 1810 colored enhancer is an ultra fine color treatment and stone enhancer designed to effectively deepens and retorts the stone's natural color. It is designed to be use for polished marble or granite and does not leave any film and is highly vapor transmittable on the treated surface. The solution penetrates instantly into the stones has excellent water repelling properties. There are 5 colors: Black, Yellow, Green, Red and Brown which can be diluted with Moistproof 1050 to match the stone's color.

Method of Application

- All areas must be fully dry prior to application.
- Use directly from container without any dilution.
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a non colored cotton cloth / Flat mop
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Buff off after 10-20 minutes

Coverage Guide1 litre / coat = 20m²1 litre / coat = 25m²**Type of Surfaces**

Polished granite

Polished marble / Tiles

Packing

Metal container in 1 litre, 5 litres and 20 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement / grouts prior to any treatment.

Use Moistproof 1050 / Proseal 1000 / Aquapro 1010 to impregnate all natural stones before application of Crystalshine 1800. Applied Colorpoxy 1810 in manner using either a flat mop / sponge / cotton cloth or spray method. Spread evenly in not more then 2-3m² for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Crystalshine 1800 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.euroseal sealers.com

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

EUROSEAL SEALERSwww.euroseal sealers.com