

Aquamatte 200

matte finished- waterbased stone sealer for porous stones

Product Data

Aquamatte 200 is a unique formulated acrysilicone waterbased stone sealer developed for deep penetration for porous natural stones, for both external and internal applications. Aquamatte 200 has good UV properties and depending on the density of the stone's surface it produces a natural satin matte finish. Aquamatte 200 does not create any thick filming and has good resistances against surface stains.

Method of Application

- All areas must be fairly dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft brush / roller / sponge.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 thin application coat should be sufficient in most cases
- Should a 2nd coat be required, apply before 1st coat cures.

Coverage Guide

1 litre / coat = 12m²

1 litre / coat = 10m²

1 litre / coat = 8m²

Type of Surfaces

Slates / Quartzite / Quarry Tiles / Sandstone

Rough Limestone

Flamed & Bushhammered Granite / Tumbled Marble

Packing

Plastic Bottles in 1 litre, 4 litres and 25 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Aquamatte 200 must be applied in manner using either a roller / brush / sponge. Spread evenly in not more than 2-3m² in for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Aquamatte 200, be allowed without the consent of the product manufacturer or Specifier

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.euroseal sealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application.

EUROSEAL SEALERS

www.euroseal sealers.com