

**Aquashine 300**

gloss finish - waterbased stone sealer for porous stones

**Product Data**

Aquashine 300 is a specially formulated high quality acrysilicone emulsion sealer designed for long lasting surface protection. Aquashine 300 cures to form a clear gloss surface and does not peel or yellow the treated stone. Aquashine 300 is suitable for external as well as internal application, and has excellent surface stain resistant.

**Method of Application**

- All areas must be fairly dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft brush / roller / sponge.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 thin application coat should be sufficient in most cases.
- Should a 2<sup>nd</sup> coat be required, apply 1<sup>st</sup> coat cures.

**Coverage Guide**

1 litre / coat = 12m<sup>2</sup>  
1 litre / coat = 10m<sup>2</sup>  
1 litre / coat = 8m<sup>2</sup>

**Type of Surfaces**

Slates / Quartzite / Quarry Tiles / Sandstone  
Rough Limestone  
Flamed & Bushhammered Granite / Tumbled Marble

**Packing**

Plastic Bottles in 1 litre, 4 litres and 25 litres

**Specifications**

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Aquashine 300 must be applied in manner using either a roller / brush / sponge. Spread evenly in not more than 2-3m<sup>2</sup> in for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Aquashine 300, be allowed without the consent of the product manufacturer or Specifier

**Caution!**

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to [www.euroseal sealers.com](http://www.euroseal sealers.com).

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application.

***EUROSEAL SEALERS***

[www.euroseal sealers.com](http://www.euroseal sealers.com)