

**Product Data**

Europox 3000 is a clear non yellowing transparent 2 component liquid solvent based epoxy binder and treatment system. When mixed together with pebbles it forms a tough weather resistant seamless flooring without the use of cement mortar. When used on concrete or landscape stone flooring it will enhance the texture and helps pro-long the surface. Europox 3000 has good resistances against oil, acid and general stains.

**Method of Application**

- All areas must be fully dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Mix component A & B together proportionally, stir well before applying.
- Pot life approx 60 minutes in normal weather condition.
- Use application with a roller/ brush. As for pebbles binding mix with metal trowel together with the pebbles before laying onto floor. Make sure pebbles, surfaces are totally dry .
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Should a 2<sup>nd</sup> coat be required, apply after 1<sup>st</sup> coat has cured or at least 12 hour after.

**Coverage Guide**

1 kg / coat = 1-2m<sup>2</sup>  
1 kg / coat = 10m<sup>2</sup>

**Type of Surfaces**

Pebbles (binding)  
Pebbles (sealing), concrete, rough stones

**Packing**

Metal container in 1 kg, 5 kg and 20 kg

**Specifications**

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Europox 3000 must be applied in manner using a metal trowel (groove less). Spread evenly in not more then 2-3m<sup>2</sup> for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Europox 3000, be allowed without the consent of the product manufacturer or Specifier.

**Caution!**

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to [www.eurosealsealers.com](http://www.eurosealsealers.com)

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

**EUROSEAL SEALERS**

[www.eurosealsealers.com](http://www.eurosealsealers.com)