

Rapidfill 3300

liquid filler & hardener for marble

Product Data

Rapidfill 3300 is a 2 component clear liquid filler and hardener for marble. Its has been designed to fill micro hairline cracks on marble, and further aid of a re-enforcement in strengthening the surface as well. Increased shine can be observed after filling with Rapidfill 3300, after polishing. Rapidfill 3300 can help to slow efflorescence and moisture.

Method of Application

- All areas must be fully dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Best to roughen surface before application (must be dry surface)
- Mix component A & B together proportionally, stir well before applying.
- Pot life approx 60 minutes in normal weather condition.
- Use application with a flat metal trowel, spread and scrape off excess material immediately as you apply.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Should a 2nd coat be required, apply after 1st coat has cured or at least 12 hour after.
- Allow at least 24 hours before polishing work.

Coverage Guide1 litre / coat = 20m²**Type of Surfaces**

Marble / limestone

Packing

Metal container in 1 kg, 5 kg and 20 kg

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Rapidfill 3300 must be applied in manner using a metal trowel (groove less). Spread evenly in not more then 2-3m² for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Rapidfill 3300, be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

EUROSEAL SEALERSwww.eurosealsealers.com