

**Aquadamp 400**

anti-dampness back treatment

**Product Data**

Aquadamp 400 is an easy to use true waterbased back treatment for all sawn cut or cleft surfaces of most natural stones. Unlike any type of film forming so call back treatment products that creates an anti-bonding barrier to the bedding mortar Aquadamp 400 does not. Aquadamp 400 is a time tested & proven product which is totally absorbed into the back of the stone. Once cured there will not be any film on the back of the stone (anti-bonding barrier), and the bonding mortar adhesion will not be affected. Aquadamp 400 has excellent vapor transmission allowing the mortar to cure properly and at the same time blocking heavy moisture from building up inside the stones, creating water marks. A highly recommended products to use!

**Method of Application**

- All areas must be fairly dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft brush / roller / sponge.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 thin application coat should be sufficient in most cases. Clean off excess immediately.
- Should a 2<sup>nd</sup> coat be required, apply before 1<sup>st</sup> coat cures.
- Allow at least 12 hour to cure before installation, stack vertically for drying.

**Coverage Guide**1 litre / coat = 8-12m<sup>2</sup>**Type of Surfaces**Slates / Quartzite / Quarry Tiles / limestone  
Limestone / Sandstone1 litre / coat = 12-15m<sup>2</sup>

Marble / Granite

(Note: coverage is for back and edges of stones)

**Packing**

Plastic Bottles in 1 litre, 4 litres and 25 litres

**Specifications**

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment. .

Applications of Aquadamp 400 must be applied in manner using either a roller / brush / sponge. Spread evenly in not more then 2-3m<sup>2</sup> in for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Aquadamp 400, be allowed without the consent of the product manufacturer or Specifier.

**Caution!**

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to [www.eurosealsealers.com](http://www.eurosealsealers.com).

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application.

**EUROSEAL SEALERS**[www.eurosealsealers.com](http://www.eurosealsealers.com)