

**Product Data**

Stonepoxy 500 is a clear solvent based micro-acrylic solution that cures and form into a hard wearing satin finished effect. Stonepoxy 500 creates a chemical resistant surface with anti-graffiti properties. Stones that are applied with Stonepoxy 500 will have an enhanced texture and maintenances will be much easier.

**Method of Application**

- All areas must be fully dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft brush / roller.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Should a 2<sup>nd</sup> coat be required, apply after 1<sup>st</sup> coat has cured or at least 12 hour after.

**Coverage Guide**

1 litre / coat = 10m<sup>2</sup>

1 litre / coat = 12m<sup>2</sup>

**Type of Surfaces**

Slates / Quartzite / Quarry Tiles / limestone  
Rough Limestone / Sandstone / Pebbles

Tumbled Marble / Flamed or textured Granite

**Packing**

Metal container in 1 litre, 5 litres and 20 litres

**Specifications**

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Stonepoxy 500 must be applied in manner using either a roller / brush. Spread evenly in not more than 2-3m<sup>2</sup> for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Stonepoxy 500, be allowed without the consent of the product manufacturer or Specifier.

**Caution!**

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to [www.euroseal sealers.com](http://www.euroseal sealers.com).

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

**EUROSEAL SEALERS**

[www.euroseal sealers.com](http://www.euroseal sealers.com)