

Tileguard 600

solvent based mosaic & ceramic tile grout protection

Product Data

Tileguard 600 is a solvent based penetrating invisible protection coat for tile and grout surfaces designed specially for mosaic, quartz / compress stones and ceramic tile. Tileguard 600 has anti-fungal properties preventing grout joints resistant against common staining and yellowing, making treated surface easier to clean and maintain. Tileguard 600 allows vapor transmission. and is clear in color.

Method of Application

- All areas must be dry prior to application.
- Use directly from container / drum. No Dilution!
- Use with a soft brush / roller / sponge / by spraying method. Wipe off excess liquid before it dries
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 thin application coat should be sufficient in most cases.
- Wash off with water or Stripper X 1100 on excess areas.
- Should a 2nd coat be required, apply after 12 hours.
- Allow at least 24 hour to cure before exposure to water.

Coverage Guide1 litre / coat = above 40m²1 litre / coat = above 60m²**Type of Surfaces**

Mosaic

Ceramic tiles, Compress Stones, Quartz Stones

Packing

Metal container in 1 litre, 5 litres and 25 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Tileguard 600 must be applied in manner using either by spraying / brush / sponge method. Spread evenly into the grouts approx 2m² each time and wipe over with a soft cloth for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Tileguard 600 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.euroseal-sealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application.

EUROSEAL SEALERSwww.euroseal-sealers.com