

Mop & Grip 1330 concentrated
waterbased anti-skid floor maintenance solution

Product Data

Mop & Grip 1330 is a clear concentrated floor maintenance solution, used for twice monthly or weekly as desired to help maintain the effectiveness on the co-efficient of friction on polished ceramic, marble and granite floors treated with Antiskid 1350 or Slipproof 1300. Floors that have not been treated with Antiskid 1350 or Slipproof 1300 can also use Mop & Grip 1330 as a mopping additive to help make the flooring less slippery. Mop & Grip 1330 can be mopped over with other regular wax free cleaning solution. Can be diluted up 20 to 25 times of clean water with 1 part of Mop & Grip 1330 floor.

Method of Application

- Dilute 1 part Mop & Grip 1330 to 20 -25 parts of clean water.
- Use application with any clean cotton mop / sponge / cloth.
- Mop over floor area with the mixture. A thin even mopping is desire.
- 1 even application coat is sufficient.
- Allow floors to dry before mopping over with clean water the next day.
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- If some visible residue occurs simply clean off with warm water & use more dilution of water for future mopping

Coverage Guide

250ml diluted with 5litres of water = approx 125m2

Type of Surfaces

Polished marble / granite /
compressed stones, wood
floors, ceramic tiles, vinyl floors

Packing

Plastic Bottles in 250ml, 1 litre, 4 litres and 25 litres

Specifications

Applications of Mop & Grip 1330 must be applied in manner using either a clean mop / sponge or cloth. Spread evenly and according to manufacture instructions and method. Mop over in a thin even uniform pattern and do mix with other products which might cause the performance of Mop & Grip 1330. Mixed solution must be used within 2 weeks. Do not add water to the concentrated 1330

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.euroseal sealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application

EUROSEAL SEALERS

www.euroseal sealers.com