

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SOVEREIGN SX70 MAHOGANY Supercedes Date: 13-Apr-2021 Revision date 03-Nov-2021 Revision Number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SOVEREIGN SX70 MAHOGANY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use

Restricted to professional users. Paints and varnishes.

Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Limited
Common Rd
ST16 3EH
Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Skin sensitisation	Category 1A - (H317)
Carcinogenicity	Category 1B - (H350)
Reproductive toxicity	Category 1B - (H360)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 3-lodo-2-propynyl butylcarbamate [IPBC], 2-Butanone, oxime



Signal word Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways.

H317 - May cause an allergic skin reaction.

United Kingdom - BE Page 1 / 18

Revision date 03-Nov-2021

Supercedes Date: 13-Apr-2021 Revision Number 3

H350 - May cause cancer.

H360 - May damage fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

SOVEREIGN SX70 MAHOGANY

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe vapour

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Toxic to aquatic life. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics	918-481-9	RR-113412-9	>25 - <40	Asp. Tox. 1 (H304) (EUH066)		01-2119457273- 39-XXXX
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	919-857-5		10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)		01-2119463258- 33-XXXX
Hydrocarbons, C9-C11, n-alkanes, isoalkanes,	919-857-5	64742-48-9	10 - <20	STOT SÉ 3 (H336)		01-2119463258- 33-XXXX

United Kingdom - BE Page 2 / 18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021

Revision date 03-Nov-2021 Revision Number 3

Asp. Tox. 1 cyclics, <2% aromatics (H304)(EUH066) Flam. Liq. 3 (H226) Hydrocarbons, C9-C12, 919-446-0 RR-91855-8 1- <2.5 STOT SE 3 01-2119458049n-alkanes, isoalkanes, (H336) 33-XXXX cyclics, aromatics STOT RE 1 (2-25%)(H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066) Diethylene glycol 01-2119475104-203-961-6 112-34-5 1-<2.5 Eye Irrit. 2 monobutyl ether 44-XXXX (H319)3-lodo-2-propynyl 259-627-5 55406-53-6 0.1 - <1 STOT RE 1 butylcarbamate [IPBC] (H372) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302) Acute Tox. 3 (H331) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (M Factor Acute = 10)(M Factor $\hat{Chronic} = 1$ 01-2119524678-Cobalt 205-250-6 136-52-7 0.1 - <1 Eye Irrit. 2 29-XXXX bis(2-ethylhexanoate) (H319) Skin Sens. 1A (H317) Repr. 1B (H360f) Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412) 255-437-1 41556-26-7 Bis(1,2,2,6,6-pentameth 0.1 - <1 Skin Sens. 1 yl-4-piperidyl) sebacate (H317) 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Hexanoic acid, 2-ethyl-, 286-272-3 85203-81-2 Eye Irrit. 2 01-2119979093-0.1 - <1 30-XXXX zinc salt, basic (H319) Repr. 2 (H361d) Aquatic Chronic 3 (H412)

United Kingdom - BE Page 3 / 18

SOVEREIGN SX70 MAHOGANY Revision date 03-Nov-2021 Supercedes Date: 13-Apr-2021 **Revision Number** 3

Dipropylene glycol	252-104-2	34590-94-8	0.1 - <1	^	01-2119450011-
monomethyl ether					60-XXXX
Calcium	205-249-0	136-51-6	0.1 - <1	Eye Dam. 1	01-2119978297-
bis(2-ethylhexanoate)				(H318)	19-xxxx
				Repr. 2 (H361d)	
				1 ' ' 1	
2-Butanone, oxime	202-496-6	96-29-7	0.1 - <1	Acute Tox. 3	01-2119539477-
,				(H301)	28-XXXX
				Acute Tox. 4	
				(H312)	
				Skin Irrit. 2	
				(H315)	
				Eye Dam. 1	
				(H318)	
				Skin Sens. 1	
				(H317)	
				Carc. 1B (H350)	
				STOT SE 3	
				(H336)	
				STOT SÉ 1	
				(H370)	
				STOT RE 2	
				(H373)	

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

> has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention.

Delayed pulmonary edema may occur.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact

Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or

allergic reactions see a doctor.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

> material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

United Kingdom - BE Page 4/18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021
Revision Number 3

resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically. Because of the

danger of aspiration, emesis or gastric lavage should not be used unless the risk is

justified by the presence of additional toxic substances.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Hydrocarbons.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to

United Kingdom - BE Page 5 / 18

SOVEREIGN SX70 MAHOGANY Supercedes Date: 13-Apr-2021 Revision date 03-Nov-2021 Revision Number 3

collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and shoes.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

Recommended storage temperature

Keep at temperatures between 5 and 25 $^{\circ}\text{C}.$

7.3. Specific end use(s)

Specific use(s)

Restricted to professional users. Paints and varnishes.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics,	-	Vapour

United Kingdom - BE Page 6 / 18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021
Revision date 03-Nov-2021
Revision Number 3

		
<2% aromatics		RCP-TWA 1200 mg/m ³
RR-113412-9		184 ppm
		Total hydrocarbons (ExxonMobil)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	-	TWA: 350 mg/m ³
Diethylene glycol monobutyl ether	TWA: 10 ppm	TWA: 10 ppm
112-34-5	TWA: 67.5 mg/m ³	TWA: 67.5 mg/m ³
		STEL: 15 ppm
		STEL: 101.2 mg/m ³
Cobalt bis(2-ethylhexanoate)	-	TWA: 0.1 mg/m ³
136-52-7		Capable of causing occupational asthma
1,2-Propylene glycol	-	TWA: 150 ppm
57-55-6		TWA: 474 mg/m ³
		TWA: 10 mg/m ³
		STEL: 450 ppm
		STEL: 1422 mg/m ³
		STEL: 30 mg/m ³
Dipropylene glycol monomethyl ether	TWA: 50 ppm	TWA: 50 ppm
34590-94-8	TWA: 308 mg/m ³	TWA: 308 mg/m ³
	*	STEL: 150 ppm
		STEL: 924 mg/m ³
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C10-C13, alkanes,	=	=	1200 mg/m ³
isoalkanes, cyclics, <2% aromatics			171ppm
RR-113412-9			8h TWA

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Hydrocarbons, C9-C12, n-al	kanes, isoalkanes, cyclics, a	aromatics (2-25%) (RR-91855-8)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	330 mg/m ³		
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d		

3-lodo-2-propynyl butylcarbamate [IPBC] (55406-53-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	0.023 mg/m ³		
worker Short term Systemic health effects	Inhalation	1.16 mg/m³		
worker Long term Systemic health effects	Dermal	2 mg/kg bw/d		

Cobalt bis(2-ethylhexanoate) (136-52-7)				
Туре	Exposure route	Derived No Effect Level	Safety factor	
	-	(DNEL)		
worker	Inhalation	235.1 µg/cm ²		
Long term				
Local health effects				

United Kingdom - BE Page 7 / 18

SOVEREIGN SX70 MAHOGANY Supercedes Date: 13-Apr-2021 Revision date 03-Nov-2021 Revision Number 3

Calcium bis(2-ethylhexanoa	te) (136-51-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	39.98 mg/m³	
Long term Systemic health effects worker	Dermal	5.67 mg/kg bw/d	

2-Butanone, oxime (96-29-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
DNEL/DMEL Long term Systemic health effects	Inhalation	0.028 mg/m³		
Long term Local health effects	Inhalation	0.9 mg/m³		
DNEL/DMEL Long term Systemic health effects	Dermal	0.004 mg/kg bw/d		

Derived No Effect Level (DNI	Derived No Effect Level (DNEL)				
Hydrocarbons, C9-C12, n-alk	kanes, isoalkanes, cyclics, a	aromatics (2-25%) (RR-91855-8)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	71 mg/m³			
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d			

Cobalt bis(2-ethylhexanoate) (136-52-7)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Local health effects	Inhalation	37 μg/cm²		
Consumer Long term Systemic health effects	Oral	55.8 μg/Kg bw/day		

Calcium bis(2-ethylhexanoate) (136-51-6)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Long term Systemic health effects Consumer	Inhalation	9.86 mg/m³		
Long term Systemic health effects Consumer	Dermal	2.83 mg/kg bw/d		
Long term Systemic health effects Consumer	Oral	2.83 mg/kg bw/d		

United Kingdom - BE Page 8 / 18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021
Revision Number 3

2-Butanone, oxime (96-29-7)				
Туре	P	Derived No Effect Level (DNEL)	Safety factor	
Long term Systemic health effects	Inhalation	0.00482 mg/m³		
Long term Local health effects	Dermal	0.43 mg/m³		

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)	
3-lodo-2-propynyl butylcarbamate [IPBC] (55406-53-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.001 mg/l
Sewage treatment plant	0.44 mg/l
Freshwater sediment	0.017 mg/kg dry weight
Marine sediment	0.002 mg/kg dry weight
Soil	0.005 mg/kg dry weight

Cobalt bis(2-ethylhexanoate) (136-52-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	β μg/l
Marine water	2.36 μg/l
Sewage treatment plant	0.37 μg/l
Freshwater sediment	9.5 mg/kg dry weight
Marine sediment	9.5 μg/l
Soil	10.9 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic

or rubber. Suitable protective clothing. Wear chemical resistant clothing such as gloves,

apron, boots or whole bodysuits made from neoprene, as appropriate.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearanceLiquidColourRed brown

Odour Characteristic Petroleum distillates

Odour threshold No information available

United Kingdom - BE Page 9 / 18

SOVEREIGN SX70 MAHOGANY Revision date 03-Nov-2021 Supercedes Date: 13-Apr-2021 **Revision Number** 3

Values Remarks • Method **Property**

No data available Not applicable Insoluble in water No data available

pH (as aqueous solution) Melting point / freezing point No data available Initial boiling point and boiling No data available

range

Flash point > 48 °C

Evaporation rate No data available

Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available Relative vapour density No data available Relative density 0.915 - 0.935 Immiscible in water Water solubility Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available **Dynamic viscosity** No data available **Explosive properties** No data available No data available **Oxidising properties**

9.2. Other information

Solid content (%) No information available

VOC Content (%)

No data available **Density**

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

United Kingdom - BE Page 10/18

Supercedes Date: 13-Apr-2021 Revision Number 3

10.6. Hazardous decomposition products

Hazardous decomposition

SOVEREIGN SX70 MAHOGANY

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 03-Nov-2021

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture

is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin

dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary

edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 19,959.10 mg/kg
ATEmix (dermal) 21,421.80 mg/kg
ATEmix (inhalation-dust/mist) 122.80 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C10-C13,	DL50 >5000 mg/kg (Rattus)	DL50 >2000 mg/kg	LC50 (8h) >5000 mg/m³ Rat -
alkanes, isoalkanes, cyclics, <2% aromatics		(Oryctolagus cuniculus)	Vapours
RR-113412-9			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 	LD50 >2000 mg/kg (Rattus)	>3000 mg/Kg (Rattus)	Ld50 (4h)>5.6mg/L (Rattus)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	LD50 >2000 mg/kg (Rattus)	>3000 mg/Kg (Rattus)	Ld50 (4h)>5.6mg/L (Rattus)

United Kingdom - BE Page 11 / 18

Supercedes Date: 13-Apr-2021 Revision Number 3

Revision date 03-Nov-2021

		 -	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Diethylene glycol monobutyl ether 112-34-5	=5660 mg/kg (Rattus)	= 2700 mg/kg (Oryctolagus cuniculus)	
3-lodo-2-propynyl butylcarbamate [IPBC] 55406-53-6	LD50 =1056 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (Rattus)	=0.67 mg/L (Rattus) 4 h
Cobalt bis(2-ethylhexanoate) 136-52-7	3125 mg/Kg (Rattus) (OECD 425)	> 5000 mg/kg (Oryctolagus cuniculus)	>10 mg/L (Rattus) 1 h
Bis(1,2,2,6,6-pentamethyl-4-pi peridyl) sebacate 41556-26-7	=2615 mg/kg (Rattus)		
Hexanoic acid, 2-ethyl-, zinc salt, basic 85203-81-2		> 2000 mg/kg (Rat)	
Dipropylene glycol monomethyl ether 34590-94-8	=5.35 g/kg (Rattus)	= 9500 mg/kg (Oryctolagus cuniculus)	
Calcium bis(2-ethylhexanoate) 136-51-6	>5000 mg/kg (Rattus)	=2045 mg/Kg (Rattus) (OECD 401)	>4.8 mg/L (Rattus) 1 h
2-Butanone, oxime 96-29-7	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	Muta. 1B
aromatics	
64742-48-9	

Carcinogenicity

SOVEREIGN SX70 MAHOGANY

Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

Chemical name	European Union
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	Carc. 1B
aromatics	
64742-48-9	
2-Butanone, oxime	Carc. 1B
96-29-7	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicityContains a known or suspected reproductive toxin. Classification based on data available for ingredients. May damage fertility or the unborn child.

United Kingdom - BE Page 12/18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021
Revision date 03-Nov-2021
Revision Number 3

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics RR-113412-9	LEO (72h) =1000 mg/L Algae (Pseudokirchner iella subcapitata)	LLO (96h) =1000 mg/L (Oncorhynchus mykiss)	-	LEO (48h) =1000 mg/L (Daphnia magna)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 	-	LC50 (96h) >1000 mg/L Oncorhynchus mykiss	-	LL50 (48h) >1000 mg/L Daphnia magna		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	-	LC50 (96h) >1000 mg/L Oncorhynchus mykiss	-	LL50 (48h) >1000 mg/L Daphnia magna		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	EL50 (72h) = 4.1 mg/l (Pseudokirchner ella subcapitata) OECD 401	10-30 mg/l	-	10-30mg/l (daphnia magna)		
Diethylene glycol monobutyl ether 112-34-5	EC50: >100mg/L (96h, Desmodesmus subspicatus)	LC50: =1300mg/L (96h, Lepomis macrochirus)	-	EC50: =2850mg/L (24h, Daphnia magna) EC50: >100mg/L (48h, Daphnia magna)		
3-lodo-2-propynyl butylcarbamate [IPBC] 55406-53-6	EC50 (72 hrs) 0.022 mg/l Scenedesmus subspicatus	LC50 96 h 0.049 - 0.079 mg/L (Oncorhynchus	-	Acute EC50 (48hrs) 0.16 mg/l - Daphnia magna	10	1

United Kingdom - BE Page 13/18

Supercedes Date: 13-Apr-2021 Revision Number 3

Revision date 03-Nov-2021

		mykiss				
		flow-through)				
Cobalt	-	EC50 1.5 mg/L	-	-	1	
bis(2-ethylhexanoate)		dissolved cobalt				
136-52-7		- read-across				
Bis(1,2,2,6,6-pentamet	-	LC50:	-	EC50: =20mg/L		
hyl-4-piperidyl)		=0.97mg/L (96h,		(24h, Daphnia		
sebacate		Lepomis		magna)		
41556-26-7		macrochirus)				
Hexanoic acid, 2-ethyl-,	-	LC50:	-	-		
zinc salt, basic		=100mg/L (96h,				
85203-81-2		Cyprinus carpio)				
Dipropylene glycol	-	LC50:	-	LC50:		
monomethyl ether		>10000mg/L		=1919mg/L		
34590-94-8		(96h,		(48h, Daphnia		
		Pimephales		magna)		
		promelas)				
2-Butanone, oxime	EC50: =83mg/L	LC50:	EC50 = 281	EC50:		
96-29-7	(72h,	=760mg/L (96h,	mg/L 17 h	=750mg/L (48h,		
	Desmodesmus	Poecilia	EC50 = 950	Daphnia magna)		
	subspicatus)	reticulata) LC50:	mg/L 5 min			
		777 - 914mg/L				
		(96h,				
		Pimephales				
		promelas) LC50:				
		320 - 1000mg/L				
		(96h, Leuciscus				
		idus)				

12.2. Persistence and degradability

SOVEREIGN SX70 MAHOGANY

Persistence and degradability No information available.

Component Information							
3-lodo-2-propynyl butylcarbamate [IPBC] (55406-53-6)							
Method	Exposure time Value Results						
OECD Test No. 301F: Ready	28 days		Not readily biodegradable				
Biodegradability: Manometric							
Respirometry Test (TG 301 F)							

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
3-lodo-2-propynyl butylcarbamate [IPBC] 55406-53-6	2.88	-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	0.37	-
Dipropylene glycol monomethyl ether 34590-94-8	-0.064	-
2-Butanone, oxime 96-29-7	0.65	5.8

12.4. Mobility in soil

Mobility in soil No information available.

United Kingdom - BE Page 14/18

SOVEREIGN SX70 MAHOGANY Revision date 03-Nov-2021 Supercedes Date: 13-Apr-2021 **Revision Number** 3

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics RR-113412-9	The substance is not PBT / vPvB	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	The substance is not PBT / vPvB	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	The substance is not PBT / vPvB	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	The substance is not PBT / vPvB	
Diethylene glycol monobutyl ether	The substance is not PBT / vPvB	
112-34-5	PBT assessment does not apply	
3-lodo-2-propynyl butylcarbamate [IPBC]	The substance is not PBT / vPvB	
55406-53-6	PBT assessment does not apply	
Cobalt bis(2-ethylhexanoate)	The substance is not PBT / vPvB	
136-52-7	PBT assessment does not apply	
Hexanoic acid, 2-ethyl-, zinc salt, basic 85203-81-2	PBT assessment does not apply	
Dipropylene glycol monomethyl ether 34590-94-8	The substance is not PBT / vPvB	
Calcium bis(2-ethylhexanoate) 136-51-6	PBT assessment does not apply	
2-Butanone, oxime 96-29-7	The substance is not PBT / vPvB	

12.6. Other adverse effects

No information available. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

United Kingdom - BE Page 15/18

SOVEREIGN SX70 MAHOGANY
Supercedes Date: 13-Apr-2021
Revision Number 3

14.1 UN number or ID number UN1263

14.2 Proper Shipping Name Paint related material

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group III

Description UN1263, Paint related material, 3, III, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 163, 650, 367

Classification code F1
Tunnel restriction code (D/E)
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler 30

Number)

IMDG

14.1 UN number or ID number UN1263

14.2 Proper Shipping Name Paint related material

14.3 Transport hazard class(es) 3 **14.4 Packing group** III

Description UN1263, Paint related material (3-lodo-2-propynyl butylcarbamate [IPBC]), 3, III, (48°C

c.c.), Marine Pollutant

14.5 Marine pollutant P

14.6 Special Provisions 163, 223, 367, 955

Limited Quantity (LQ) 5 L EmS-No F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1263

14.2 Proper Shipping Name Paint related material

14.3 Transport hazard class(es) 3 14.4 Packing group

Description UN1263, Paint related material, 3, III

14.5 Environmental hazards Yes

14.6 Special Provisions A3, A72, A192

Limited quantity (LQ) 10 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

United Kingdom - BE Page 16/18

SOVEREIGN SX70 MAHOGANY Supercedes Date: 13-Apr-2021 Revision date 03-Nov-2021 Revision Number 3

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diethylene glycol monobutyl ether	112-34-5	55. 75.

CAS 112-34-5 restricted for use in aerosol products sold to general public. Products for general public with level above 3% should be labeled "Do not use in paint spraying equipment".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H360F - May damage fertility

H361d - Suspected of damaging the unborn child

H361f - Suspected of damaging fertility

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

United Kingdom - BE Page 17 / 18

Revision date 03-Nov-2021

Supercedes Date: 13-Apr-2021 Revision Number 3

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

SOVEREIGN SX70 MAHOGANY

H410 - Very toxic to aquatic life with long lasting effects H411 - Toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Nov-2021

Indication of changes

Revision note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 18 / 18