

Inventory Control Form

3.5 mm Low Profile Pelvic System



Patient Information:

Synthes (USA)
To Order: (800) 523-0322

Synthes (Canada) Ltd.
To Order: (800) 668-1119

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

3.5 mm Pelvic Cortex Screws, self-tapping



	LENGTH		LENGTH
<input type="checkbox"/>	204.640 40 mm	<input type="checkbox"/>	204.700 100 mm
<input type="checkbox"/>	204.645 45 mm	<input type="checkbox"/>	204.705 105 mm
<input type="checkbox"/>	204.650 50 mm	<input type="checkbox"/>	204.710 110 mm
<input type="checkbox"/>	204.655 55 mm	<input type="checkbox"/>	204.715 115 mm
<input type="checkbox"/>	204.660 60 mm	<input type="checkbox"/>	204.720 120 mm
<input type="checkbox"/>	204.665 65 mm	<input type="checkbox"/>	204.725 125 mm
<input type="checkbox"/>	204.670 70 mm	<input type="checkbox"/>	204.730 130 mm
<input type="checkbox"/>	204.675 75 mm	<input type="checkbox"/>	204.735 135 mm
<input type="checkbox"/>	204.680 80 mm	<input type="checkbox"/>	204.740 140 mm
<input type="checkbox"/>	204.685 85 mm	<input type="checkbox"/>	204.745 145 mm
<input type="checkbox"/>	204.690 90 mm	<input type="checkbox"/>	204.750 150 mm
<input type="checkbox"/>	204.695 95 mm		

3.5 mm Locking Screws, self-tapping, with StarDrive recess



	LENGTH		LENGTH
<input type="checkbox"/>	212.101 10 mm	<input type="checkbox"/>	212.117 40 mm
<input type="checkbox"/>	212.102 12 mm	<input type="checkbox"/>	212.118 42 mm
<input type="checkbox"/>	212.103 14 mm	<input type="checkbox"/>	212.119 45 mm
<input type="checkbox"/>	212.104 16 mm	<input type="checkbox"/>	212.120 48 mm
<input type="checkbox"/>	212.105 18 mm	<input type="checkbox"/>	212.121 50 mm
<input type="checkbox"/>	212.106 20 mm	<input type="checkbox"/>	212.122 52 mm
<input type="checkbox"/>	212.107 22 mm	<input type="checkbox"/>	212.123 55 mm
<input type="checkbox"/>	212.108 24 mm	<input type="checkbox"/>	212.124 60 mm
<input type="checkbox"/>	212.109 26 mm	<input type="checkbox"/>	212.125 65 mm
<input type="checkbox"/>	212.110 28 mm	<input type="checkbox"/>	212.126 70 mm
<input type="checkbox"/>	212.111 30 mm	<input type="checkbox"/>	212.127 75 mm
<input type="checkbox"/>	212.112 32 mm	<input type="checkbox"/>	212.128 80 mm
<input type="checkbox"/>	212.113 34 mm	<input type="checkbox"/>	212.129 85 mm
<input type="checkbox"/>	212.114 35 mm	<input type="checkbox"/>	212.130 90 mm
<input type="checkbox"/>	212.115 36 mm	<input type="checkbox"/>	212.131 95 mm
<input type="checkbox"/>	212.116 38 mm		

3.5 mm Cortex Screws, self-tapping



	LENGTH		LENGTH
<input type="checkbox"/>	204.810 10 mm	<input type="checkbox"/>	204.826 26 mm
<input type="checkbox"/>	204.812 12 mm	<input type="checkbox"/>	204.828 28 mm
<input type="checkbox"/>	204.814 14 mm	<input type="checkbox"/>	204.830 30 mm
<input type="checkbox"/>	204.816 16 mm	<input type="checkbox"/>	204.832 32 mm
<input type="checkbox"/>	204.818 18 mm	<input type="checkbox"/>	204.834 34 mm
<input type="checkbox"/>	204.820 20 mm	<input type="checkbox"/>	204.836 36 mm
<input type="checkbox"/>	204.822 22 mm	<input type="checkbox"/>	204.838 38 mm
<input type="checkbox"/>	204.824 24 mm		

3.5 mm Threaded Plug, StarDrive

(for protection of the 3.5 mm Threaded Plate holes during contouring)

02.200.003



Implants (cont'd)

3.5 mm Cortex Screws, self-tapping, with T15 StarDrive recess



	LENGTH		LENGTH
	02.200.010	10 mm	
	02.200.012	12 mm	
	02.200.014	14 mm	
	02.200.016	16 mm	
	02.200.018	18 mm	
	02.200.020	20 mm	
	02.200.022	22 mm	
	02.200.024	24 mm	
	02.200.026	26 mm	
	02.200.028	28 mm	
	02.200.030	30 mm	
	02.200.032	32 mm	
	02.200.034	34 mm	
	02.200.036	36 mm	
	02.200.038	38 mm	
	02.200.040	40 mm	
	02.200.042	42 mm	
	02.200.044	44 mm	
	02.200.045	45 mm	
	02.200.046	46 mm	
	02.200.048	48 mm	
	02.200.050	50 mm	
	02.200.055	55 mm	
	02.200.060	60 mm	
	02.200.065	65 mm	
	02.200.070	70 mm	
	02.200.075	75 mm	
	02.200.080	80 mm	
	02.200.085	85 mm	
	02.200.090	90 mm	
	02.200.095	95 mm	
	02.200.100	100 mm	
	02.200.105	105 mm	
	02.200.110	110 mm	
	02.200.115	115 mm	
	02.200.120	120 mm	
	02.200.125	125 mm	
	02.200.130	130 mm	
	02.200.135	135 mm	
	02.200.140	140 mm	
	02.200.145	145 mm	
	02.200.150	150 mm	

4.5 mm Cortex Screws, self-tapping



	LENGTH		LENGTH
	214.840	40 mm	
	214.842	42 mm	
	214.844	44 mm	
	214.846	46 mm	
	214.848	48 mm	
	214.850	50 mm	
	214.852	52 mm	
	214.854	54 mm	
	214.856	56 mm	
	214.858	58 mm	
	214.860	60 mm	
	214.862	62 mm	
	214.864	64 mm	
	214.866	66 mm	
	214.868	68 mm	
	214.870	70 mm	
	214.872	72 mm	
	214.876	76 mm	
	214.880	80 mm	
	214.885	85 mm	
	214.890	90 mm	
	214.895	95 mm	
	214.900	100 mm	
	214.905	105 mm	
	214.910	110 mm	
	214.915	115 mm	
	214.920	120 mm	
	214.925	125 mm	
	214.930	130 mm	
	214.935	135 mm	
	214.940	140 mm	
	214.945	145 mm	

4.5 mm Cortex Screws (non self-tapping)



	LENGTH		LENGTH
	214.040	40 mm	
	214.042	42 mm	
	214.044	44 mm	
	214.046	46 mm	
	214.048	48 mm	
	214.050	50 mm	
	214.052	52 mm	
	214.054	54 mm	
	214.056	56 mm	
	214.058	58 mm	
	214.060	60 mm	
	214.062	62 mm	
	214.064	64 mm	
	214.066	66 mm	
	214.068	68 mm	
	214.070	70 mm	
	214.072	72 mm	
	214.076	76 mm	
	214.080	80 mm	
	214.085	85 mm	
	214.090	90 mm	
	214.095	95 mm	
	214.100	100 mm	
	214.105	105 mm	
	214.110	110 mm	
	214.115	115 mm	
	214.120	120 mm	
	214.125	125 mm	
	214.130	130 mm	
	214.135	135 mm	
	214.140	140 mm	
	214.145	145 mm	
	214.150	150 mm	
	214.155	155 mm	
	214.160	160 mm	

3.5 mm Spring Plates



	HOLES		STERILE	HOLES
	02.100.301	1	02.100.301S	1
	02.100.302	2	02.100.302S	2
	02.100.303	3	02.100.303S	3

3.5 mm Low Profile Reconstruction Plates



	HOLES	LENGTH		HOLES	LENGTH	
	245.023	3	39 mm	245.031	11	143 mm
	245.024	4	52 mm	245.032	12	156 mm
	245.025	5	65 mm	245.033	13	169 mm
	245.026	6	78 mm	245.034	14	182 mm
	245.027	7	91 mm	245.035	15	195 mm
	245.028	8	104 mm	245.036	16	208 mm
	245.029	9	117 mm	245.038	18	234 mm
	245.030	10	130 mm	245.039	20	260 mm

Implants (cont'd)

3.5 mm Low Profile Curved Reconstruction Plates



88 mm radius		108 mm radius		HOLES	LENGTH
	245.906		245.876	6	78 mm
	245.908		245.878	8	104 mm
	245.910		245.880	10	130 mm
	245.912		245.882	12	156 mm
	245.914		245.884	14	182 mm
	245.916		245.886	16	208 mm

3.5 mm Wide Angle Low Profile Reconstruction Plates



	HOLES	LENGTH
	02.100.203	3 39 mm
	02.100.204	4 52 mm
	02.100.205	5 65 mm
	02.100.206	6 78 mm
	02.100.207	7 91 mm
	02.100.208	8 104 mm
	02.100.209	9 117 mm
	02.100.210	10 130 mm
	02.100.211	11 143 mm
	02.100.212	12 156 mm
	02.100.213	13 169 mm
	02.100.214	14 182 mm
	02.100.215	15 195 mm
	02.100.216	16 208 mm
	02.100.218	18 234 mm
	02.100.220	20 260 mm

3.5 mm Low Profile Reconstruction J-Plates (88 mm radius)



LEFT	RIGHT	HOLES	LENGTH
		10	130 mm
		12	156 mm
		14	182 mm
		16	208 mm

3.5 mm Locking Low Profile Reconstruction Plates



	HOLES	LENGTH
	02.100.103	3 39 mm
	02.100.104	4 52 mm
	02.100.105	5 65 mm
	02.100.106	6 78 mm
	02.100.107	7 91 mm
	02.100.108	8 104 mm
	02.100.109	9 117 mm
	02.100.110	10 130 mm
	02.100.111	11 143 mm
	02.100.112	12 156 mm
	02.100.113	13 169 mm
	02.100.114	14 182 mm
	02.100.115	15 195 mm
	02.100.116	16 208 mm
	02.100.118	18 234 mm
	02.100.120	20 260 mm

3.5 mm Locking Low Profile Reconstruction J-Plates (88 mm radius)



LEFT	RIGHT	HOLES	LENGTH
		10	130 mm
		12	156 mm
		14	182 mm
		16	208 mm

3.5 mm Pubic Symphysis Plate with Coaxial Combi Holes



	HOLES	LENGTH
	02.100.004	4 57 mm
	02.100.006	6 78 mm

3.5 mm Pubic Symphysis Plate with 2 DCP Holes



	HOLES	LENGTH
	02.100.014	4 57 mm
	02.100.016	6 78 mm

	219.98	Washer, 7.0 mm
	292.20	2.0 mm Kirschner Wire, 150 mm, trocar point, (10/pkg.)
	294.68	6.0 mm Schanz Screw, 190 mm, spade point

Instruments

Drill Bits, quick coupling



		DIAMETER	LENGTH
<input type="checkbox"/>	310.288	2.8 mm	165 mm
<input type="checkbox"/>	310.37	3.5 mm	195 mm
<input type="checkbox"/>	324.210	2.5 mm	300 mm, 200 mm calibration
<input type="checkbox"/>	324.211	2.8 mm	300 mm, 200 mm calibration

Three-Fluted Drill Bits, quick coupling



		DIAMETER	LENGTH
<input type="checkbox"/>	315.92	2.5 mm	230 mm, 200 mm calibration
<input type="checkbox"/>	315.93	3.2 mm	230 mm, 200 mm calibration
<input type="checkbox"/>	315.48	4.5 mm	195 mm

Taps



<input type="checkbox"/>	311.31	for 3.5 mm Cortex Screws, 175 mm, 140 mm calibration
<input type="checkbox"/>	311.47	for 4.5 mm Cortex Screws, 175 mm, 140 mm calibration

Bending Templates



<input type="checkbox"/>	03.100.034	for 3.5 mm Low Profile Reconstruction Plates, 20 holes
--------------------------	------------	--



<input type="checkbox"/>	03.100.035	for 3.5 mm Low Profile Reconstruction J-Pates, 16 holes
--------------------------	------------	---



<input type="checkbox"/>	03.100.036	for 3.5 mm Low Profile Curved Reconstruction Plates, 88 mm radius, 16 holes
--------------------------	------------	---



<input type="checkbox"/>	03.100.037	for 3.5 mm Low Profile Curved Reconstruction Plates, 108 mm radius, 16 holes
--------------------------	------------	--