

Inventory Control Form

4.5 mm VA-LCP Curved Condylar Plate System



Patient Information:

Synthes (USA)
To Order: (800) 523-0322

Synthes (Canada) Ltd.
To Order: (800) 668-1119

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

Variable Angle Plates 4.5 mm VA LCP Curved Condylar Plates[◇]



		HOLES	LENGTH
<input type="checkbox"/>	02.124.406	6, Right	159 mm
<input type="checkbox"/>	02.124.407	6, Left	159 mm
<input type="checkbox"/>	02.124.408	8, Right	195 mm
<input type="checkbox"/>	02.124.409	8, Left	195 mm
<input type="checkbox"/>	02.124.410	10, Right	230 mm
<input type="checkbox"/>	02.124.411	10, Left	230 mm
<input type="checkbox"/>	02.124.412	12, Right	266 mm
<input type="checkbox"/>	02.124.413	12, Left	266 mm
<input type="checkbox"/>	02.124.414	14, Right	301 mm
<input type="checkbox"/>	02.124.415	14, Left	301 mm
<input type="checkbox"/>	02.124.416	16, Right	336 mm
<input type="checkbox"/>	02.124.417	16, Left	336 mm
<input type="checkbox"/>	02.124.418	18, Right	370 mm
<input type="checkbox"/>	02.124.419	18, Left	370 mm
<input type="checkbox"/>	02.124.420S	20, Right, Sterile (available sterile only)	405 mm
<input type="checkbox"/>	02.124.421S	20, Left, Sterile (available sterile only)	405 mm
<input type="checkbox"/>	02.124.422S	22, Right, Sterile (available sterile only)	439 mm
<input type="checkbox"/>	02.124.423S	22, Left, Sterile (available sterile only)	439 mm

5.0 mm Variable Angle Locking Screws, Self-Tapping, T25 Stardrive



		LENGTH
<input type="checkbox"/>	02.231.214	14 mm
<input type="checkbox"/>	02.231.216	16 mm
<input type="checkbox"/>	02.231.218	18 mm
<input type="checkbox"/>	02.231.220	20 mm
<input type="checkbox"/>	02.231.222	22 mm
<input type="checkbox"/>	02.231.224	24 mm
<input type="checkbox"/>	02.231.226	26 mm
<input type="checkbox"/>	02.231.228	28 mm
<input type="checkbox"/>	02.231.230	30 mm
<input type="checkbox"/>	02.231.232	32 mm
<input type="checkbox"/>	02.231.234	34 mm
<input type="checkbox"/>	02.231.236	36 mm
<input type="checkbox"/>	02.231.238	38 mm
<input type="checkbox"/>	02.231.240	40 mm
<input type="checkbox"/>	02.231.242	42 mm
<input type="checkbox"/>	02.231.244	44 mm
<input type="checkbox"/>	02.231.246	46 mm
<input type="checkbox"/>	02.231.248	48 mm
<input type="checkbox"/>	02.231.250	50 mm
<input type="checkbox"/>	02.231.255	55 mm
<input type="checkbox"/>	02.231.260	60 mm
<input type="checkbox"/>	02.231.265	65 mm
<input type="checkbox"/>	02.231.270	70 mm
<input type="checkbox"/>	02.231.275	75 mm
<input type="checkbox"/>	02.231.280	80 mm
<input type="checkbox"/>	02.231.285	85 mm
<input type="checkbox"/>	02.231.290	90 mm
<input type="checkbox"/>	02.231.295S	95 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.300S	100 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.305S	105 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.310S	110 mm, Sterile (available sterile only)

Variable Angle Screws: 5.0 mm Periprosthetic Variable Angle Locking Screws, Self-Tapping, T25 Stardrive[◇]

		LENGTH
<input type="checkbox"/>	02.231.008S	8 mm, sterile (available sterile only)
<input type="checkbox"/>	02.231.010	10 mm
<input type="checkbox"/>	02.231.012	12 mm
<input type="checkbox"/>	02.231.014	14 mm
<input type="checkbox"/>	02.231.016	16 mm
<input type="checkbox"/>	02.231.018	18 mm

[◇]Available nonsterile and sterile-packed. Add S to product number for sterile product.
Synthes is a trademark of Synthes, Inc. or its affiliates.

4.5 mm VA-LCP Curved Condylar Plate System

Implants (cont'd)

5.0 mm Cannulated Variable Angle Locking Screws



		LENGTH
<input type="checkbox"/>	02.231.620	20 mm
<input type="checkbox"/>	02.231.625	25 mm
<input type="checkbox"/>	02.231.630	30 mm
<input type="checkbox"/>	02.231.635	35 mm
<input type="checkbox"/>	02.231.640	40 mm
<input type="checkbox"/>	02.231.645	45 mm
<input type="checkbox"/>	02.231.650	50 mm
<input type="checkbox"/>	02.231.655	55 mm
<input type="checkbox"/>	02.231.660	60 mm
<input type="checkbox"/>	02.231.665	65 mm
<input type="checkbox"/>	02.231.670	70 mm
<input type="checkbox"/>	02.231.675	75 mm
<input type="checkbox"/>	02.231.680	80 mm
<input type="checkbox"/>	02.231.685	85 mm
<input type="checkbox"/>	02.231.690	90 mm
<input type="checkbox"/>	02.231.695S	95 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.700S	100 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.705S	105 mm, Sterile (available sterile only)
<input type="checkbox"/>	02.231.710S	110 mm, Sterile (available sterile only)

4.5 mm Cortex Screws, self tapping, 3.5 Hex

		LENGTH
<input type="checkbox"/>	214.822	22 mm
<input type="checkbox"/>	214.824	24 mm
<input type="checkbox"/>	214.826	26 mm
<input type="checkbox"/>	214.828	28 mm
<input type="checkbox"/>	214.830	30 mm
<input type="checkbox"/>	214.832	32 mm
<input type="checkbox"/>	214.834	34 mm
<input type="checkbox"/>	214.836	36 mm
<input type="checkbox"/>	214.838	38 mm
<input type="checkbox"/>	214.840	40 mm
<input type="checkbox"/>	214.842	42 mm
<input type="checkbox"/>	214.844	44 mm
<input type="checkbox"/>	214.846	46 mm
<input type="checkbox"/>	214.848	48 mm
<input type="checkbox"/>	214.850	50 mm
<input type="checkbox"/>	214.852	52 mm
<input type="checkbox"/>	214.854	54 mm
<input type="checkbox"/>	214.856	56 mm
<input type="checkbox"/>	214.858	58 mm
<input type="checkbox"/>	214.860	60 mm
<input type="checkbox"/>	214.862	62 mm
<input type="checkbox"/>	214.864	64 mm
<input type="checkbox"/>	214.866	66 mm
<input type="checkbox"/>	214.868	68 mm
<input type="checkbox"/>	214.870	70 mm

Instruments

Drill Bits and Wires

<input type="checkbox"/>	310.243	2.5 mm Drill Tip Guide Wire, 200 mm
<input type="checkbox"/>	310.31	3.2 mm Drill Bit, 145 mm, quick coupling
<input type="checkbox"/>	310.431	4.3 mm Drill Bit, 180 mm, quick coupling
<input type="checkbox"/>	324.212	3.2 mm Percutaneous Drill Bit QC/300 mm/ calibrated
<input type="checkbox"/>	324.213	4.3 mm Percutaneous Drill Bit QC/300 mm/ calibrated
<input type="checkbox"/>	292.652	2.0 mm Non colored, threaded guide wire, spade point, 230 mm
<input type="checkbox"/>	310.44	4.5 mm Drill Bit, 145 mm, quick coupling
<input type="checkbox"/>	310.634	4.3 mm Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/>	310.632	5.0 Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/>	03.120.026	2.5 mm Drill Tip Guide Wire, 300 mm