

# Inventory Control Form

## Titanium Cannulated Retrograde/Antegrade Femoral Nail-EX System



Patient Information:

Synthes (USA)  
To Order: (800) 523-0322

Synthes (Canada) Ltd.  
To Order: (800) 668-1119

Date: \_\_\_\_\_

Hospital: \_\_\_\_\_

Surgeon: \_\_\_\_\_

Procedure: \_\_\_\_\_

### Implants

#### 5.0 mm Titanium Locking Screws, with T25 StarDrive recess



	LENGTH		LENGTH		
<input type="checkbox"/>	04.005.516	26 mm	<input type="checkbox"/>	04.005.548	58 mm
<input type="checkbox"/>	04.005.518	28 mm	<input type="checkbox"/>	04.005.550	60 mm
<input type="checkbox"/>	04.005.520	30 mm	<input type="checkbox"/>	04.005.552	62 mm
<input type="checkbox"/>	04.005.522	32 mm	<input type="checkbox"/>	04.005.554	64 mm
<input type="checkbox"/>	04.005.524	34 mm	<input type="checkbox"/>	04.005.556	66 mm
<input type="checkbox"/>	04.005.526	36 mm	<input type="checkbox"/>	04.005.558	68 mm
<input type="checkbox"/>	04.005.528	38 mm	<input type="checkbox"/>	04.005.560	70 mm
<input type="checkbox"/>	04.005.530	40 mm	<input type="checkbox"/>	04.005.562	72 mm
<input type="checkbox"/>	04.005.532	42 mm	<input type="checkbox"/>	04.005.564	74 mm
<input type="checkbox"/>	04.005.534	44 mm	<input type="checkbox"/>	04.005.566	76 mm
<input type="checkbox"/>	04.005.536	46 mm	<input type="checkbox"/>	04.005.568	78 mm
<input type="checkbox"/>	04.005.538	48 mm	<input type="checkbox"/>	04.005.570	80 mm
<input type="checkbox"/>	04.005.540	50 mm	<input type="checkbox"/>	04.005.575	85 mm
<input type="checkbox"/>	04.005.542	52 mm	<input type="checkbox"/>	04.005.580	90 mm
<input type="checkbox"/>	04.005.544	54 mm	<input type="checkbox"/>	04.005.585	95 mm
<input type="checkbox"/>	04.005.546	56 mm	<input type="checkbox"/>	04.005.590	100 mm

#### 6.0 mm Titanium Locking Screws, with T25 StarDrive recess



	LENGTH		LENGTH		
<input type="checkbox"/>	04.005.616	26 mm	<input type="checkbox"/>	04.005.648	58 mm
<input type="checkbox"/>	04.005.618	28 mm	<input type="checkbox"/>	04.005.650	60 mm
<input type="checkbox"/>	04.005.620	30 mm	<input type="checkbox"/>	04.005.654	64 mm
<input type="checkbox"/>	04.005.622	32 mm	<input type="checkbox"/>	04.005.658	68 mm
<input type="checkbox"/>	04.005.624	34 mm	<input type="checkbox"/>	04.005.662	72 mm
<input type="checkbox"/>	04.005.626	36 mm	<input type="checkbox"/>	04.005.666	76 mm
<input type="checkbox"/>	04.005.628	38 mm	<input type="checkbox"/>	04.005.670	80 mm
<input type="checkbox"/>	04.005.630	40 mm	<input type="checkbox"/>	04.005.675	85 mm
<input type="checkbox"/>	04.005.632	42 mm	<input type="checkbox"/>	04.005.680	90 mm
<input type="checkbox"/>	04.005.634	44 mm	<input type="checkbox"/>	04.005.685	95 mm
<input type="checkbox"/>	04.005.636	46 mm	<input type="checkbox"/>	04.005.690	100 mm
<input type="checkbox"/>	04.005.638	48 mm	<input type="checkbox"/>	04.005.691	105 mm
<input type="checkbox"/>	04.005.640	50 mm	<input type="checkbox"/>	04.005.692	110 mm
<input type="checkbox"/>	04.005.642	52 mm	<input type="checkbox"/>	04.005.693	115 mm
<input type="checkbox"/>	04.005.644	54 mm	<input type="checkbox"/>	04.005.694	120 mm
<input type="checkbox"/>	04.005.646	56 mm	<input type="checkbox"/>	04.005.695	125 mm

#### 5.0 mm Titanium Locking Screws, with hexagonal recess



	LENGTH		LENGTH		
<input type="checkbox"/>	458.926	26 mm	<input type="checkbox"/>	458.954	54 mm
<input type="checkbox"/>	458.928	28 mm	<input type="checkbox"/>	458.956	56 mm
<input type="checkbox"/>	458.930	30 mm	<input type="checkbox"/>	458.958	58 mm
<input type="checkbox"/>	458.932	32 mm	<input type="checkbox"/>	458.960	60 mm
<input type="checkbox"/>	458.934	34 mm	<input type="checkbox"/>	458.964	64 mm
<input type="checkbox"/>	458.936	36 mm	<input type="checkbox"/>	458.968	68 mm
<input type="checkbox"/>	458.938	38 mm	<input type="checkbox"/>	458.972	72 mm
<input type="checkbox"/>	458.940	40 mm	<input type="checkbox"/>	458.976	76 mm
<input type="checkbox"/>	458.942	42 mm	<input type="checkbox"/>	458.980	80 mm
<input type="checkbox"/>	458.944	44 mm	<input type="checkbox"/>	458.985	85 mm
<input type="checkbox"/>	458.946	46 mm	<input type="checkbox"/>	458.990	90 mm
<input type="checkbox"/>	458.948	48 mm	<input type="checkbox"/>	458.995	95 mm
<input type="checkbox"/>	458.950	50 mm	<input type="checkbox"/>	458.999	100 mm
<input type="checkbox"/>	458.952	52 mm			

#### 6.0 mm Titanium Locking Screws, with hexagonal recess



	LENGTH		LENGTH		
<input type="checkbox"/>	450.873	30 mm	<input type="checkbox"/>	450.866	70 mm
<input type="checkbox"/>	450.874	35 mm	<input type="checkbox"/>	450.867	75 mm
<input type="checkbox"/>	450.875	40 mm	<input type="checkbox"/>	450.868	80 mm
<input type="checkbox"/>	450.861	45 mm	<input type="checkbox"/>	450.869	85 mm
<input type="checkbox"/>	450.862	50 mm	<input type="checkbox"/>	450.870	90 mm
<input type="checkbox"/>	450.863	55 mm	<input type="checkbox"/>	450.871	95 mm
<input type="checkbox"/>	450.864	60 mm	<input type="checkbox"/>	450.872	100 mm
<input type="checkbox"/>	450.865	65 mm			

◇ Available nonsterile or sterile-packed. Add S to catalog number to order sterile product.  
Synthes is a trademark of Synthes, Inc. or its affiliates.

# Inventory Control Form

## Titanium Cannulated Retrograde/Antegrade Femoral Nail-EX System

### Implants (cont'd)

#### Titanium Cannulated Retrograde Femoral Nails-EX, sterile

##### 9 mm diameter (green)



	LENGTH		LENGTH
<input type="checkbox"/>	04.013.312S 160 mm	<input type="checkbox"/>	04.013.328S 240 mm
<input type="checkbox"/>	04.013.316S 180 mm	<input type="checkbox"/>	04.013.332S 260 mm
<input type="checkbox"/>	04.013.320S 200 mm	<input type="checkbox"/>	04.013.336S 280 mm
<input type="checkbox"/>	04.013.324S 220 mm		

##### 10 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.412S 160 mm	<input type="checkbox"/>	04.013.428S 240 mm
<input type="checkbox"/>	04.013.416S 180 mm	<input type="checkbox"/>	04.013.432S 260 mm
<input type="checkbox"/>	04.013.420S 200 mm	<input type="checkbox"/>	04.013.436S 280 mm
<input type="checkbox"/>	04.013.424S 220 mm		

##### 11 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.512S 160 mm	<input type="checkbox"/>	04.013.528S 240 mm
<input type="checkbox"/>	04.013.516S 180 mm	<input type="checkbox"/>	04.013.532S 260 mm
<input type="checkbox"/>	04.013.520S 200 mm	<input type="checkbox"/>	04.013.536S 280 mm
<input type="checkbox"/>	04.013.524S 220 mm		

##### 12 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.612S 160 mm	<input type="checkbox"/>	04.013.628S 240 mm
<input type="checkbox"/>	04.013.616S 180 mm	<input type="checkbox"/>	04.013.632S 260 mm
<input type="checkbox"/>	04.013.620S 200 mm	<input type="checkbox"/>	04.013.636S 280 mm
<input type="checkbox"/>	04.013.624S 220 mm		

##### 13 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.712S 160 mm	<input type="checkbox"/>	04.013.728S 240 mm
<input type="checkbox"/>	04.013.716S 180 mm	<input type="checkbox"/>	04.013.732S 260 mm
<input type="checkbox"/>	04.013.720S 200 mm	<input type="checkbox"/>	04.013.736S 280 mm
<input type="checkbox"/>	04.013.724S 220 mm		

##### 14 mm diameter (aqua)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.812S 160 mm	<input type="checkbox"/>	04.013.828S 240 mm
<input type="checkbox"/>	04.013.816S 180 mm	<input type="checkbox"/>	04.013.832S 260 mm
<input type="checkbox"/>	04.013.820S 200 mm	<input type="checkbox"/>	04.013.836S 280 mm
<input type="checkbox"/>	04.013.824S 220 mm		

##### 15 mm diameter (aqua)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.912S 160 mm	<input type="checkbox"/>	04.013.928S 240 mm
<input type="checkbox"/>	04.013.916S 180 mm	<input type="checkbox"/>	04.013.932S 260 mm
<input type="checkbox"/>	04.013.920S 200 mm	<input type="checkbox"/>	04.013.936S 280 mm
<input type="checkbox"/>	04.013.924S 220 mm		

#### Titanium Cannulated Retrograde/Antegrade Femoral Nails-EX, sterile

##### 9 mm diameter (green)



	LENGTH		LENGTH
<input type="checkbox"/>	04.013.340S 300 mm	<input type="checkbox"/>	04.013.360S 400 mm
<input type="checkbox"/>	04.013.344S 320 mm	<input type="checkbox"/>	04.013.364S 420 mm
<input type="checkbox"/>	04.013.348S 340 mm	<input type="checkbox"/>	04.013.368S 440 mm
<input type="checkbox"/>	04.013.352S 360 mm	<input type="checkbox"/>	04.013.372S 460 mm
<input type="checkbox"/>	04.013.356S 380 mm	<input type="checkbox"/>	04.013.376S 480 mm

##### 10 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.440S 300 mm	<input type="checkbox"/>	04.013.460S 400 mm
<input type="checkbox"/>	04.013.444S 320 mm	<input type="checkbox"/>	04.013.464S 420 mm
<input type="checkbox"/>	04.013.448S 340 mm	<input type="checkbox"/>	04.013.468S 440 mm
<input type="checkbox"/>	04.013.452S 360 mm	<input type="checkbox"/>	04.013.472S 460 mm
<input type="checkbox"/>	04.013.456S 380 mm	<input type="checkbox"/>	04.013.476S 480 mm

##### 11 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.540S 300 mm	<input type="checkbox"/>	04.013.560S 400 mm
<input type="checkbox"/>	04.013.544S 320 mm	<input type="checkbox"/>	04.013.564S 420 mm
<input type="checkbox"/>	04.013.548S 340 mm	<input type="checkbox"/>	04.013.568S 440 mm
<input type="checkbox"/>	04.013.552S 360 mm	<input type="checkbox"/>	04.013.572S 460 mm
<input type="checkbox"/>	04.013.556S 380 mm	<input type="checkbox"/>	04.013.576S 480 mm

##### 12 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.640S 300 mm	<input type="checkbox"/>	04.013.660S 400 mm
<input type="checkbox"/>	04.013.644S 320 mm	<input type="checkbox"/>	04.013.664S 420 mm
<input type="checkbox"/>	04.013.648S 340 mm	<input type="checkbox"/>	04.013.668S 440 mm
<input type="checkbox"/>	04.013.652S 360 mm	<input type="checkbox"/>	04.013.672S 460 mm
<input type="checkbox"/>	04.013.656S 380 mm	<input type="checkbox"/>	04.013.676S 480 mm

##### 13 mm diameter (green)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.740S 300 mm	<input type="checkbox"/>	04.013.760S 400 mm
<input type="checkbox"/>	04.013.744S 320 mm	<input type="checkbox"/>	04.013.764S 420 mm
<input type="checkbox"/>	04.013.748S 340 mm	<input type="checkbox"/>	04.013.768S 440 mm
<input type="checkbox"/>	04.013.752S 360 mm	<input type="checkbox"/>	04.013.772S 460 mm
<input type="checkbox"/>	04.013.756S 380 mm	<input type="checkbox"/>	04.013.776S 480 mm

##### 14 mm diameter (aqua)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.840S 300 mm	<input type="checkbox"/>	04.013.860S 400 mm
<input type="checkbox"/>	04.013.844S 320 mm	<input type="checkbox"/>	04.013.864S 420 mm
<input type="checkbox"/>	04.013.848S 340 mm	<input type="checkbox"/>	04.013.868S 440 mm
<input type="checkbox"/>	04.013.852S 360 mm	<input type="checkbox"/>	04.013.872S 460 mm
<input type="checkbox"/>	04.013.856S 380 mm	<input type="checkbox"/>	04.013.876S 480 mm

##### 15 mm diameter (aqua)

	LENGTH		LENGTH
<input type="checkbox"/>	04.013.940S 300 mm	<input type="checkbox"/>	04.013.960S 400 mm
<input type="checkbox"/>	04.013.944S 320 mm	<input type="checkbox"/>	04.013.964S 420 mm
<input type="checkbox"/>	04.013.948S 340 mm	<input type="checkbox"/>	04.013.968S 440 mm
<input type="checkbox"/>	04.013.952S 360 mm	<input type="checkbox"/>	04.013.972S 460 mm
<input type="checkbox"/>	04.013.956S 380 mm	<input type="checkbox"/>	04.013.976S 480 mm

# Inventory Control Form

## Titanium Cannulated Retrograde/Antegrade Femoral Nail-EX System

### Implants (cont'd)

#### Titanium End Caps with T40 StarDrive, for Femoral Nails-EX <sup>◇</sup>



		EXTENSION
<input type="checkbox"/>	04.003.000	0 mm
<input type="checkbox"/>	04.003.001	5 mm
<input type="checkbox"/>	04.003.002	10 mm
<input type="checkbox"/>	04.003.003	15 mm
<input type="checkbox"/>	04.003.004	20 mm

#### Titanium End Cap T40 StarDrive, for Retrograde Femoral Nails-EX Spiral Blade <sup>◇</sup>



		EXTENSION
<input type="checkbox"/>	04.013.000	0 mm

#### Titanium Spiral Blades, for Titanium Retrograde Femoral Nails-EX <sup>◇</sup>



	LENGTH		LENGTH		
<input type="checkbox"/>	04.013.041	45 mm	<input type="checkbox"/>	04.013.047	75 mm
<input type="checkbox"/>	04.013.042	50 mm	<input type="checkbox"/>	04.013.048	80 mm
<input type="checkbox"/>	04.013.043	55 mm	<input type="checkbox"/>	04.013.049	85 mm
<input type="checkbox"/>	04.013.044	60 mm	<input type="checkbox"/>	04.013.050	90 mm
<input type="checkbox"/>	04.013.045	65 mm	<input type="checkbox"/>	04.013.051	95 mm
<input type="checkbox"/>	04.013.046	70 mm	<input type="checkbox"/>	04.013.052	100 mm

### Instruments

#### Guide Wire

03.010.115 3.2 mm, 290 mm long

#### Drill Bits—Cannulated <sup>◇</sup>



351.27 13.0 mm, 300 mm  
 03.010.034 13.0 mm, flexible, large quick coupling, 465 mm

#### Drill Bits—Three-Fluted <sup>◇</sup>



03.010.061 4.2 mm, quick coupling, 330 mm, 100 mm calibration  
 03.010.062 5.0 mm, quick coupling, 330 mm, 100 mm calibration  
 03.010.101 4.2 mm, quick coupling, needle point, 145 mm for Radiolucent Drive  
 03.010.102 5.0 mm, quick coupling, needle point, 145 mm for Radiolucent Drive  
 03.010.104 4.2 mm, quick coupling, needle point, 145 mm  
 03.010.105 5.0 mm, quick coupling, needle point, 145 mm

#### Reaming Rods



351.706S 2.5 mm, with ball tip, 950 mm, sterile  
 351.708S 2.5 mm, with ball tip, 1150 mm, sterile  
 351.707S 2.5 mm, with ball tip and extension, 950 mm, sterile

#### Guide Rod <sup>◇</sup>

355.041 3.0 mm, with smooth tip, 950 mm