

INVENTORY CONTROL FORM

Variable Angle Locking Hand System 316L Stainless Steel

Case Information (eg, Case ID):

To order (USA): 800-523-0322
To order (Canada): 800-946-8999

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Stainless Steel Implants

1.3 mm Locking Plates^o

<input type="checkbox"/>	02.130.150	Straight Plate, 6 holes
<input type="checkbox"/>	02.130.151	Straight Plate, 12 holes
<input type="checkbox"/>	02.130.152	T-Plate, 3 holes head, 5 holes shaft
<input type="checkbox"/>	02.130.153	Y-Plate, 3 holes head, 5 holes shaft
<input type="checkbox"/>	02.130.154	Phalangeal Base Plate, 2 holes head, 5 holes shaft
<input type="checkbox"/>	02.130.156	Phalangeal Head Plate, right
<input type="checkbox"/>	02.130.157	Phalangeal Head Plate, left
<input type="checkbox"/>	02.130.158	Strut Plate, 8 holes, oblique, right
<input type="checkbox"/>	02.130.159	Strut Plate, 8 holes, oblique, left
<input type="checkbox"/>	02.130.161	Web Plate, 14 holes

1.5 mm Variable Angle Locking Plates^o

<input type="checkbox"/>	02.130.250	Straight Plate, 6 holes
<input type="checkbox"/>	02.130.251	Straight Plate, 12 holes
<input type="checkbox"/>	02.130.252	T-Plate, 3 holes head, 7 holes shaft
<input type="checkbox"/>	02.130.253	Y-Plate, 3 holes head, 7 holes shaft
<input type="checkbox"/>	02.130.254	Phalangeal Base Plate, 2 holes head, 6 holes shaft
<input type="checkbox"/>	02.130.255	Condylar Plate, 2 holes head, 6 holes shaft
<input type="checkbox"/>	02.130.256	Phalangeal Head Plate, right
<input type="checkbox"/>	02.130.257	Phalangeal Head Plate, left
<input type="checkbox"/>	02.130.258	Strut Plate, 8 holes, oblique, right
<input type="checkbox"/>	02.130.259	Strut Plate, 8 holes, oblique, left
<input type="checkbox"/>	02.130.260	Strut Plate, 12 holes
<input type="checkbox"/>	02.130.261	Web Plate, 14 holes
<input type="checkbox"/>	02.130.262	Box Plate, 4 holes
<input type="checkbox"/>	02.130.263	First Metacarpal Plate, dorsal
<input type="checkbox"/>	02.130.264	First Metacarpal Plate, lateral, right
<input type="checkbox"/>	02.130.265	First Metacarpal Plate, lateral, left
<input type="checkbox"/>	02.130.266	Rotation Correction Plate, 6 holes
<input type="checkbox"/>	02.130.267	Fracture Plate, 6 holes
<input type="checkbox"/>	02.130.268	Metacarpal Neck Plate

2.0 mm Variable Angle Locking Plates^o

<input type="checkbox"/>	02.130.350	Straight Plate, 6 holes
<input type="checkbox"/>	02.130.351	Straight Plate, 12 holes
<input type="checkbox"/>	02.130.352	T-Plate, 3 holes head, 7 holes shaft
<input type="checkbox"/>	02.130.353	Y-Plate, 3 holes head, 7 holes shaft
<input type="checkbox"/>	02.130.354	Phalangeal Base Plate, 2 holes head, 6 holes shaft
<input type="checkbox"/>	02.130.355	Condylar Plate, 2 holes head, 6 holes shaft
<input type="checkbox"/>	02.130.360	Strut Plate, 12 holes
<input type="checkbox"/>	02.130.362	Box Plate, 4 holes
<input type="checkbox"/>	02.130.363	First Metacarpal Plate, dorsal
<input type="checkbox"/>	02.130.366	Rotation Correction Plate, 6 holes
<input type="checkbox"/>	02.130.367	Fracture Plate, 6 holes

1.0 mm Cortex Screws, self-tapping, cruciform

	LENGTH	
<input type="checkbox"/>	200.526	6 mm
<input type="checkbox"/>	200.527	7 mm
<input type="checkbox"/>	200.528	8 mm
<input type="checkbox"/>	200.529	9 mm
<input type="checkbox"/>	200.530	10 mm
<input type="checkbox"/>	200.531	11 mm
<input type="checkbox"/>	200.532	12 mm
<input type="checkbox"/>	200.533	13 mm
<input type="checkbox"/>	200.534	14 mm

1.3 mm Cortex Screws, self-tapping with T4 STARDRIVE™ Recess

	LENGTH	
<input type="checkbox"/>	02.130.004	4 mm
<input type="checkbox"/>	02.130.005	5 mm
<input type="checkbox"/>	02.130.006	6 mm
<input type="checkbox"/>	02.130.007	7 mm
<input type="checkbox"/>	02.130.008	8 mm
<input type="checkbox"/>	02.130.009	9 mm
<input type="checkbox"/>	02.130.010	10 mm
<input type="checkbox"/>	02.130.011	11 mm
<input type="checkbox"/>	02.130.012	12 mm
<input type="checkbox"/>	02.130.013	13 mm
<input type="checkbox"/>	02.130.014	14 mm
<input type="checkbox"/>	02.130.015	15 mm
<input type="checkbox"/>	02.130.016	16 mm
<input type="checkbox"/>	02.130.018	18 mm




^oAvailable non-sterile or sterile packed. Add "S" to catalog number to order sterile product.

INVENTORY CONTROL FORM

Variable Angle Locking Hand System 316L Stainless Steel

Stainless Steel Implants (cont'd)

1.3 mm Locking Screws, self-tapping with T4 STARDRIVE™ Recess

		LENGTH	
<input type="checkbox"/>	02.130.104	4 mm	
<input type="checkbox"/>	02.130.105	5 mm	
<input type="checkbox"/>	02.130.106	6 mm	
<input type="checkbox"/>	02.130.107	7 mm	
<input type="checkbox"/>	02.130.108	8 mm	
<input type="checkbox"/>	02.130.109	9 mm	
<input type="checkbox"/>	02.130.110	10 mm	
<input type="checkbox"/>	02.130.111	11 mm	
<input type="checkbox"/>	02.130.112	12 mm	
<input type="checkbox"/>	02.130.113	13 mm	
<input type="checkbox"/>	02.130.114	14 mm	
<input type="checkbox"/>	02.130.115	15 mm	
<input type="checkbox"/>	02.130.116	16 mm	
<input type="checkbox"/>	02.130.118	18 mm	


1.5 mm Cortex Screws, self-tapping with T4 STARDRIVE Recess

		LENGTH	
<input type="checkbox"/>	02.214.104	4 mm	
<input type="checkbox"/>	02.214.105	5 mm	
<input type="checkbox"/>	02.214.106	6 mm	
<input type="checkbox"/>	02.214.107	7 mm	
<input type="checkbox"/>	02.214.108	8 mm	
<input type="checkbox"/>	02.214.109	9 mm	
<input type="checkbox"/>	02.214.110	10 mm	
<input type="checkbox"/>	02.214.111	11 mm	
<input type="checkbox"/>	02.214.112	12 mm	
<input type="checkbox"/>	02.214.113	13 mm	
<input type="checkbox"/>	02.214.114	14 mm	
<input type="checkbox"/>	02.214.115	15 mm	
<input type="checkbox"/>	02.214.116	16 mm	
<input type="checkbox"/>	02.214.118	18 mm	
<input type="checkbox"/>	02.214.120	20 mm	
<input type="checkbox"/>	02.214.122	22 mm	
<input type="checkbox"/>	02.214.124	24 mm	

1.5 mm Variable Angle Locking Screws, self-tapping with T4 STARDRIVE Recess

		LENGTH	
<input type="checkbox"/>	02.130.204	4 mm	
<input type="checkbox"/>	02.130.205	5 mm	
<input type="checkbox"/>	02.130.206	6 mm	
<input type="checkbox"/>	02.130.207	7 mm	
<input type="checkbox"/>	02.130.208	8 mm	
<input type="checkbox"/>	02.130.209	9 mm	
<input type="checkbox"/>	02.130.210	10 mm	
<input type="checkbox"/>	02.130.211	11 mm	
<input type="checkbox"/>	02.130.212	12 mm	
<input type="checkbox"/>	02.130.213	13 mm	
<input type="checkbox"/>	02.130.214	14 mm	
<input type="checkbox"/>	02.130.215	15 mm	
<input type="checkbox"/>	02.130.216	16 mm	
<input type="checkbox"/>	02.130.218	18 mm	
<input type="checkbox"/>	02.130.220	20 mm	
<input type="checkbox"/>	02.130.222	22 mm	
<input type="checkbox"/>	02.130.224	24 mm	

2.0 mm Cortex Screws, self-tapping with T6 STARDRIVE Recess

		LENGTH	
<input type="checkbox"/>	201.356.97	6 mm	
<input type="checkbox"/>	201.357.97	7 mm	
<input type="checkbox"/>	201.358.97	8 mm	
<input type="checkbox"/>	201.359.97	9 mm	
<input type="checkbox"/>	201.360.97	10 mm	
<input type="checkbox"/>	201.361.97	11 mm	
<input type="checkbox"/>	201.362.97	12 mm	
<input type="checkbox"/>	201.363.97	13 mm	
<input type="checkbox"/>	201.364.97	14 mm	
<input type="checkbox"/>	201.365.97	15 mm	
<input type="checkbox"/>	201.366.97	16 mm	
<input type="checkbox"/>	201.368.97	18 mm	
<input type="checkbox"/>	201.370.97	20 mm	
<input type="checkbox"/>	201.372.97	22 mm	
<input type="checkbox"/>	201.374.97	24 mm	

2.0 mm Variable Angle Locking Screws, self-tapping with T6 STARDRIVE Recess

		LENGTH	
<input type="checkbox"/>	02.130.306	6 mm	
<input type="checkbox"/>	02.130.307	7 mm	
<input type="checkbox"/>	02.130.308	8 mm	
<input type="checkbox"/>	02.130.309	9 mm	
<input type="checkbox"/>	02.130.310	10 mm	
<input type="checkbox"/>	02.130.311	11 mm	
<input type="checkbox"/>	02.130.312	12 mm	
<input type="checkbox"/>	02.130.313	13 mm	
<input type="checkbox"/>	02.130.314	14 mm	
<input type="checkbox"/>	02.130.315	15 mm	
<input type="checkbox"/>	02.130.316	16 mm	
<input type="checkbox"/>	02.130.318	18 mm	
<input type="checkbox"/>	02.130.320	20 mm	
<input type="checkbox"/>	02.130.322	22 mm	
<input type="checkbox"/>	02.130.324	24 mm	
<input type="checkbox"/>	02.130.326S†	26 mm, sterile	
<input type="checkbox"/>	02.130.328S†	28 mm, sterile	
<input type="checkbox"/>	02.130.330S†	30 mm, sterile	

†Available sterile only.

INVENTORY CONTROL FORM

Variable Angle Locking Hand System 316L Stainless Steel

Instruments

1.0 mm Drill Bits



<input type="checkbox"/>	03.130.100	K-Wire Attachment for threaded hole
<input type="checkbox"/>	03.130.101	Stryker J-Latch for threaded hole
<input type="checkbox"/>	03.130.102	Mini Quick Coupling for threaded hole

1.3 mm Drill Bits



<input type="checkbox"/>	03.130.110	K-Wire Attachment for gliding hole
<input type="checkbox"/>	03.130.111	Stryker J-Latch for gliding hole
<input type="checkbox"/>	03.130.112	Mini Quick Coupling for gliding hole

1.1 mm Drill Bits



<input type="checkbox"/>	03.130.200	K-Wire Attachment for threaded hole
<input type="checkbox"/>	03.130.201	Stryker J-Latch for threaded hole
<input type="checkbox"/>	03.130.202	Mini Quick Coupling for threaded hole

1.5 mm Drill Bits



<input type="checkbox"/>	03.130.210	K-Wire Attachment for gliding hole
<input type="checkbox"/>	03.130.211	Stryker J-Latch for gliding hole
<input type="checkbox"/>	03.130.212	Mini Quick Coupling for gliding hole



<input type="checkbox"/>	03.130.300	K-Wire Attachment for threaded hole
<input type="checkbox"/>	03.130.301	Stryker J-Latch for threaded hole
<input type="checkbox"/>	03.130.302	Mini Quick Coupling for threaded hole

2.0 mm Drill Bits



<input type="checkbox"/>	03.130.310	K-Wire Attachment for gliding hole
<input type="checkbox"/>	03.130.311	Stryker J-Latch for gliding hole
<input type="checkbox"/>	03.130.312	Mini Quick Coupling for gliding hole

0.8 mm Drill Bits



<input type="checkbox"/>	03.130.000	K-Wire Attachment for threaded hole, 64 mm
<input type="checkbox"/>	316.385	Mini Quick Coupling for threaded hole, 47 mm
<input type="checkbox"/>	316.494	Stryker J-Latch for threaded hole, 56 mm

0.76 mm Drill Bits, mini quick coupling



<input type="checkbox"/>	316.286	with 6 mm stop
<input type="checkbox"/>	316.288	with 8 mm stop
<input type="checkbox"/>	316.290	with 10 mm stop
<input type="checkbox"/>	316.292	with 12 mm stop
<input type="checkbox"/>	316.294	with 14 mm stop

0.76 mm Drill Bits, Stryker J-Latch



<input type="checkbox"/>	316.306	with 6 mm stop
<input type="checkbox"/>	316.308	with 8 mm stop
<input type="checkbox"/>	316.310	with 10 mm stop
<input type="checkbox"/>	316.312	with 12 mm stop
<input type="checkbox"/>	316.314	with 14 mm stop

Kirschner Wires



<input type="checkbox"/>	292.06	0.6 mm K-Wire, with trocar point, 70 mm
<input type="checkbox"/>	292.08	0.8 mm K-Wire, with trocar point, 70 mm
<input type="checkbox"/>	292.10	1.0 mm K-Wire, with trocar point, 150 mm
<input type="checkbox"/>	292.12	1.25 mm K-Wire, with trocar point, 150 mm



Manufactured or distributed by:

Synthes USA Products, LLC
1302 Wrights Lane East
West Chester, PA 19380

Synthes USA, LLC
1101 Synthes Avenue
Monument, CO 80132

To order (USA): 800-523-0322
To order (Canada): 800-946-8999

Note: For recognized manufacturer, refer to the product label.

www.depuysynthes.com

© DePuy Synthes 2018. All rights reserved.
VAHANDICF5S001v1