



REPLACEMENT

220 SERIES

with argon gas all glazing saves ene warm air inside in

The Vinyl Replacement Window 220 is offered with a LoE glass option. LoE highperformance glass with argon gas allows light to filter in while keeping the sun's harmful rays out. In addition, this special glazing saves energy and reduces utility costs by keeping the cool air inside in the summer and the warm air inside in the winter.

### **FEATURES**

- 3" main frame beveled exterior profile gives an outstanding, bold appearance.
- Tilt-in sash for easy cleaning.
- Block and tackle balance system for long-lasting, smooth, quiet operation.
- 3/4" LoE E66 Environsealed Windows™, environmentally friendly with warm-edge spacer reduces thermal loss.
  Type and look of warm-edge spacer may vary.
- Ventilation control for opening windows only 4".
- Metal-reinforced center bar for better structural performance and weather tightness.
- Multi-chambered design for structural integrity, superior thermal performance, maintenance-free, vinyl frame and sash extrusions.

Note: All picture windows, shapes and one-frame glass larger than 30 square feet will come with Tempered Glass as standard for safety reasons. All additional charges for Tempered Glass will automatically be applied.

### **OPTIONS**

- Argon-enhanced glass improves energy efficiency.
- The Replacement 220 is available with an integral nail fin.
- Tempered glass, rain glass, obscure glass.
- Factory mulls (combined units) with continuous head and sill.
- \* Units are made in 1/4" increments, plus or minus 1/8". Order 1/4" less than smallest measurement.

## CARDINALIG **\***

# **COLOR OPTIONS**







# PERFORMANCE DATA

Single Hung, Picture, and Sliding Windows – 220 Series									
Glass Dual 3/4" OA Insulated		e Hung/: SHGC	Slider VT		ure Win			ng Win SHGC	
E66 LoE air no grilles	.35	.20	.45	.32	.21	.48	.33	.20	.45
E66 LoE air w/ grilles	.35	.22	.51	.34	.24	.54	.33	.22	.51
E66 LoE argon no grilles	.31	.20	.45	.28	.21	.48	.31	.20	.45
E66 LoE argon w/ grilles	.31	.22	.51	.28	.23	.54	.31	.22	.51

Check local jurisdictions for current energy codes. Standard windows meet or exceed 2016 Texas Adopted State Energy Code.

For information about measuring & installing Krestmark Collection windows, visit our website: WestlakeRoyalWindows.com

3950 Bastille Road, Suite 100 • Dallas, TX 75212 • PH: 214.237.5055





ONE LITE



3/4" PRAIRIE



3/4" COLONIAL



1-1/8" SIMULATED DIVIDED LITE



GRILLE BETWEEN







