

9130 UTENSIL WASHER Technical specification



POWER / CONNECTIONS

Electrical

Electrical connection 3N 60Hz 240/480, PE Effect 16.5 kW

Heating Elements

Wash tank 1x4.5 kW Rinse Tank 2x6.0 kW

Fuses

240 volt Max 50 amp 480 volt Max 50 amp

Motor safety Yes

Wash pump motor horsepower 2-2.7 kW

Water

Connection ½ inch.

Pressure 45 to 60 psi

Consumption per cycle 2.1 gallons

Temperature: (minimum) 122° F (50 °C)

Drain

Drain dimension: 1 ½ inch

Rinse Temperature: 183° F (84° C) Rinse Time: 25 seconds

Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 2-2.7 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump

Optional features

- Automatic hood opener
- Soap dosage pump
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity 33 gallons

Wash area

 $H \times W \times D$ 25x50x25 inch

Overall dimensions

Electrical connection

H x W x D 64x57x29 inch H x W x D with hood open 82x57x29 inch

8 feet

Weight Shipping 550 lbs
Weight installed 825 lbs
Water connection, flexible 8 feet

Vinyl brush, daily maintenance 1 piece



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE