

## Technical specification



Temperature: 183° F (84° C)  
 Rinse Time: 25 seconds

### Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 1-2.0, 1-2.7 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- 2 tray racks

### Optional features

- Automatic hood opener
- Soap dosage pump
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

### General specification

Wash tank capacity	25 gallons
Wash area	
H x W x D	25x39x25 inch
Overall dimensions	
H x W x D	64x46x29 inch
H x W x D with hood open	82x46x29 inch
Weight Shipping	495 lbs
Weight installed	704 lbs
Water connection, flexible	8 feet
Electrical connection	8 feet
Vinyl brush, daily maintenance	1 piece

### POWER / CONNECTIONS

#### Electrical

Electrical connection	3N 60Hz 208/230 PE
Effect	16.5 kW
Heating Elements	

Wash tank	1x4.5 kW
Rinse Tank	2x6.0 kW

Fuses	
208/230/240 volt	Max 50 amp
480 volt	Max 50 amp
Motor safety	Yes
Wash pump motor horsepower	2-2.0 kW

#### Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	2.1 gallons
Temperature: (minimum)	122° F (50 C°)

#### Drain

Drain dimension:	1 ½ inch
------------------	----------

#### Rinse



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE