



100%
MADE IN ITALY



LINDHAUS[®]
QUALITY CLEANING EQUIPMENT

P R O F E S S I O N A L L I N E



LW30-38pro 
LW30pro L-ion



LW30pro
LW38pro

LW30pro
L-ion

Advanced, innovative, multifunction floor scrubber driers

STRENGTHS

- › Lightweight 10,2 - 10,6 Kg (under 25.1 pounds)
- › The lightest weight for the operator 1,3 Kg (2.8 lbs)
- › The world lowest profile 14 cm (5.5 in)
- › Carpet cleaner (LW30pro)
- › Injection / extraction
- › Window cleaner
- › Minimum consumption of water and detergents

LW30pro L-ion

- › Light, only 11,4 Kg
- › Replaceable lithium-ion battery (36V - 6Ah)
- › Autonomy 20 min. - Charging time 90 min.
- › Great flexibility and practicality

Cleans and dries in record time!



THE WORLDS LOWEST PROFILE

The base height is only 14 cm (5.5 in.) and allows easy access under low

FLOOR CLEANING

Lindhaus LW30-38pro is the perfect machine for cleaning hard floor surfaces ranging from the roughest to the most delicate. Its versatility along with the low profile base and the sleek upright body make it effortless to use with sparkling results. The floor remains perfectly dry allowing you to use the cleaned area immediately. The cleaning components, squeegees and roller can be easily removed without any tools for a quick rinse after using the machine.

furniture. The remarkable inclination of the vertical suction body 65 cm (2.1 ft.) allows total access under tables.

LIGHT HANDLE WEIGHT

The brush motor is located in the base and the high efficiency by-pass vacuum motor is positioned in the rotation axis of the vertical body thus providing the user with a handle weight of only 1,3 Kg (2.6 lbs), with a full tank.



Hard work, long drying time
and ineffective cleaning?

No thanks!

LW30-38pro is the solution

LONG CLEANING CYCLE

The clean water/cleaning solution tank holds 2,6 liters allowing a full 9 minutes of cleaning time per tank. The 4 non marking rubber wheels and the brush pressure adjustment allow the machine to be used on polished or uneven floors.

INTEGRATED TANKS

The clean and soiled water tanks are integrated in one unique container. With a simple movement you release the tank, empty the soiled water and refill it with ordinary tap water and fresh cleaning solution.

DETERGENT DOSES

The tank cap is also a dispensing device for your cleaning solutions. Just 1% of the Lindhaus detergent is all you need for thorough cleaning. The impact on the environment is kept to a bare minimum. The LW Pro requires 10 times less water and cleaning solution than any manual or mechanical washing system available on the market today.

ELECTRICAL CONTROL

A sophisticated electronic control, which allows the gradual start of the brush motor, keeps the 1800 RPM's perfectly steady. It also controls the overload, indicated by the two lights, and provides the correct brush pressure which is adjustable using the knob shown in the photo.

EASY BRUSH REPLACEMENT

The brush can be changed without any tools and takes only a few seconds. Just unhook the side support and remove the brush from underneath.

QUICK CONNECTION

Located on the back of the machine there is a quick connection which provides the injection/extraction function. The lower cord hook is located on the transport handle.

UPHOLSTERY AND WINDOW CLEANING

With an ergonomically designed accessory it is possible to deep clean fabrics such as car seats, sofas and chairs. Also available is the window cleaning kit which is also great for cleaning stairs and hard to reach areas. (both are optional)

CLEANING CARPETS AND RUGS

When the LW30pro is equipped with the optional carpet nozzle, soft bristle brush roller and the textile detergent it becomes an excellent (low pile, commercial grade) carpet cleaner.

TOTAL PROTECTION

The machine is equipped with a front bumper in soft rubber and 4 rubber side rolls. This prevents damage to furniture and allows you to clean close to the wall on both sides without marks.

EASILY MANEUVERABLE

The machine runs smooth and easy on its 4 rubber wheels. The brush is kept uniformly wet by a set of injectors. There are several brush types available for different floor surfaces and cleaning needs. The suction is perfect in both directions thanks to the two squeegee nozzles working simultaneously.

EASY TO TRANSPORT

The four rubber wheels, and the ability to tilt the machine, allow you to move it from one place to another with ease. The extremely light weight and comfortable handles make it easy to lift and transport the machine up or down stairs and to load it into a vehicle.





APPLICATION FIELDS

LW30-LW38pro can operate on any type of hard floor with spaces from 50 to 500 m². On the side we show just a few areas suitable for this machine: restaurants, hotels, shops, offices, bakeries, butcher shops, restaurants kitchens, schools, surgery rooms, beauty centers.



FUNCTIONS

All the machine's motors functions are located on the wand and can be independently controlled by the touch of a finger.

DETERGENTS

Lindhaus has developed a line of completely foam free concentrated detergents for use with the LW30-38pro:

Neutrolux: neutral, self polishing and lightly scented floor cleaner, and maintainer

Actiplus: universal floor decreasing detergent

Textile: lightly scented deodorant, detergent for textiles and upholstery

ROLLERS

LW30-38pro has no limits when it comes to the perfect cleaning of any hard surfaces: marble, wood, ceramic, resin, quartz etc.

The brush pressure is adjustable. A large selection of brushes or abrasive disks are available to handle any type of job from delicate to difficult.

The company Lindhaus srl reserves its right to make any modifications without any prior notice.

TECHNICAL DATA

	LW30pro	LW38pro	LW30pro L-ion
Input power (W)	1100	1100	550
Water lift mm/H ₂ O (in/H ₂ O)	2000 (78.7)	2000 (78.7)	1000 (39.4)
Air volume lt/sec (CFM)	46 (95.5)	46 (95.5)	26 (54)
Brush motor (W)	250	250	180
Brush roller constant speed (rpm)	1800	1800	1500
Electronic overload control	Standard	Standard	Standard
Cylindrical brush D/L mm (in)	72/255 (2.8/10)	72/335 (2.8/13.2)	72/255 (2.8/10)
Suction width mm (in)	280 (11)	358 (14)	280 (11)
Solution Tank (lt.)	2.6	2.6	2.6
Recovery tank (lt.)	2.6	2.6	2.6
Working capacity m ² /h (sq.ft/h)	250 (2600)	320 (3400)	300 (3200)
Water dosing	Pump	Pump	Solenoid valve
Working time per tank (min)	9	9	15
Base height mm (in)	140 (5.5)	140 (5.5)	140 (5.5)
Total weight Kg (lb)	10.2 (22.5)	10.6 (23.3)	11.4 (25.1) with batt.
Handle weight Kg (lb)	1.3 (2.8)	1.3 (2.8)	1.9 (4.2)
Cord length mt. (ft)	10 (41)	10 (41)	-
Noise level db (A)	74	74	69
Sealing protection	IPX 4	IPX 4	IPX 4



APPROVALS:



HEADQUARTERS › LINDHAUS SRL

Via Belgio, 22 Z.I. 35127 › Padova, ITALY
tel. +39 0498700307 › fax +39 049 8700605
vacuum@lindhaus.it › www.lindhaus.it

LINDHAUS USA

Minneapolis › Minnesota USA
info@lindhaus.com › www.lindhaus.com

DISTRIBUTOR / DEALER