

AXIS Companion Line

AXIS Companion VMS

Video Surveillance
made simple

Up to 16 cameras per site,
with multisite support



Go simple! Wireless solution


Easiest set-up for one or two cameras.
Recording on AXIS Companion Card 64 GB
with 1 week retention time.



0895-003 AXIS Companion Dome WV inc. SD card
0892-003 AXIS Companion Cube LW inc. SD card

Go flexible! Switch and SD card solution

Cameras for surveillance indoors or out,
day or night. Up to 4 cameras per PoE
switch, recording on SD cards with 1 week
retention time.



5801-353 AXIS Companion Switch 4CH
5801-941 AXIS Companion Card 64 GB

Go scalable! Recorder solution

Extended recording and ready to scale with changing needs. Up to 8
cameras per recorder and 1 to 2 months retention time.

0832-003 AXIS Companion Recorder 8CH 2TB
0893-003 AXIS Companion Recorder 8CH 4TB
01035-003 AXIS Companion Recorder 4CH 1 TB

AXIS Companion video management software.
Download the free PC-client and mobile app for iOS or Android from
www.axiscompanion.com/vms



AXIS Companion Dome

AXIS Companion Cube

AXIS Companion Eye

AXIS Companion Bullet

	-V		-WV		-L		-LW		-L		-LVE		-LE			
Max. video resolution (pixels)	1920x1080 (2 MP)				1920x1080 (2 MP)				1920x1080 (2 MP)				1920x1080 (2 MP)			
Horizontal angle of view	106°				110°				115°				115°			
Day and night	No				Yes				Yes				Yes			
Min. illumination (lux)	0.25				0.25 (Color) 0.05 (B/W) 0 with IR on				0.2 (Color) 0.04 (B/W) 0 with IR on				0.2 (Color) 0.04 (B/W) 0 with IR on			
Power	PoE IEEE 802.3af/802.3at Class 1		Micro USB for DC power		PoE IEEE 802.3af/802.3at Class 2		Micro USB for DC power		PoE IEEE 802.3af/802.3at Class 2		PoE IEEE 802.3af/802.3at Class 2		PoE IEEE 802.3af/802.3at Class 2			
Outdoor ready	No IP42 water and dust resistant, IK08-rated				No				No IP42 water and dust resistant		Yes IP66-, NEMA 250 Type 4X and IK08-rated		Yes IP66-, NEMA 250 Type 4X and IK08-rated			
Other	HDMI output (micro), Zipstream, Memory card slot, WDR, Corridor format				IR illumination, Built-in PIR sensor, Built-in microphone, Built-in speaker, Zipstream, Memory card slot, WDR, Corridor format				IR illumination, Zipstream, Memory card slot, WDR, Corridor format				IR illumination, Zipstream, Memory card slot, WDR, Corridor format			
Wireless interface	N/A		IEEE 802.11 a/b/g/n, support for Wi-Fi Protected Setup™		N/A		IEEE 802.11 a/b/g/n, support for Wi-Fi Protected Setup™		N/A		N/A		N/A			
Part number	0894-001		0895-003		0891-001		0892-003		0881-001		0880-001		0959-001			