

Fusion

Perforated or Non-Perforated Ceiling & Wall Panels

Fusion acoustic ceiling and wall panels feature wood-veneer face, either in flat panels or with a variety of perforation options. Standard perforations are available in 4mm, 6mm, and 8mm diameter holes spaced 16mm or 32mm on center in both square and diamond patterns. Custom diameter, spacing, and patterns are available, as well as slotted designs. For projects requiring sound absorption, acoustical backer may be installed above Fusion ceiling or behind Fusion wall panels.

FEATURES

APPEARANCE & COLOR

Available in wood veneer in the species shown below*
Standard perforations in 4mm, 6mm, and 8mm diameter
Slotted and custom perforations available
Perforation spacing: 16mm and 32mm O.C., typical square
or diamond pattern, or slotted patterns
FSC available
May contribute LEED® projects
FINISHES: Lacquer top coat or stained to match

CORE / FIRE RATING

Available core materials are: Class A Fire Rated Particle Board Class A Fire Rated MDF

Touch-up finish available for field application

ACOUSTICAL ABSORPTION

Acoustically absorptive when perforated - NRC varies based on the hole pattern

Soundtex applied to back of perforated panels for acoustical absorption

Optional features for sound control:

Acoustical backer available in 1" and 2"

SIZES

Standard Fusion flat or Fusion perforated: 3/4" thickness 2' x 2', 2 x 4', 2' x 6', 2' x 8'



MOUNTING OPTIONS

Ceilings: Lay-in or tegular lay-in; torsion spring Walls: Z-clip / Z-bar

MODULARS















COLOR CHART



^{*}Different species may increase production lead time. Natural wood products vary in color and grain. Due to differences in printing, actual color may differ from images above.











