Methods

Chloride is the most common inorganic anion found in water and wastewater. The Maximum Secondary Contaminant Level for drinking water for chloride is 250 mg/L. Natural sources of salt are the ocean and various salt deposits above and below ground.

Chloride is very corrosive to most metals in systems with elevated pressures and temperatures such as boilers and oil-drilling equipment.

The Mercuric Nitrate Method

References: APHA Standard Methods, 22nd ed., Method 4500-Cl⁻ C - 1997. ASTM D 512-04, Chloride Ion in Water, Test Method A. USEPA Methods for Chemical Analysis of Water and Wastes, Method 325.3 (1983).

CHEMetrics employs a mercuric nitrate titrant in acid solution with diphenylcarbazone as the end point indicator. Results are expressed as ppm (mg/L) Cl⁻.

The Ferric Thiocyanate Method

References: APHA Standard Methods, 22nd ed., Method 4500-Cl⁻ E - 1997. D. Zall, D. Fisher, M. Garner, "Photometric Determination of Chlorides in Water," *Analytical Chemistry*, Vol 28, No. 11, pp. 1665-1668, November 1956. J. O'Brien, "Automatic Analysis of Chlorides in Sewage," *Wastes Engineering*, pp. 670-672, December 1962.

The Chloride Vacu-vials® test employs the ferric thiocyanate chemistry. Chloride reacts with mercuric thiocyanate to liberate thiocyanate ion. Ferric ion reacts with thiocyanate ion to produce an orange-brown thiocyanate complex in proportion to the chloride concentration. Results are expressed as ppm (mg/L) Cl⁻.



Range: 20-200 ppm

MDL: 20 ppm / Method: Mercuric Nitrate

Cat#

Titrets Kit, Shelf-life 20 months

*K-2020

Increments:

20, 22, 24, 26, 28, 30, 32, 36, 40, 50, 60, 70, 80, 100, 140, 200 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, Activator Solution, titrettor, 25 mL sample cup and instructions.

Range: 50-500 ppm

MDL: 50 ppm / Method: Mercuric Nitrate

Cat#

Titrets Kit, Shelf-life 20 months

*K-2050

Increments

50, 55, 60, 65, 70, 75, 80, 90, 100, 125, 150, 175, 200, 250, 350, 500 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, Activator Solution, titrettor, 25 mL sample cup and instructions.

Range: 250-2500 ppm

MDL: 250 ppm / Method: Mercuric Nitrate

Cat#

Titrets Kit, Shelf-life 20 months

*K-2051

Increments:

250, 275, 300, 325, 350, 375, 400, 450, 500, 625, 750, 875, 1000, 1250, 1750, 2500 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, Activator Solution, titrettor, 25 mL sample cup and instructions.



^{*}Contains mercury. Dispose according to local, state or federal laws.

Cat#

A-0013

A-0023

A-0027

A-0053

A-0063

Range: 1000-10,000 ppm MDL: 1000 ppm / Method: Mercuric Nitrate

Cat#

Titrets Kit, Shelf-life 20 months

*K-2055

1000, 1100, 1200, 1300, 1400, 1500, 1600, 1800, 2000, 2500, 3000, 3500, 4000, 5000, 7000, 10,000 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, Activator Solution, titrettor, 25 mL sample cup and instructions.

Instructions and MSDS(s) are posted on our website.

Kit Components common to Chloride

Description

Sample Cup Pack, 25 mL (6 ea)

Ampoule Blank Pack (5 ea) Syringe Pack, 1.0 mL (6 ea)

Syringe Pack, 3.0 mL (6 ea)

Titrettor Pack (1 ea)

If no shelf-life is listed for a product, then the shelf-life is at least 2 years.

Range: 10,000-100,000 ppm MDL: 10,000 ppm / Method: Mercuric Nitrate

Cat#

Titrets Kit, Shelf-life 20 months

*K-2070

Increments:

10,000, 11,000, 12,000, 13,000, 14,000, 15,000, 16,000, 18,000, 20,000, 25,000, 30,000, 35,000, 40,000, 50,000, 70,000, 100,000 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests (except distilled water): thirty ampoules with valve assemblies, Activator Solution, titrettor, 25 mL sample cup, 3.0 mL syringe and instructions.



Instrumental Kit

Multi-Analyte Photometers

V-2000 / V-3000 Series

(See page 14 for instrumental features)

Range: 0-40.0 ppm

Method: Ferric Thiocyanate

Cat# Vacu-vials Kit *K-21031

Kit comes in a cardboard box and contains everything needed to perform up to 29 tests (except distilled water): thirty ampoules, Activator Solution, 25 mL sample cup, ampoule blank, 1.0 mL syringe and instructions.

Vacu-vials Kits require the use of a CHEMetrics Direct-Readout Photometer (photometers sold separately) or a spectrophotometer capable of accepting a 13 mm diameter round cell. See page 14 for details.



¹Although the test kit contains 30 ampoules, a fresh reagent ampoule blank must be prepared for each series of tests; therefore, the number of samples that can be tested with each kit will vary from a maximum of 29 to a minimum of 15.

*Contains mercury. Dispose according to local, state or federal laws.