

Canada GL Lighting Technology Inc

Telphone: 905-604-100 Fax: 1-866-756-3987

20W/30W/50W LED FLOOD FIXTRUE LIGHT





Feature:

A new generation of floodlight: Structure of the fixture is completely and slim integral die casting aluminum so it has a superior heat dissipation ability. The unique medal frame can perfectly safe guard the glass, making the whole fixture very solid. Professionally designed lighting at high transmittance, with the application of high quality USA Bridgelux LED chips and Integrated light source, It looks very beautiful. The fixture can achieve a lumen output of 120 per watt and higher, demonstrating the outstanding lighting performance of LED flood fixture.



Canada GL Lighting Technology Inc

Telphone: 905-604-100 Fax: 1-866-756-3987

Specification

- This product range includes: 20W,30W and 50W
- IP66 rated, suitable for wet locations.
- Temperature rated at -30° to 50°C.
- CRI>80, CCT: optional 3000K,4000K & 5000K.
- Operating voltage:120-277VAC

Model	Watts	Size (mm)	CCT (XX)	Lumens
GLFLD-20W-XX	20W	142*179*48	3000K(30)	2400LM
GLFLD-300W-XX	30W	190*223*56	4000K(40)	3500LM
GLFLD-50W-XX	50W	283*250*65	5000K(50)	6000LM

Warranty for 3 years

Mounting

