

70W/100W/200W/300W

LED FLOOD FIXTRUE LIGHTING



Feature:



A new generation of floodlight: Structure of the fixture is completely and slim integral die casting aluminum so it has a superior heat dissipation ability. The unique medal frame can perfectly safe guard the glass, making the whole fixture very solid.Professionally designed lighting at high transmittance, with the application of high quality PHILIPS LED chips, the fixture can achieve a lumen output of 130 per watt and higher, demonstrating the outstanding lighting performance of LED flood fixture.



Canada GL Lighting Technology Inc Telphone :905-604-100 Fax:1-866-756-3987







Specification

- This product range includes: 70W, 100W, 150W, 200W, 250W and 300W.
- IP65 rated, suitable for wet locations.
- Temperature rated at -40° to 50°C.
- CRI>80, CCT: optional 3000K,4000K &5000K.
- Operating voltage:120-277VAC/347-480VAC (optional)

Model	Watts	Size (mm)	Lumens
GLFLD-70W-XX	70W	285*238*68	7000LM
GLFLD-100W-XX	100W	345*300*85	10000LM
GLFLD-150W-XX	150W	415*345*11	18000LM
GLFLD-200W-XX	200W	415*345*11	22000LM
GLFLD-300W-XX	300W	495*425*118	31000LM

Mounting




Canada GL Lighting Technology Inc Telphone :905-604-100 Fax:1-866-756-3987

3



Arm-mounted (signvue Downlight)



Suspend-mounted (baylight High/low)




2

Arm-mounted (signvue Uplight)



Pole-mounted (parking Lots)



Canopy-mounted (Shops Facade Floodlight) (Area Floodlight)



Wall-mounted (tunnel Lighting)



4

8

Wall-mounted



On The Ground (landscape Lighting)

Optional accessories

A, Slip fitter





B, Photocell sensor

C. Motion sensor



