


ECO R-Panel W/ PBR (also available w/out PBR)



The R-Panel w/ PBR (purlin bearing rib) metal panel is commonly used for a wide variety of architectural, agricultural, commercial, and industrial applications. The R-Panel w/ PBR is a structural, exposed fastener panel that can be used for both roof and wall applications. The minimum roof slope for PBR is ½:12. (Also available without the purlin bearing rib mainly for walls.) It is available in 26 gauge steel. Our ECO #1 painted steel panels have a siliconized polyester paint finish. It has a 40 year crack, check, peel warranty, and a 30 year prorated fade and chalk warranty. It's also available in 26ga Galvalume. We produce the trims, including a formed ridge cap, and have most accessories available in matching colors.

- Coverage Width 36"
- Minimum Slope 1/2:12 (under 3/12 butyl tape recommended)
- Custom cut lengths 1' to 40'+
- Panel Attachment Exposed Fastening System
- Gauge 26
- · Finishes Smooth
- Coatings Siliconized polyester (40yr. crack, check peel warranty, 30yr prorated fade & Chalk)
 Galvalume
- Rib Spacing 12" on center
- Rib Height 1-1/4"

ECONOMY METALS R-PANEL 26GA. TRIMS

10'6" STANDARD LENGTHS (CUSTOM TRIM & LENGTHS AVAILABLE)
(* = PITCH NEEDED)

