



## MONOGATE LITE



Lite model of MonoGate.

The gate is very slim, almost invisible with performance of 180 cm.

Any type of configuration is available.

Mono Antenna as well.



## Technical specifications:

**RFID specification:** Operating frequency: 13,56 MHz, max. Transmission power 2-5 W  
Supported tags types: ISO15693 (SLIX-SLIX 2)

---

**Material and dimensions:** Plexiglas, transparent acryl panel, ABS UV  
(w x d x h millimeters): 66 x 510 x 1810

---

**Weight:** 15 KG

---

**Power:** Supply voltage: 24 V  
Power consumption: 32 VA  
Standby mode (min. power consumption)

---

**RF Power:** 2-5 W

---

**Alarm:** Audible and Visual

---

**Detecting mode:** 3D

---

**Data:** RS 232, USB, Ethernet (TCP/IP)

---

**Detection speed:** 1 m/sec

---

**Performance:** Detection 170/180 cm

---

**Standard complication:** EN 300 330, FCC Part 15  
RSS-210, EN 301 489, EN 60950-1, EN 50364

---

**People counter:** Radar

---

**Temperature range:** Operating: - 25C / + 50C

---

**Functionality:** Tracker (on request)

---

**Certification:** CE/UL/FCC.