


HELIUM NEON LASER POWER SUPPLY MODULE MODEL: E-15-NN-xx



The E-15-NN-xx series of 12 VDC input models are compact, high reliability switching power supplies, delivering ultra-low output ripple, input filtering, a CDRH time delay, useradjustable output current and an open-collector disable ("TTL control").

Designed to provide outstanding conversion efficiency, the units are fully encapsulated in a specifically formulated epoxy for maximum heat dissipation and electrical insulation.

SPECIFICATIONS		E-15-NN-LP	E-15-NN-MP	E-15-NN-HP
Input Voltage	(VDC)	10 to 14	10 to 14	10 to 14
Input Current	(A, max sustaining)	2.0	2.0	2.5
Output Voltage	(VDC)	1100 to 1500	1200 to 1800	1800 to 2500
Start Voltage	(kVDC)	> 8	> 10	> 10
Current Setting Range	e (mA)	3.0 to 6.5	3.0 to 6.5	4.0 to 7.0
SPECIFICATIONS (Commo	n to all models)			
Conversion Efficiency	(%)			> 80
Current Ripple	(% Peak to Peak)			< 0.5
Current Ripple	(% RMS)			< 0.2
CDRH Power-on Delay (Seconds)		Cut violet loop to Eliminate		3 to 7
TTL Enable:		Ground yellow lead	d to Enable	Present
Input Connector:		Flying Leads		None
Output Connector:		Amphenol Alden D100FY"L"		Present
Output Fault Protection:		Open, Short, Arc		Present
Internal Bleed-down F	Resistor:			Present
ENVIRONMENTAL SPECIFICATIONS		OPERATING		NON-OPERATING
Temperature (°C)		-20 to + 50		-40 to + 80
Altitude (meters)		0 to 12,000		0 to ∞
Relative Humidity (%, non-condensing)		0 to 99%		0 to 99%
MECHANICAL SHOCK & V	BRATION			
Shock (per IEC 68-2-27)		300 m/s ² for 11 msec, Half Sine, 3 cycles per axis		
Vibration (per IEC 68-2-6)		10-55 Hz, .35mm amplitude, 1 Octave per minute, 6 cycles per axis		



NRTL COMPLIANCE	IEC 62368-1:2014 CAN/CSA-C22.2 No. 62368-1-14		
-			
,			
SELF-CERTIFICATION	CU72205067 04		
EMC	EN 61326-1: 2013		
REACH	1907/2006 + Annex XIV, XVII		
EU POP	EU 2019/1021		
RoHS 3	EU 2015/863/EU		
	laration of Conformity for further compliance information.		
EXPORT INFORMATI			
ECCN	EAR99		
HTTS	8504.40.9510		
Country of Origin	United States		
THESE PRODUCTS ARE SOLD II	ACCORDANCE WITH UNITED STATES EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAWS IS PROHIBITED		
	To the Outer Encourse RECOVER AND SAME CO USA Outer Income Recover and the California Section of the California S		
1.00 [25.4]			
	3.75 [95.3] A38 MAX [11.1] VIO SEE ABOVE FOR LABEL INFORMATION T T T T T T T T T T T T T		
2X .15 ± .01 [3.8 ± .3]	2.30 [58.4] 50 (12.7) BLK YEL 50 [12.7] (304] 50 [12.7]		

Information contained herein is for reference only and subject to change without notice. Removal of Product Label voids warranty and invalidates all regulatory compliance certifications.

© Voltex, Inc. All Rights Reserved

Page 2/2