



PRECISION, TEMPERATURE STABLE, RELIABLE

Tel# 914 337-4775, Fax# 914 779-7109, E-mail; coilqcorp@aol.com

Catalog No	L nom uH	Q @ L nom	F Test MHz	Fo @ L Nom MHz	DCR Ohms
Q2-.10uH	0.10	125	25	650	<.1
Q2-.12uH	0.12	125	25	580	<.1
Q2-.15uH	0.15	135	25	510	<.1
Q2-.18uH	0.18	145	25	450	<.1
Q2-.22uH	0.22	150	25	390	<.1
Q2-.27uH	0.27	155	25	340	<.1
Q2-.33uH	0.33	158	25	320	<.1
Q2-.39uH	0.39	160	25	290	<.1
Q2-.47uH	0.47	160	25	250	<.1
Q2-.56uH	0.56	160	25	240	<.1
Q2-.68uH	0.68	155	25	220	<.1
Q2-.82uH	0.82	155	25	200	<.1
Q2-1.0uH	1	150	25	175	<.1
Q2-1.2uH	1.2	150	7.9	160	<.1
Q2-1.5uH	1.5	150	7.9	140	0.1
Q2-1.8uH	1.8	160	7.9	125	0.15
Q2-2.2uH	2.2	150	7.9	110	0.15
Q2-2.7uH	2.7	160	7.9	96	0.2
Q2-3.3uH	3.3	165	7.9	95	0.2
Q2-3.9uH	3.9	160	7.9	86	0.3
Q2-4.7uH	4.7	160	7.9	78	0.4
Q2-5.6uH	5.6	160	7.9	68	0.4
Q2-6.8uH	6.8	155	7.9	62	0.4
Q2-8.2uH	8.2	150	7.9	55	0.7
Q2-10uH	10	145	7.9	47	0.8
Q2-12uH	12	165	2.5	40	0.42
Q2-15uH	15	165	2.5	35	0.6
Q2-18uH	18	165	2.5	31	0.6
Q2-22uH	22	165	2.5	29	0.9
Q2-27uH	27	165	2.5	25	1
Q2-33uH	33	160	2.5	21.5	1.1
Q2-39uH	39	160	2.5	20.5	1.2
Q2-47uH	47	155	2.5	20	1.8
Q2-56uH	56	150	2.5	16.5	2
Q2-68uH	68	148	2.5	14.5	1.7
Q2-82uH	82	140	2.5	13.5	1.8
Q2-100uH	100	135	2.5	10.8	2.1

Q2-120uH	120	137	0.79	9.6	2.2
Q2-150uH	150	137	0.79	9.5	2.6
Q2-180uH	180	135	0.79	8.3	4.2
Q2-220uH	220	135	0.79	7.1	4.5
Q2-270uH	270	135	0.79	5.6	4.9
Q2-390uH	390	140	0.79	5.5	6.8
Q2-330uH	330	135	0.79	5.2	5.5
Q2-470uH	470	142	0.79	5.2	7.4
Q2-560uH	560	132	0.79	4.8	10.8
Q2-680uH	680	130	0.79	4.5	11.5
Q2-820uH	820	130	0.79	4	13
Q2-1000uH	1000	125	0.79	3.8	15