







The SMRT Logic internet gateway provides secure, ondemand access to your Toro® and Irritrol® irrigation controller, Unique Lighting Systems® outdoor landscape lighting transformer, or other landscape features using a smartphone, tablet, PC or smart home speaker.

# SMRT LOGIC®

CLOUD BASED HUB FOR LANDSCAPES

## SIMPLE SET-UP

Simply plug SMRT Logic into any internet modem or router. SMRT Logic makes a connection to the web automatically. No Wi-Fi passwords or permissions required.

#### CONNECTION FOR OUTDOOR ENVIRONMENTS

SMRT Logic communicates to the irrigation controller, outdoor lighting transformer and other landscape features using a secure and robust transmission signal with more range and reliability than Wi-Fi and Bluetooth platforms.

### **SECURE RELIABLITY**

SMRT Logic features industry standard encryption and mobile device operation with or without being connected to a Wi-Fi network.

#### **COMPATIBLE**

SMRT Logic is backward compatible. It works with all existing Toro, Irritrol and Unique Lighting contollers or transformers for easy, affordable system upgrades.







SMRTscape<sup>1</sup> Lighting





# **How It Works?**



# **Easy to Setup, Easy to Use**





- 1. Connect the SMRT Logic Internet Gateway (Ethernet connection to router)
- 2. Register and create an account at www.SMRTscape.com
- 3. Configure location(s), irrigation controllers, lighting scenes, and AUX relays.







SMRTscape™

SMRTscape™ Remote

Lighting

Available through iTunes App Store/Google Play.\*





# **Additional Features**

- ✓ Add users (representatives) to an account for greater flexibility and ease of system management.
- Control and manage up to 10 irrigation controllers through a single SMRT Logic<sup>®</sup> gateway.
- Control and program any 120V-powered indoor or outdoor device using the Wireless Auxiliary Relay (e.g., pond lights, fountains, awnings, Holiday lights, or indoor lamps).
- $\checkmark$  Custom name stations and programs, and add images through the SMRTscape<sup>™</sup> mobile app and website.
- The TMC-424, TMC-212, and Custom Command™ equipped with Irritrol® Mini-Receiver (CL-MR) or Climate Logic® Weather System (CL-100-WIRELESS) enables automatic weather-based irrigation schedule adjustment.

# **SPECIFICATIONS**

### **Operational**

- Input: 5Vdc 1 amp
- FCC

#### **Dimensions**

- 4.5" W x 5.5" H x 4.5" D (antenna installed in typical orientation)
- · Weight: 0.6 lbs.

#### Warranty

Five Years

# **Toro**° Specifying Information – SMRT Logic

- p, g	
Model	Description
SMRT-T	SMRT Logic Internet Gateway

## **Irritrol**®

Specifying Information – SMRT Logic

-p,g	
Model	Description
SMRT-CLMR-KIT	SMRT Logic + CL Mini Receiver

# Unique Lighting Systems®

Specifying Information – SMRT Logic

. , ,	9
Model	Description
LPLUS	SMRT Logic Internet Gateway
LPCU-A	Relay Module

