





MODEL

CAPACITIES						
Snow Tank						
Actual Volume	2.83 m ³	100 cu. ft.				
Compacted	3.54 m ³	125 cu. ft.				
Water						
Ice Making	738 L	195 gal.				
Wash Water	310 L	82 gal.				
Total	1048 L	277 gal.				
Hydraulic Oil	95 L	25 gal.				
POWERTRAIN						
Four-Wheel Drive						
Engine	Kubota® 1.6 L / 50 HP at 3000 RPM Four Cylinder Liquid Cooled					
Transmission	Continuously variable hydrostatic pump and motor are axial-piston type.					
Hydraulics	Double pump powers the vertical and horizontal augers. Hydraulic down pressure for optimal resurfacing results.					
Axles						
Front	1950 kg	4300 lb				
Rear	2903 kg	6400 lb				
Brakes	Full Hydrodynamic Braking					

DIMENSIONS								
Overall	L	w	н	L	w	н		
Snow Tank Down	4.04 m	2.13 m	2.16 m	159 in.	84 in.	85 in.		
Snow Tank Up	5.03 m	2.13 m	3.91 m	198 in.	84 in.	154 in.		
Shaving Blade	L	W	н	L	W	н		
	195.6 cm	12.7 cm	1.27 cm	77 in.	5 in.	0.5 in.		
Clearance								
Minimum Operator Height Clearance			246.4 cm	97 in.				
Snow Pit Clearance		125.7 cm			49.5 in.			
Conveyor System								
Horizontal Auger Diameter		25.4 cm			10 in.			
Vertical Auger Diameter		25.4 cm			10 in.			
Manueverability								
Wheelbase		1.96 m			77 in.			
Wheel Track		1.37 m			54 in.			
Turning Radius at Conditioner		4.87 m			16 ft.			
Weight								
Empty		2912 kg			6420 lb			
with Water		3910 kg				8620 lb		



Some features described or shown may be optional at extra cost and prices, colors, materials, specifications and models are subject to change. Some options are required in combination with other options. ZAMBONI and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. © Zamboni 2016 Rev 06/16/2017





Advanced Water System — AWS[™] Regulates the amount of water dispensed

onto the ice relative to the machine speed for an efficient and even application.

STANDARD FEATURES

- 2 Year Warranty
- 400 Micron Wash Water Deep Filter Bag Aluminum Alloy Wheels Chassis: Strong All Welded Steel Tubing Conditioner Safety Guards Digital Training and Reference Materials Engine: EPA and CARB Certified Familiar Automobile-Style Foot Controls Four-Wheel Drive Fuel Options: Gasoline, Propane Full Hydrodynamic Braking Guide Wheel Headlights and Tail Light (for Off Ice Travel) High Quality 10 and 20 Micron Filters High Speed Vertical Auger Hydraulic Oil Level Sight Gauge Load Sensing Engine Governor Multi-Function Display
- **On-Dash Diagnostics**

Parking Brake

power.

Zamboni Power Brush™

Wider brush path reaches higher on the

dasher board kick plate for superior cleaning

- Power Steering
- Premium Polyester Felt Spreader Towel Replaceable Poly Conditioner Side Plate Rugged Dana Spicer® Axles Rust-Free Poly Ice Making Water Tank Snow Tank Safety Stand Stainless Steel Hardware Steering Wheel Spinner Knob Touch-Up Paint Kit Tungsten Carbide Studded Tires Under Seat Storage Wide Spectrum of Premium Automotive Paint Colors

OPTIONS

conditioner

Advanced Water System (AWS[™]) Automatic Snow Breaker Back Up Alarm Blade Change System Cab Enclosure Conditioner: Galvanized Electric Water Level Gauge Engine Diagnostic Computer Interface Tool Front Squeegee Hydraulic Oil Cooler Kit IceCaps® Wheel Advertising System Integrated Auger Washout System Low Fuel Light Low Guide Wheel Snow Melting Kit Snow Tank Dump Height Restriction Snow Tank Light Stainless Steel Water Distribution Pipe

Integrated Auger Washout System

Simplifies the vertical and horizontal auger

washout task, from a single point on the

Tire Wash System V-Plow Wash Water to Ice Making Water Transfer Water Level Sight Gauge Zamboni Power Brush™ Board Brush System

ZAMBONI

Some features described or shown may be optional at extra cost and prices, colors, materials, specifications and models are subject to change. Some options are required in combination with other options. ZAMBONI and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. © Zamboni 2016 Rev 06/16/2017