

GENERAL NOTES

Precast concrete shall be exposure Class S and meet min compressive strength of 35MPA


Cement: Type GU Air Category: 4.0% — 7.0% Aggregate: CSA/CAN A23.4 Maximum Size: 20mm Admixtures: CSA/CAN A23.4 Reinforcing: Grade 400W CSA G30.18-09

Inserts/Embeds: As noted in drawing details

Manufacture of precast concrete units shall be in accordance with specification CSA A23.4

** LEKO PRECAST LTD SHALL NOT BE RESPONSIBLE FOR ANY INSTALLATION PRACTICES FOLLOWED ON-SITE UNLESS PERFORMED BY LEKO PRECAST LTD **

Tank Volume 1,220igal (800/420) Tank Weight 4,497Kg (9,914 lbs) Lid Weight 1,391Kg (3,066 lbs) Total Weight 5,888Kg (12,980 lbs)



ע נ	PRECAST	

1250IG PUM	IP OUT TANK	•		
DRAWN BY: JA	CHECKED BY:	APPROVED BY:	DATE: June 2022	
ASSEMBLY DWG.	PREVIOUS DWG.	DRAWING NO.		REVISION
SCALE: 1:50 ISOMETRIC: 1:50		S0205M		2
DO NOT SCALE THIS DRAWING				