

2.0MP HD-AHD IR HIGH SPEED DOME CAMERA 100M IR DISTANCE

FEATURES

2.0 MP HD-AHD
100M IR Distance
Full Aluminium Alloy Wiper
OSD Menu in English
256 preset points
Pan Range: 360° continuous rotation
Tile Range: -10°~90° with auto flip
Manual Speed: Horizontal: 0.01°/s - 350°/s, Vertical: 0.01°/s - 120°/s
Preset Speed: Pan: 350°/s, Tile: 120°/s
Video Analysis Light-Adjustment Technology
IP 66 all-environments protection



SPECIFICATION

MODEL	ASD4200-2000AIRW
Image Sensor	1/2.8" Sony CMOS Sensor
Resolution	1080P(1920x1080)
Optical Zoom	20X optical zoom
IRIS	F1.6~F3.5
Focal Length	4.9~97mm
IR-CUT	Auto/Manual
Electronic Shutter	support
Day/Night	on/off/auto
BLC	ON/OFF
White balance	Auto/Manual/Ggain/Bgain
Noise Reduction	support
AGC	Auto/Manual
Pan Range	360°
Tile Range	Range -10°~90°
Manual Speed	Horizontal: 0.01°/s - 350°/s, Vertical: 0.01°/s - 120°/s
Preset Speed	Pan: 350°/s, Tile: 120°/s
Preset	256
Auto Cruising	8 groups (32 Preset/group)
Auto Scan	8 groups (setup left and right boundary)
Pattern Scanning	4 groups
Wiper	Optional
Bracket	Wall mount/ Pendant mount
OSD Menu	English/Chinese
Timing function	Support
Alarm	2 inputs/ 1 outputs (Optional)
Power Supply	DC12V±10%
Power consumption	≤50W
Working Temp	-35°C +60 °C
Working Humidity	<90%, no condensing
Protection Level	IP66, the secondary lightning protection, 3000V anti-surge design
Size	5 Inch
Weight	4.8kg

