Most Popular Material & Imprint Colors Available on all materials. Ships in 10 business days.

PMS Black C	PMS White	PMS 115C	PMS 151C	PMS 195C	PMS 200C	PMS 268C	PMS 289C	PMS 294C	PMS 316C	PMS 348C	PMS 5535C
Additional	Material &	Imprint Col	ors Ribbed F	Polyester mate	erial only, app	lies to PH10,	ELSS and 2T1	.0. Ships in 13	-15 business	days.	
Black/	Red/	R.Blue/	Yellow/	Purple/	Silver	PMS	PMS	PMS	PMS	PMS	PMS
White	White	White	White	White	Glitter	White NC	Black 2C	Black 3C	Black 4C	Black 6C	Black 7C
PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Cool	PMS Warm	PMS Warm
Gray 1C	Gray 3C	Gray 4C	Gray 5C	Gray 6C	Gray 7C	Gray 8C	Gray 9C	Gary 10C	Gary 11C	Gray 1C	Gray 2C
PMS Warm	PMS Warm	PMS Orange	PMS Reflex	PMS Rubine	PMS	PMS	PMS	PMS	PMS	PMS	PMS
Gray 3C	Gray 4C	021C	Blue C	Red C	Yellow C	072C	101C	102C	106C	108C	109C
PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS
116C	123C	124C	130C	136C	137C	152C	161C	165C	166C	169C	171C
PMS 172C	PMS	PMS	PMS	PMS	PMS	PMS	PMS 185C	PMS	PMS 187C	PMS	PMS
1720	173C	176C	178C	179C	183C	184C	163C	186C	16/C	189C	190C
PMS 191C	PMS 193C	PMS 199C	PMS 204C	PMS 206C	PMS 207C	PMS 210C	PMS 211C	PMS 218C	PMS 219C	PMS 226C	PMS 227C
1,10	1700	1776	20.0							2200	22, 3
PMS 230C	PMS 232C	PMS 233C	PMS 236C	PMS 237C	PMS 243C	PMS 255C	PMS 272C	PMS 279C	PMS 282C	PMS 286C	PMS 287C
PMS 290C	PMS 291C	PMS 292C	PMS 296C	PMS 301C	PMS 303C	PMS 306C	PMS 314C	PMS 319C	PMS 321C	PMS 322C	PMS 332C
PMS 335C	PMS 341C	PMS 349C	PMS 350C	PMS 355C	PMS 356C	PMS 365C	PMS 366C	PMS 368C	PMS 375C	PMS 376C	PMS 377C
PMS 381C	PMS 382C	PMS 388C	PMS 389C	PMS 400C	PMS 401C	PMS 403C	PMS 405C	PMS 406C	PMS 407C	PMS 409C	PMS 410C
PMS 412C	PMS 413C	PMS 414C	PMS 417C	PMS 418C	PMS 419C	PMS 421C	PMS 422C	PMS 423C	PMS 424C	PMS 426C	PMS 428C
PMS 429C	PMS 432C	PMS 433C	PMS 439C	PMS 440C	PMS 443C	PMS 445C	PMS 446C	PMS 447C	PMS 449C	PMS 452C	PMS 461C
D) 46	D) 10	D) 16	D) 16	D) 40	D) 10	D) 46	D) 40	D) 40	D) 46	D) 10	D) 46
PMS 463C	PMS 467C	PMS 476C	PMS 478C	PMS 481C	PMS 482C	PMS 483C	PMS 495C	PMS 496C	PMS 508C	PMS 512C	PMS 513C
DNAC	DNAC	DMC	DNAC	DNAC	DMC	DMC	DNAC	DNAC	DNAC	DMC	DNAC
PMS 514C	PMS 531C	PMS 532C	PMS 533C	PMS 534C	PMS 542C	PMS 553C	PMS 556C	PMS 563C	PMS 565C	PMS 574C	PMS 577C

Colors are approximate and may appear slightly lighter or darker depending on printing conditions. A PANTONE® book should be used for more accurate color matching.

Additional Material & Imprint Colors Cont. Ribbed Polyester material only, applies to PH10, ELSS and 2T10. Ships in 13-15 business days.

Additional	ı Materiai &	Imprint Col	lors Cont. R	ibbed Polyes	ter material o	only, applies to	PH10, ELSS	and 2110. Sh	ips in 13-15 b	usiness days.	
PMS 584C	PMS 600C	PMS 628C	PMS 635C	PMS 646C	PMS 653C	PMS 654C	PMS 655C	PMS 657C	PMS 659C	PMS 661C	PMS 672C
PMS 675C	PMS 688C	PMS 693C	PMS 698C	PMS 710C	PMS 801C	PMS 802C	PMS 804C	PMS 806C	PMS 809C	PMS 812C	PMS 814C
PMS 1215C	PMS 1235C	PMS 1395C	PMS 1495C	PMS 1505C	PMS 1545C	PMS 1585C	PMS 1635C	PMS 1645C	PMS 1665C	PMS 1765C	PMS 1767C
PMS 1785C	PMS 1895C	PMS 1905C	PMS 1915C	PMS 1925C	PMS 2060C	PMS 2115C	PMS 2123C	PMS 2139C	PMS 2143C	PMS 2163C	PMS 2241C
PMS 2276C	PMS 2287C	PMS 2299C	PMS 2308C	PMS 2322C	PMS 2333C	PMS 2425C	PMS 2562C	PMS 2567C	PMS 2572C	PMS 2577C	PMS 2582C
PMS 2627C	PMS 2635C	PMS 2645C	PMS 2655C	PMS 2665C	PMS 2695C	PMS 2706C	PMS 2717C	PMS 2728C	PMS 2747C	PMS 2756C	PMS 2757C
PMS 2758C	PMS 2766C	PMS 2767C	PMS 2768C	PMS 2915C	PMS 2925C	PMS 2945C	PMS 2985C	PMS 2995C	PMS 3115C	PMS 3155C	PMS 3165C
PMS 3255C	PMS 3282C	PMS 3288C	PMS 3395C	PMS 3405C	PMS 4625C	PMS 4685C	PMS 4695C	PMS 4975C	PMS 4985C	PMS 5225C	PMS 5255C
PMS 5275C	PMS 5285C	PMS 5295C	PMS 5395C	PMS 5415C	PMS 5467C	PMS 5487C	PMS 5523C	PMS 5615C	PMS 5747C	PMS 5753C	PMS 5767C
PMS 7403C	PMS 7407C	PMS 7408C	PMS 7421C	PMS 7427C	PMS 7443C	PMS 7451C	PMS 7452C	PMS 7453C	PMS 7454C	PMS 7461C	PMS 7462C
PMS 7478C	PMS 7479C	PMS 7482C	PMS 7485C	PMS 7490C	PMS 7499C	PMS 7501C	PMS 7502C	PMS 7504C	PMS 7505C	PMS 7507C	PMS 7509C
PMS 7511C	PMS 7528C	PMS 7529C	PMS 7531C	PMS 7532C	PMS 7533C	PMS 7534C	PMS 7535C	PMS 7536C	PMS 7537C	PMS 7538C	PMS 7540C
73116											73100
PMS 7542C	PMS 7544C	PMS 7545C	PMS 7546C	PMS 7553C	PMS 7558C	PMS 7561C	PMS 7564C	PMS 7567C	PMS 7574C	PMS 7575C	PMS 7579C
75-120							7 33 10				73770
PMS 7580C	PMS 7582C	PMS 7595C	PMS 7596C	PMS 7668C	PMS 7678C	PMS 7682C	PMS 7684C	PMS 7686C	PMS 7692C	PMS 7693C	PMS 7725C
, 5000	. 3020	.5,50	7.3736	7.0000	7.57.50	, 0020	7.00 %	7.0000	7.0720	. 3,30	11236
PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS	PMS		
7726C	7727C	7732C	7734C	7735C	7748C	7753C	7757C	7764C	7771C		

Additional colors can apply to Smooth Polyester, Flexible Tubular, Flat Tubular and Woven Lanyards for an additional charge.

Customization Information

ARTWORK: The following computer files are acceptable:

- Adobe Illustrator version 6.0 or less– all fonts converted to "OUTLINES" and saved as an .ai or .eps file.
- Adobe Photoshop version 6.0 or less– files saved as .tiff, .bmp, .jpg, .psd or .gif (minimum DPI 150, logos from websites are NOT acceptable).
- Adobe InDesign version 6.0 or less- all fonts converted to "OUTLINES" and package the links when sending the file.

Please specify the name and type of the files being sent. DO NOT embed files in a Microsoft Word® file. Include a color copy for color breakdown only. Preproduction, custom-imprinted samples are available for an additional charge. Modifications to artwork will be quoted on a per order basis. A minimum charge applies. (No photocopies or faxes.)

SET-UP CHARGES: A set-up charge may apply to orders. Call for details.

RUSH CHARGES: Additional charges may apply. Call for details.

CANCELLATION: Orders may be subject to a cancellation charge to compensate for any costs incurred prior to cancellation (i.e. artwork charges, printing plates, etc.).

PAD PRINTING: For plastics, metals, neck lanyard sliders, snap buckles, badge reels and detachable attachments. Provides a quality, durable imprint. Exact color matches cannot be guaranteed.

CLEAR DOMING RESIN: Provides permanent protection for a multi-color label. Available on round and diamond sliders, detachable attachments and badge reels.

DYE-SUBLIMATION: A permanent transfer process used on our neck lanyards and select wristbands. A digital image is transferred onto a white base allowing for fine, photo-realistic detail. Any color can be used for a base color.

CONTINUOUS PRINTING AND POSITIONAL PRINTING: Many lanyards come in either a continuously printed imprint or a positionally printed imprint. See diagram below for examples of printing styles.



CONTINUOUS PRINTINGIMPRINT CONTINUES THROUGH SEAM AND BREAKAWAY



POSITIONAL PRINTING
IMPRINT STOPS BEFORE SEAM AND BREAKAWAY

Production & Shipping

PRODUCTION TIME: Timetables for shipping are based on credit approval, receipt of camera-ready art and proof approval. Production timetable is valid for all catalog products in catalog quantities. No guarantees are made as to arrival dates. Please specify and authorize special shipping which may be required to meet exact event dates or deadlines.

PACKAGING: Lanyards are bundled in quantities of 100. Additional charges may apply for other quantities or special requests. Call for quote.

DAMAGED SHIPMENTS: All merchandise is inspected, weighed, and carefully packed for shipment before leaving any of our warehouses. The freight company accepts liability when the shipment leaves our facility. Upon delivery of your shipment, promptly check the number and condition of cartons against the Bill of Lading totals before signing the freight Bill of Lading.

LIABILITY: The products become the customer's property upon delivery to the carrier. If damage or loss is discovered—either visible or concealed—you must file a claim with the freight carrier within 14 days of the delivery date.

Breakaway Information

SPECIAL WARNING FOR BREAKAWAY LANYARDS: Breakaway performance will vary and lanyards will not break away under all conditions. The male/ female part pull force specification for round breakaways is 3-11 lbs under tested conditions per M-3-QA-0167. The male/female part pull force specification for flat breakaways is 4-10 lbs under test conditions per M-3-QA-0167. A full description of the M-3-QA-0167 test procedure can be provided upon request. Not recommend for use around moving objects or playgrounds.

LIMITED BREAKAWAY WARRANTY: Breakaway performance will vary and lanyards will not break away under all conditions. Customers should test the breakaway feature for suitability for their use and environment. This product is subject to a limited warranty. Seller warrants to the original purchaser for use that the goods or any component thereof will be free from defects in workmanship for a period of one year from the date of purchase. Seller's sole liability and the purchaser's sole remedy for a failure of goods under this limited warranty, and for any and all claims arising out of the purchase and use of the goods, shall be limited to the repair or replacement of the goods that do not conform to this warranty. There are no express or implied warranties covering these goods other than as set forth above.

General Information

We reserve the right to change pricing of products or services without notice. Imprints, logos or trademarks displayed in this catalog are for purpose of showing printing capabilities only. Use of such does not constitute an endorsement of the product, nor does it indicate that the product has been used or purchased by the person or company whose name or logo appears on the product.