acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Date of compilation: 2019-11-05

# **SECTION 1: Identification**

Version number: GHS 1.0

1.1 Product identifier

Trade name

### **#79 Metal Master**

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Automotive / Marine Chrome and ornamental metal polish

## 1.3 Details of the supplier of the safety data sheet

CDN Distributors, Inc. PO Box 3191 Scranton, PA 18505

1-800-834-8916 (570) 457-1960

www.cdndistributors.com

### 1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

## SECTION 2: Hazard(s) identification

### 2.1 Classification of the substance or mixture

### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	.2 skin corrosion/irritation		Skin Irrit. 2	H315
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning
- Pictograms

GHS07

	1	
- <b>N</b>	:	
	Ŭ	

<ul> <li>Hazard statements</li> </ul>	
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

- Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0		Date of compilation: 2019-11-05
- Precautionary sta	tements	
P403+P233	Store in a well-ventilated p	lace. Keep container tightly closed.
P405	Store locked up.	
P501	Dispose of contents/conta	iner in accordance with local/regional/national/international regulations.
- Hazardous ingred	lients for labelling	C9-C15 mixed cycloalkanes and alkanes

#### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
C9-C15 mixed cycloalkanes and al- kanes	CAS No 64742-47-8	20-<40	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 4 / H227

Hazardous ingredients, Consideration of other advice

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

### **SECTION 4: First-aid measures**

#### 4.1 Description of first- aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

### **SECTION 5: Fire-fighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

#### Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

## 7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as Frost

### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun try	Name of agent	CAS No	lden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Sourc e
US	alpha-Alumina	1344-28- 1	REL							appx- D	NIOS H REL
US	alpha-alumina	1344-28- 1	PEL		15					i, dust	29 CFR 1910.1 000
US	alpha-alumina	1344-28- 1	PEL		5					r, dust	29 CFR 1910.1 000
US	aluminium, insol- uble compounds	1344-28- 1	TLV®		1					r	AC- GIH® 2019
US	aluminium oxide	1344-28- 1	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium oxide	1344-28- 1	PEL (CA)		5					r	Cal/ OSHA PEL

Notation

appx-D see Appendix D - Substances with No Established RELs

Ceiling-C ceiling value is a limit value above which exposure should not occur

dust as dust i inhalable fraction

r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (viscous)
Color	light blue
Odor	characteristic

#### Other safety parameters

pH (value)	7.5–8.5 (25 °C)		
Melting point/freezing point	not determined		
Initial boiling point and boiling range	100 °C		
Flash point	99 °C at 101.3 kPa 211 °F at 1 atm closed cup		
Evaporation rate	not determined		
Flammability (solid, gas)	not relevant, (fluid)		

Explosive limits

- Lower explosion limit (LEL)	0.8 vol%		
- Upper explosion limit (UEL)	6 vol%		
Vapor pressure	31.69 hPa at 25 °C		
Density	1.11 <sup>g</sup> / <sub>cm³</sub> at 25 °C		
Vapor density	this information is not available		
Solubility(ies)	not determined		
Partition coefficient			
- n-octanol/water (log KOW)	this information is not available		

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

Auto-ignition temperature	>220 °C
Viscosity	
- Kinematic viscosity	600 cSt at 25 °C
- Dynamic viscosity	666 cP at 25 °C
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	$\begin{array}{ c c c }\hline T2D \ (maximum \ permissible \ surface \ temperature \ on \ the \ equipment: \\ 215^\circ\text{C}) \end{array}$

# SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

**12.2** Persistence and degradability Data are not available.

Dala di e nol avaliable.

- **12.3 Bioaccumulative potential** Data are not available.
- **12.4 Mobility in soil** Data are not available.
- **12.5** Results of PBT and vPvB assessment Data are not available.

#### 12.6 Other adverse effects

Endocrine disrupting potential None of the ingredients are listed.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0 Date of compilation: 2019-11-05 **SECTION 14: Transport information** 14.1 **UN number** not subject to transport regulations 14.2 UN proper shipping name not assigned 14.3 Transport hazard class(es) not assigned 14.4 Packing group not assigned 14.5 **Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations 14.6 Special precautions for user There is no additional information. 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk. Information for each of the UN Model Regulations Transport of dangerous goods by road or rail (49 CFR US DOT) Not subject to transport regulations. International Maritime Dangerous Goods Code (IMDG) Not subject to IMDG. International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

Toxic Substance Control Act (TSCA)all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

#### **Clean Air Act**

none of the ingredients are listed

# California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

#### Proposition 65 List of chemicals

•					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the tox- icity
methanol	methanol	67-56-1	0.00219		develop- mental
ethyl alcohol	ethanol (ethyl alcohol)	64-17-5	0.05143	in alcoholic beverages	develop- mental
4-methylpentan-2-one	methyl isobutyl ketone	108-10-1	0.001122		cancer
4-methylpentan-2-one	methyl isobutyl ketone (MIBK)	108-10-1	0.001122		develop- mental

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0 Date of compilation: 2019-11-05

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the tox- icity
2,2'-iminodiethanol	diethanolamine	111-42-2	0.02		cancer

#### **VOC content**

Г

Regulated Volatile Organic Compounds (VOC-EPA): 26.63 % Regulated Volatile Organic Compounds (VOC-Cal ARB): 26.63 %

### Industry or sector specific available guidance(s)

### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### **NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description	
Flammability	1	material that must be preheated before ignition can occur	
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury	
Instability	0	material that is normally stable, even under fire conditions	
Special hazard			

#### **National inventories**

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

 DSL
 Domestic Substances List (DSL)

 REACH Reg.
 REACH registered substances

 TSCA
 Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

5

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Date of compilation: 2019-11-05

# SECTION 16: Other information, including date of preparation or last revision

## Abbreviations and acronyms

Version number: GHS 1.0

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protect- ing human health and the environment
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

## Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

acc. to 29 CFR 1910.1200 App D

# **#79 Metal Master**

Version number: GHS 1.0

Date of compilation: 2019-11-05

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text	
H227	27 Combustible liquid.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336 May cause drowsiness or dizziness.		

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.