



**Valvoline**™

SAFETY DATA SHEET	Page: 1
	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid  VV341	Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Valvoline™ TYPE F  
Automatic Transmission Fluid

### Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant

**Details of the supplier of the safety data sheet**  
Valvoline LLC  
100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)  
1-800-TEAMVAL (1-800-832-6825)  
  
SDS@valvoline.com

**Emergency telephone number**  
1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number**  
1-800-TEAMVAL (1-800-832-6825)

**Product Information**  
1-800-TEAMVAL (1-800-832-6825)

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Not a hazardous substance or mixture.

### GHS label elements

Not a hazardous substance or mixture.

### Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:  
7.6484 %

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=90.00 - <=100.00
MINERAL OIL		This material is not	>=5.00 - < 10.00



**Valvoline**™

<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid VV341	Version: 1.3

		considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=5.00 - < 10.00
METHACRYLATE COPOLYMER		Eye Irrit. 2A; H319	>=1.50 - < 5.00

---

#### SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

In case of eye contact : Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:



**Valvoline**™

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid		Version: 1.3
VV341		

stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing methods	:  Product is compatible with standard fire-fighting agents.
Further information	: Standard procedure for chemical fires.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE



**Valvoline**™

SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid VV341	Version: 1.3

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m <sup>3</sup> Mist	OSHA Z-1
		TWA	5 mg/m <sup>3</sup> Inhalable fraction	ACGIH
		TWA	5 mg/m <sup>3</sup> Mist	OSHA P0
		TWA	5 mg/m <sup>3</sup> Mist	NIOSH REL
		ST	10 mg/m <sup>3</sup> Mist	NIOSH REL
		PEL	5 mg/m <sup>3</sup> particulate	CAL PEL
MINERAL OIL		TWA	5 mg/m <sup>3</sup> Mist	OSHA Z-1
		TWA	5 mg/m <sup>3</sup> Inhalable fraction	ACGIH
		TWA	5 mg/m <sup>3</sup> Mist	OSHA P0
		TWA	5 mg/m <sup>3</sup> Mist	NIOSH REL
		ST	10 mg/m <sup>3</sup> Mist	NIOSH REL
		PEL	5 mg/m <sup>3</sup> particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m <sup>3</sup> Mist	OSHA Z-1
		TWA	5 mg/m <sup>3</sup> Inhalable fraction	ACGIH
		TWA	5 mg/m <sup>3</sup> Mist	OSHA P0
		TWA	5 mg/m <sup>3</sup> Mist	NIOSH REL
		ST	10 mg/m <sup>3</sup>	NIOSH REL



**Valvoline**™

<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid VV341	Version: 1.3

	PEL	Mist 5 mg/m <sup>3</sup> particulate	CAL PEL
--	-----	--	---------

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

---

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : red

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 390 °F / > 199 °C  
Method: Cleveland open cup

Evaporation rate : > 1  
Ethyl Ether

Flammability (solid, gas) : No data available



**Valvoline**™

		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid		Version: 1.3
VV341		

Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.013333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.87 (15.6 °C)
Density	: 0.8750 g/cm3 (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons



**Valvoline**™

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid  VV341		Version: 1.3

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation

Skin contact

Eye Contact

Ingestion

### Acute toxicity

Not classified based on available information.

### Components:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation

### MINERAL OIL:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

### METHACRYLATE COPOLYMER:

Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Product:

Remarks : Unlikely to cause eye irritation or injury.

### Components:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation

Assessment : No eye irritation

### MINERAL OIL:

Result : Slight, transient irritation

Assessment : Slight, transient irritation

### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation



**Valvoline**™

		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid		Version: 1.3
VV341		

Assessment : Slight, transient irritation

**METHACRYLATE COPOLYMER:**

Result : Irritating to eyes.

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**MINERAL OIL:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

May be fatal if swallowed and enters airways.



**Valvoline**™

		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid		Version: 1.3
VV341		

#### Further information

##### Product:

Remarks : No data available

---

#### SECTION 12. ECOLOGICAL INFORMATION

##### **Ecotoxicity**

##### Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

##### Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

##### **Persistence and degradability**

##### Components:

No data available

##### **Bioaccumulative potential**

##### Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7



**Valvoline**™

SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid VV341	Version: 1.3

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

## SECTION 14. TRANSPORT INFORMATION

### International transport regulations

#### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

#### U.S. DOT - ROAD

Not dangerous goods

#### CFR\_RAIL\_C

Not dangerous goods

#### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

#### TDG\_ROAD\_C

Not dangerous goods

#### TDG\_RAIL\_C

Not dangerous goods



**Valvoline**™

<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid VV341	Version: 1.3

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	<input type="checkbox"/>	no
------------------	--------------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory



# Valvoline

---

Page: 12

<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid  VV341	Version: 1.3

ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

## TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

---

**SECTION 16. OTHER INFORMATION**

## Further information

Revision Date: 09/07/2018

NFPA:	HMIS III:						
 <p>Flammability Health Special hazard. Inhalability</p>	<table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>0</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>1</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

#### NFPA Flammable and Combustible Liquids Classification

## Combustible Liquid Class IIIB

## Full text of H-Statements

**H304** May be fatal if swallowed and enters airways.  
**H319** Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports



**Valvoline**™

		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid		Version: 1.3
VV341		

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LC<sub>xx</sub> : Lethal Concentration, for xx percent of test population

LD<sub>xx</sub> : Lethal Dose, for xx percent of test population.

IC<sub>xx</sub> : Inhibitory Concentration for xx of a substance

Ec<sub>xx</sub> : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

 <b>Valvoline</b> ™	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0102925
Valvoline™ TYPE F Automatic Transmission Fluid  VV341	Version: 1.3

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System