

Mini Track Loaders / MT55 Mini Track Loader

MT55 Loader Specifications & Options

See complete specifications and options for the MT55 mini track loader.

Standard
 Optional
 N/A Not Applicable

Units US

Bobcat MT55

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in ³
Number of Cylinders	3
Horsepower	24.8 hp

Performance

Rated Operating Capacity (ISO)	550 lb
ROC (ISO) with Standard Counterweight - Undercarriage Position	n/a
ROC (ISO) with Standard Counterweight - Rear Upright Position	n/a
Carry Position ROC with Standard Counterweight - UnderCarriage Position	n/a
Carry Position ROC with Standard Counterweight - Rear Upright Position	n/a
Tipping Load	1610 lb
Operating Weight	2610 lb
Ground Pressure (Rubber)	4.9 psi
Travel Speed	3.5 mph
Travel Speed - Reverse	1.4 mph

Capacities

Fuel Tank	7 gal
-----------	-------

Hydraulic System

Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	n/a

Dimension

Length	93.1 in
Width	35.6 in
Height	49.1 in
Height to Bucket Hinge Pin	71.2 in
Length of track on ground	34 in
Reach @ Maximum Height	18.2 in

Features

Lift-Arm Support	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Reverse Travel Stop Panel	<input type="checkbox"/>
Wide Track	<input checked="" type="checkbox"/>
Neutral Start Interlocks	<input type="checkbox"/>
Lift Arm Lockout With Manual Bypass	<input type="checkbox"/>
Tilt Lockout	<input type="checkbox"/>
Built-In Tie Down & Crane/Lift Locations	<input type="checkbox"/>
Ride-on Platform	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.