

TRANS DECO CEILING

Product Description A vinyl plastic, high density flat finish specially formulated for ceilings. The high density of Trans Deco Ceiling ensures ease of application through reduced dripping and spatter, whilst the flat finish and high opacity enhances ceiling appearance.

Recommended Use An interior surface coating specifically developed for ceilings, it's flat finish helping to "hide" surface irregularities. Not recommended for use on walls or exterior applications. Ceiling in wet areas are best coated using an alkyd system.

Physical Data	Colour	White
	Resin Type	P.V.A Copolymer
	Gloss Level	Flat
	Recommended Film Thickness per Coat	62 microns (wet) 21 microns (dry)
	Theoretical Coverage	Approximately 16.00 sq.m/ltr But this depends upon surface texture and porosity of the surface.
	Packaging	5 litres; 20 litres
	Number Of Component	1
	Durability	For interior use only
	Flash Point	Non Flammable

Surface Preparation Remove grease, dust and dirt by washing down with a liquid detergent and warm water followed by a rinse with clean water. Allow to dry. All loose, peeling and flaking material or rust must be removed. Sand the surface smooth and remove all dust. Sand glossy painted surfaces until all gloss removed. Fill holes and cracks with a spackling compound and sand lightly to an even finish.

Mould
After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilize the surface before repainting.

Application Data	Application Methods	
	Apply By	Brush, Roller or Spray
	Apply Over	Prepared surfaces
	Clean Up	Brushes, rollers and spray equipment should be cleaned in water
	Thinner	No thinning required, but if necessary thin sparingly with water
	Cleaner	Brushes, rollers and spray equipment should be cleaned by water
	Washability	Specially formulated for use in non-contact areas
	Drying Time	
	Touch Dry	20 minutes (longer under cold or adverse drying conditions)
	Recoat	2 hours

TRANS DECO CEILING

CAUTION:

- Provide adequate ventilation during use.
- Do not use below 10°C.

Instruction

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply one or two coats to all surfaces by brush, roller or spray equipment.

Disclaimer

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.
