

## TRANS DECO FLAT ACRYLIC

<b>Product Description</b>	A high quality general purposes paint that is suitable for interior and exterior use. This paint is ideally suited for use on wall and ceiling surfaces in low traffic areas such as bedrooms, etc. Its flat finish will help "hide" surface irregularities.	
<b>Recommended Use</b>	Suitable for use in general living areas over suitably prepared timber, wallboards, brick, stone, fibre cement, plaster, cement and previously painted surfaces. For wet areas, an alkyd system is recommended.	
<b>Physical Data</b>	Colour	Available On Request
	Resin Type	Styrene Acrylic
	Gloss Level	Flat
	Recommended Film Thickness per Coat	65 microns (wet) 20 microns (dry)
	Theoretical Coverage	Approximately 16.00 sq.m/ltr But this depends upon surface texture and porosity of the surface.
	Packaging	5 litres; 20 litres
	Number of Component	1
	Durability	Interior and exterior
	Flash Point	Non Flammable
<b>Surface Preparation</b>	Remove grease, dust and dirt by washing down with a liquid detergent and warm water followed by a rinse with clean water. Allow to dry. All loose, chalky, peeling and flaking material or rust must be removed with a scraper or wire brush. Sand the surface smooth and remove all dust. Sand glossy painted surfaces until all gloss removed. Fill holes and cracks with a suitable stopping compound. Sand lightly to an even finish. <b>Mould</b> After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilize the surface before repainting.	
<b>Application Data</b>	<b>Application Methods</b>	
	Apply By	Brush, Roller or Spray
	Apply Over	Prepared surfaces
	Clean Up	Wash brushes, rollers and spray equipment with water
	Thinner	No thinning required, but if necessary thin sparingly with water
	Cleaner	Brushes, rollers and spray equipment should be cleaned by water
	Washability	Fair
	Drying Time	
	Touch Dry	20 minutes (longer under cold or adverse drying conditions)
	Recoat	2 - 4 hours

## TRANS DECO FLAT ACRYLIC

**CAUTION:**

- Provide adequate ventilation during use.
- Leave seven days after application of final coat before washing.

**Instruction**

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply one or two coats to all surfaces by brush, roller or spray equipment.

---

**Disclaimer**

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.

---