

TRANS DECO SOLVENT BASED ALKALI RESISTANT SEALER

Product Description This pigmented solvent based sealer is based on the latest in Polymer technology to give exceptional resistance to saponification and alkali attack. It is designed for use under both water based and solvent based finishes. It is easy to apply and gives a sound base for further finishing. It has been formulated to have excellent sealing properties for both interior and exterior cement and cementitious surfaces. Because of its highly penetrative properties, it has excellent adhesion, and can “bind” porous and chalky surfaces.

Recommended Use Suitable for use on old or fully cured new cement surfaces such as render, and formwork to prevent alkali attack on the Finish coats. Suitable for other surfaces, such as brickwork, cement sheeting, plasterboarded, etc.

Physical Data	Colour	Not Applicable
	Resin Type	Pure Acrylic
	Gloss Level	Matt
	Recommended Film Thickness per Coat	75 microns (wet) 25 microns (dry)
	Number of Coat	1
	Theoretical Coverage	Approximately 12 sq.m/ltr. Be sure to allow for application losses, surface irregularities, and surface porosity, when computing coverage.
	Packaging	5 litres; 20 litres
	Number Of Component	1
	Durability	For Interior and Exterior use. Must be topcoated.
	Flash Point	Non Flammable

Surface Preparation Remove any contamination from the surface, such as dust and dirt, release agents, etc. by washing down with a liquid detergent in warm water, followed by a rinse with clean water. Allow to dry. Remove all loose surface material or surface projections. Fill holes and cracks with an exterior grade filler, and sand smooth. This sealer has been designed to cope where excess alkalinity occurs, but because of its exceptional sealing properties, it should not be used where extremely high moisture content exists in the substrate as it will seal the water underneath the film. Allow the substrate to dry first before painting.

Application Data	Application Method	
	Apply By	Brush, Roller and Spray
	Apply Over	Clean, dry contaminant free surface
	Clean Up	Brushes, rollers and spray equipment should be cleaned with Thinner Trans 190
	Thinner	Not thinning required, however if thinning is necessary to ease application etc. thin sparingly with Thinner Trans 190
	Cleaner	Thinner Trans 190
	Washability	Not recommended. Must be topcoated.

TRANS DECO SOLVENT BASED ALKALI RESISTANT SEALER

Drying Time

Touch Dry	30 minutes
Recoat	2 hours

CAUTION: Highly flammable. Flash point above 23⁰C. Provide adequate ventilation during use. Keep away from ignition sources. Do not smoke whilst using this product.

Instruction

- Stir content thoroughly with a flat stirrer before and during use.
- Apply one full coat by using a roller or brush, making sure that there are no misses and that the "air-holes" and other imperfections are fully coated.

Note: Ensure that new cement or concrete work is dry before applying the Trans Deco Solvent Based Alkali Resistant Sealer.

Disclaimer

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.
