

TRANS DECO WATER BASED ALKALI RESISTANT SEALER

Product Description Acrylic based pigmented sealer, for use under both water based and solvent based finishes. It is easy to apply and gives a sound base for further finishing. Formulated to resist the action of alkali, and to give a good seal on both interior and exterior cement render and other porous surfaces.

Recommended Use Suitable for use on old or fully cured new cement surfaces such as render, and formwork. Suitable for other surfaces, such as brickwork, cement sheeting, plasterboarded, etc.

Physical Data	Colour	White and Light Tints
	Resin Type	Pure Acrylic
	Gloss Level	Matt
	Recommended Film Thickness per Coat	75 microns (wet) 25 microns (dry)
	Number of Coat	1
	Theoretical Coverage	Approximately 12 sq.m/ltr. Be sure to allow for application losses, surface irregularities, and surface porosity, when computing coverage.
	Packaging	5 litres; 20 litres
	Number of Component	1
	Durability	For Interior and Exterior use. Must be topcoated.
	Flash Point	Non Flammable

Surface Preparation Remove any contamination from the surface, such as dust and dirt, release agents, etc. by washing down with a liquid detergent in warm water, followed by a rinse with clean water. Allow to dry. Remove all loose surface material or surface projections. Fill holes and cracks with an exterior grade filler, and sand smooth. Excess alkalinity should be treated with an acid etch followed by a rinse with clean water. Allow to dry.

Application Data	Application Method	
	Apply By	Brush, Roller and Spray
	Apply Over	Clean, dry contaminant free surface
	Clean Up	Brushes, rollers and spray equipment should be cleaned in water.
	Thinner	Not thinning is required, however if thinning is necessary to ease application etc. thin sparingly with water. To much added water will reduce or eliminate the coatings ability to resist alkali.
	Washability	Not recommended. Must be topcoated.
	Drying Time	
	Touch Dry	30 minutes
	Recoat	2 hours

TRANS DECO WATER BASED ALKALI RESISTANT SEALER

Instruction

- Stir content thoroughly with a flat stirrer before and during use.
- Apply one full coat by using a roller or brush, making sure that there are no misses and that the “air-holes” and other imperfections are fully coated.

Note: Ensure that new cement or concrete work is dry before applying the Trans Deco Water Based Alkali Resistant Sealer.

Disclaimer

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.
