

## TRANS DECO WEATHERCARE ACRYLIC

**Product Description** A premium quality weathercare flat 100% acrylic coating designed specifically for exterior surfaces that require an extremely durable finish.

---

**Recommended Use** For use on suitably prepared timber, brick, cement, stone, fibre cement, galvanized iron, bare iron and previously painted surfaces. May also be use on interior applications where a highly durable maintenance type finish is required.

---

|                      |  |  |
|----------------------|--|--|
| <b>Physical Data</b> | <b>Colour</b>                              | Available On Request   |
|                      | <b>Resin Type</b>                          | Acrylic Emulsion   |
|                      | <b>Gloss Level</b>                         | Flat   |
|                      | <b>Recommended Film Thickness per Coat</b> | 65 microns (wet)   |
|                      | <b>Theoretical Coverage</b>                | Approximately 16.00 sq.m/ltr<br>But this depends upon surface texture and porosity of the surface. |
|                      | <b>Packaging</b>                           | 5 litres; 20 litres  |
|                      | <b>Number of Component</b>                 | 1  |
|                      | <b>Durability</b>                          | Exterior, may also be use on interior surface  |
|                      | <b>Flash Point</b>                         | Non Flammable  |

---

**Surface Preparation** Remove grease, dust and dirt by washing down with a liquid detergent and warm water followed by a rinse with clean water. Allow to dry. All loose, chalky, peeling and flaking material or rust must be removed with a scraper or wire brush. Sand the surface smooth and remove all dust. Sand glossy painted surfaces until all gloss removed. Fill holes and cracks with a suitable stopping compound. Sand lightly to an even finish.

**Mould**

After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilize the surface before repainting.

---

|                         |                            |   |
|-------------------------|----------------------------|---|
| <b>Application Data</b> | <b>Application Methods</b> |   |
|                         | Apply By                   | Brush, Roller or Spray  |
|                         | Apply Over                 | Prepared surfaces   |
|                         | <b>Clean Up</b>            | Wash brushes, rollers and spray equipment with water.             |
|                         | <b>Thinner</b>             | No thinning required, but if necessary thin sparingly with water. |
|                         | <b>Cleaner</b>             | Brushes, rollers and spray equipment should be cleaned by water.  |
|                         | <b>Washability</b>         | Excellent   |
|                         | <b>Drying Time</b>         |   |
|                         | Touch Dry                  | 20 minutes (longer under cold or adverse drying conditions)       |
|                         | Recoat                     | Allow a minimum of two hours                                      |

## TRANS DECO WEATHERCARE ACRYLIC

### CAUTION:

- Avoid painting in temperature greater than 30°C, as a very hot surface will make brushing difficult.
- Not suitable on areas used for the collection of drinking water.
- Provide adequate ventilation during use.

### Instruction

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply one or two coats to all surfaces by brush, roller or spray equipment. Under hot conditions, application can be made easier by damping absorbent surfaces with water.

---

### Disclaimer

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.

---