



# PRIME | 2.5 MM LVT

## Technical Data Sheet

### PRODUCT SPECIFICATIONS

<b>Plank Size:</b>	7.25" X 48"
<b>Construction:</b>	LVP (Luxury Vinyl Plank)
<b>Installation Type:</b>	Glue Down
<b>Thickness:</b>	2.5mm
<b>Wear Layer Thickness:</b>	20mil—0.5mm
<b>Suitability:</b>	Residential & Commercial
<b>Backer:</b>	None—Dryback
<b>Material:</b>	100% virgin vinyl
<b>Maintenance:</b>	No waxing, buffing, sealers or finishes required

### PACKING

<b>SQFT Per Carton:</b>	48.34
<b>Planks Per Carton:</b>	20
<b>Cartons per Pallet:</b>	40
<b>SQFT Per Pallet:</b>	1,933.6

### WARRANTY

**Limited Lifetime Residential**  
**Limited 20 Year Commercial**

### TECHNICAL SPECIFICATIONS

<b>Residual Indentation</b>	ASTM F1914	Pass
<b>Classification</b>	ASTM F3261	Pass
<b>Dimensional Stability</b>	ASTM F2199	Pass
<b>Chemical Resistance</b>	ASTM F925	Pass
<b>Resistance to Heat</b>	ASTM 1514	Pass
<b>Resistance to Light</b>	ASTM 1515	Pass
<b>Static Load</b>	ASTM 970	Pass
<b>Flame Spread</b>	ASTM 648	Pass
<b>Smoke Density</b>	ASTM E662	Pass



Disclaimer: These test results were independently tested, using material from standard production, in accordance with product- specific standard test methods. Physical and performance testing may vary, within tolerances, depending on the testing apparatus and/or production lot used. Be sure to use the most recently published versions of all reference documents, specifications and test methods. To purchase the most recent version of the above mentioned ASTM and ISO standards, please visit [www.astm.org](http://www.astm.org). or [www.iso.org](http://www.iso.org), respectively. Test reports are available upon request.