PRODUCT SPECIFICATIONS

Plank Size:	7" x 48"
Construction:	SPC (Rigid Core Stone Polymer Composite)
Flooring Type:	Resilient Drop Lock Rigid Core
Overall Thickness:	3.2mm Core + 1mm EVA Pad
Wear Layer Thickness:	0.3mm	12mil
Wear Layer Coating:	Diamond plus UV cured Acrylic
Gloss Level:	7% - 9%
Locking System:	UniClic
Surface Edge:	Micro-Beveled
Material:	100% virgin vinyl

PACKING

SQFT Per Carton:	28.36
Planks Per Carton:	12
Cartons per Pallet:	60
SQFT Per Pallet:	1,701.6

WARRANTY

Limited Lifetime Residential
Limited 10 Year Commercial

TECHNICAL SPECIFICATIONS

Residual Indentation	ASTM F1914	PASS
Classification	ASTM F3261	PASS
Dimensional Stability	ASTM F2199	PASS
Chemical Resistance	ASTM F925	PASS
Resistance to Heat	ASTM 1514	PASS
Resistance to Light	ASTM 1515	PASS
Static Load	ASTM 970	PASS
Flame Spread	ASTM 648	PASS
Smoke Density	ASTM E662	PASS
Impact Insulation Class (IIC)	ASTM E492-09	60
Sound Transmission Class (STC)	ASTM E90-09	53

floor score
by SCScertified.