Irrigation Tire, Tube & Wheel Solutions





3200 US HWY 77 CORTLAND, NE 68331

TredzCentralirrigation.com 838-513-8473

Bias

MRL 332 Non Directional

Designed specifically for pivot irrigation. Utilizing lateral lugs provides you with up to 50% less track in your field. The lateral radial lugs ensure enhanced grip and less slippage, giving you fewer stuck pivots.

Available Tubeless: 11.2x24 8 Ply 11.2x38 10 Ply 14.9x24 10 Ply







MRL 331 R-1 Irrigation

Designed for irrigation utilizing curved bars to provide the best performance in wet soils. It ensures better self-cleaning properties having superior grip while protecting crops.



Available Tubeless: 11.2x24 8 Ply 11.2x38 10 Ply 14.9x24 10 Ply

MRL 329 Bias R-1

Reinforced casing and the special cut-and chip resistance compound provide an extended tire life cycle, self-cleaning deep lugs are specifically designed to provide traction and long life under hard working conditions.

Available Tube Type:

12.4x24 12 ply 14.9x24 12 ply 16.9x24 8 ply

12.4x38 14 ply 13.6x38 8 ply







Rainmaxx H20 R-1

Designed for irrigation equipment using center pivot style wheels. Heavy-duty construction and reinforced sidewalls, coupled with a unique tread pattern, delivers superior traction and handling on wet and muddy ground. New Tire replaces need for recaps.

RAINMAX H₂0

Available Tubeless: 11-22.5 10 ply 11-24.5 10 ply

Radial



Radial tire construction lessens wheel tracking and compaction beneath sprinklers utilizing a wider face tread. The rugged radial tire design cuts maintenance costs by reducing flats in the field.

Benefits

- · Low air pressure for less compaction and rutting
- Wider, stronger tread face and durable side wall
- Heavy load rating, even at lower pressures

MRL 885 Radial R-1W

Extra reinforced carcass and cut resistance compound provide extended life. MRL specifically designed tire tread allows for carrying very heavy loads at low pressure and ensuring reduced soil compaction.

Available Tubeless: 280/85R24 380/85R24 320/85R38







BKT Radial 855 R-1W

Features excellent traction and full steel belt internal structure. AGRIMAX RT 855 has excellent self-cleaning provided by the directional lug pattern and high void ratio

BKT

Available Tubeless: 320/85R24 340/85R24 380/85R24

which keeps the footprint clean.

320/85R38 340/85R38 380/85R38


Maxam Radial AgriXtra 85 R1-W

Provides outstanding performance in traction with 45 degree lug and self cleaning tread design. Low pressure and wide foot print lowers soil compaction. Premium rubber compounds reduce ozone cracking and add to the longevity of the tire.

Available Tubeless:

280/85R24 320/85R24 380/85R24

340/85R38 380/80R38





24 Wheels



Pre-Mount Wheel Buffing

We go though an extra step before mounting each pivot tire unit. The natural galvanizing process leaves sharp edges and points on the wheels that can cause damage to the tube. This can cause future flat assemblies. We spend the extra time to **buff every wheel** to save you down time dealing with flats.







8x24 Galvanized

Our galvanized 8 x 24 wheel comes standard with the 8 on 8 bolt pattern fitment. This will fit all your irrigation systems including Valley, Reinke, T-L, and Lindsay brands. Other standard features include a valve stem guard and single dish center.

Tire Fitment: 11.2x24 280/85R24

10x24 Galvanized

Our galvanized 10 \times 24 wheel comes standard with the 8 on 8 bolt pattern fitment. This will fit all your irrigation systems including Valley, Reinke, T-L, and Lindsay brands. Other standard features include a valve stem guard and single dish center.

Tire Fitment:

11.2x24 12.4x24 13.6x24 14.9x24 280/85R24 320/85R24 340/85R24 380/85R24









12x24 Galvanized

Our galvanized 12 x 24 wheel comes standard with the 8 on 8 bolt pattern fitment. This will fit all your irrigation systems including Valley, Reinke and Lindsay brands. Other standard features include a valve stem guard and single dish center.

Tire Fitment: 13.6x24 14.9x24 340/85R24 380/85R24

38 Wheels

10x38 Reinforced Galvanized

Our 10x38 Reinforced Rim comes with the 8 on 8 bolt pattern fitment. This is standard for all Zimmatic, Reinke, Valley, and T-L 8 bolt wheels. The reinforced rim is able withstand the heavy loads and stresses placed on the wheels when traveling uneven terrain. The extra support prevents damage from potential impacts and ensures smooth operation, especially in challenging soil conditions where the pivot might encounter obstacles.

Tire Fitment: 11.2x38 12.4x38 13.6x38 290/85R38 320/85R38 340/85R38









10x38 Standard Galvanized

We stock the 38" wheel in a single dish style. This option also has the 8 on 8 bolt pattern fitment and will fit all major brands. Standard features include a valve stem guard and a single dish center.

Tire Fitment: 11.2x38 12.4x38 13.6x38 290/85R38 320/85R38 340/85R38

10x38 T&L

Yellow 9 hole

These rims are designed specifically for T-L planetary drive systems. T-L has a 9 on 9 bolt pattern specific to their systems. These wheels come in the T-L yellow and are single dish wheels.

Tire Fitment: 11.2x38 12.4x38 13.6x38 290/85R38 320/85R38 340/85R38









12x38 Reinforced Galvanized

Our 12" wide rim is designed to allow for a wide tire footprint. This will reduce soil compaction, and allow for more traction. This is extremely common on swing arm corner systems or towers that get stuck frequently. This wheel comes with the 8 on 8 bolt pattern which fits all major pivot brands and includes a valve stem guard.

Tire Fitment: 13.6x38 14.9x38 340/85R38 380/80R38 380/85R38

Natural Rubber

We use all natural rubber tubes on most of our assemblies. Natural rubber has an elastic property that allows it to stretch and retain its original shape even after being pulled and stretched. This allows our tube to be far more resistant to tears and punctures, compared to its Latex counterpart, preventing your system from future flat tires. The natural rubber tubes have good dynamic performance and high resistant to wear and tear.





TR13

Valve 1.38" long fits .445" valve hole



TR15

Valve 1.38" long fits .625" valve hole



TR218a

Threaded Valve .81" long fits .625" valve hole



TRJ1175C

90 Degree Angle Valve 4.53" long fits .625" valve hole

Natural Rubber Size	Stem
8.5L/9.5L-14	TR13
26x12.00-12	TR13
10.00-15/16	TR15
11.00-16	TR15
11L15/16	TR15
12.5L15/16	TR15
4.00/5.00/5.90-15	TR15
5.50/5.90/6.00-16	TR15
6.50/7.00/7.50-18	TR15
6.50/7.00/7.50-16	TR15
7.50/8.25-20	TR15
7.60-15	TR15
11.2/12.4R24	TR218A
11.2/12.4R36	TR218A
11.2/12.4R38	TR218A
11.2R28	TR218A
13.6/14.9R24	TR218A
13.6/15.5R38	TR218A
13.6R28	TR218A
14.9/16.9/17.5LR24	TR218A
16.9/18.4R28	TR218A
16.9/18.4R30	TR218A
16.9/18.4R34	TR218A
16.9/18.4R38	TR218A
18.4/20.8R42	TR218A
18.4R46	TR218A
20.8R34	TR218A
20.8R38	TR218A
23.1R26	TR218A

TR218A

TR218A

TR218A

TRJ1175C

24.5R32

30.5LR32

20.5R25

8.3/9.5R24

15.5R25/17.5R25

Application Farm Front/Implement Lawn & Garden Farm Front/Implement Farm Irrigation Tractor Rear Farm Irrigation Tractor Rear Farm Irrigation Tractor Rear TRJ1175C Loader

Loader

Service

On Farm Installation

We know your farm work takes priority. When you're busy in the field and get a flat tire or need the convenience of tires replaced on your farm our service truck is here for you. We also offer Calcium draining and Beet Juice refill with RIMGUARD. No tire is too heavy and no job is too big with our mobile service truck.





BEET JUICE TIRE BALLAST

Rimguard Tire Ballast

Rimguard is the heaviest non corrosive tire ballast on the market. It never corrodes, performs in extreme cold weather and heavier than water. The non toxic biodegradable solution will add about 10.7 lbs per gallon. Increase traction by adding weight to your lifting equipment. Increase stability during those heavy loads. Increase your push/pull from your equipment especially effective on turf, ice, snow and wet grounds. Safe for all livestock and animals.

Pivot Wheel Exchange Program

When you're in a crunch, we are here to help! We offer a pivot wheel exchange program to help get you up and rolling when your pivot tires go flat. We carry a large inventory of used galvanized irrigation wheels with NEW tires and tubes mounted on them. We offer this in order to monitor and control the environment and condition of the wheel to ensure proper installation.

HOW IT WORKS: Bring us a flat irrigation tire assembly and we will swap you out with a New Tire/Used Galvanized Wheel Assembly. This saves you on another wheel charge. Subject to in stock availability.





Route Delivery

We run monthly delivery routes in Nebraska, lowa, South Dakota, Kansas and Missouri. Spanning from Des Moines to Sioux Falls to North Platte to Hutchinson to Branson. We can hold your order until the next designated route and then for your convenience we can meet you somewhere near your location. We load up a truck and trailer so no tire is too big and no order is too many for our route delivery. Not in this area? Shipping is always an option.



3200 US HWY 77 CORTLAND, NE 68331

TredzCentralirrigation.com

888-513-8473

Meet the Irrigation Experts



Michael Coufal Michael@tcNebraska.com



Edgar Jimenez Edgar@tcNebraska.com



Brendan Lipovsky Brendan@tcNebraska.com

Irrigation Sales Specialist developed a passion to help and support farmers and the agriculture community. Through the years in the tire industry he has grown a strong knowledge in the irrigation sector.

Tredz Central Story

of experience

across North

America.

Family owned and operated, our operation stems on core Midwest values. Being in the tire business for over 20 years now we've seen many changes in the industry and our priority remains providing the best service to our customers. Along with irrigation tires, we also operate a retail tire shop with inventory of passenger car tires, light truck tires, specialty tires, semi tires, and agricultural tires. We also stock a large inventory of trailers representing 20 different brands and pickup flatbeds on site. Located only 15 minutes south of Lincoln, stop by our location in Cortland, Nebraska today!



Tire Warranty





Maxam



3200 US HWY 77 CORTLAND, NE 68331

TredzCentralirrigation.com

888-513-8473