

SAFETY DATA SHEET

This SDS complies with 29 CFR 1910.1200 (Hazard Communication Standard) IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, and users of this product.

1. Identification

Artic Power
Artic Power
350-01
ure and uses advised against
Freezer Cleaner
See Label Instructions.
Diamond Products Inc.
1216 Bozeman Ave.
Helena, MT 59601
Infotrac: 1 800-535-5053 Emergency: (406) 449-6570
(406) 449-6570

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Acute Tox. 3;H301+311+331	Toxic if swallowed, Toxic in contact with skin, Toxic if inhaled.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Dam. 1;H318	Causes serious eye damage.
STOT SE 1;H370	Causes damage to organs.
STOT RE 2;H373	May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.





H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H370 Causes damage to organs.

H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P330: Rinse mouth.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310: Immediately call a POISON CENTER/doctor

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P308+311: IF exposed or concerned: Call a POISON CENTER or doctor.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P321 Specific treatment (see information on this label).

P332+313 If skin irritation occurs: Get medical advice / attention.

P362+364 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+235: Store in a well ventilated place. Keep cool.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methanol CAS Number: 0000067-56-1	50 - 100	Flam. Liq. 2;H225 Acute Tox. 3;H301+311+331 STOT SE 1;H370	[1][2]
Potassium hydroxide. CAS Number: 0001310-58-3	1.0 - 10	Acute Tox. 4;H302 Skin Corr. 1A;H314	[1][2]
Ethylene glycol CAS Number: 0000107-21-1	1.0 - 10	Acute Tox. 4;H302 STOT RE. 2;H373	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
4.2. Most important syn	nptoms and effects, both acute and delayed
Overview	Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents

	may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness. Toxic if inhaled.
Eyes	Causes serious eye damage.
Skin	Causes skin irritation. Toxic in contact with skin.
Ingestion	Toxic if swallowed.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, alcohol-resistant foam, carbon dioxide or water spray.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus and protective clothing.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Small spills: Mop up with water.

Large spills: Absorb with inert material and place in suitable containers. Dispose of in accordance with local, state and federal regulations.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids. Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage. Keep containers tightly closed.

Incompatible materials: Caustics. Acids. Oxidizers, Reducing agents, Alkali metals.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000067-56-1	Methanol	OSHA	TWA 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm TLV
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3)
		Supplier	No Established Limit
0001310-58-3	Potassium hydroxide.	OSHA	No Established Limit
		ACGIH	Ceiling: 2 mg/m3
		NIOSH	C 2 mg/m3
		Supplier	No Established Limit
0000107-21-1	Ethylene glycol	OSHA	No Established Limit
		ACGIH	100 mg/m3 (TLV)
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001310-58-3	Potassium hydroxide.	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-21-1	Ethylene glycol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3 No; Group 4: No;

8.2. Exposure controls

Respiratory	Organic vapor respirator if vapor concentrations exceed TLV.
Eyes	Use chemical goggles.

Skin	Chemical resistant clothing such as coveralls/apron and boots should be worn. Wear chemical resistant gloves, such as nitrile or PVC.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Clear Liquid
Odor	Alcohol
Odor threshold	Not Measured
рН	12.5 – 13.5
Melting point / freezing point	Not applicable
Initial boiling point and boiling range	150 - 180 °F
Flash Point	49.5°F
Evaporation rate (Ether = 1)	Not available
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 6%
	Upper Explosive Limit: 36%
Vapor pressure (Pa)	Upper Explosive Limit: 36% Not available
Vapor pressure (Pa) Vapor Density	•• •
••••	Not available
Vapor Density	Not available >1.0
Vapor Density Specific Gravity	Not available >1.0 0.85 g/ml
Vapor Density Specific Gravity Solubility in Water	Not available >1.0 0.85 g/ml Complete
Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow)	Not available >1.0 0.85 g/ml Complete Not Measured
Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature	Not available >1.0 0.85 g/ml Complete Not Measured Not available
Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature	Not available >1.0 0.85 g/ml Complete Not Measured Not available Not available

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.**10.2. Chemical stability**Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4. Conditions to avoid

Extreme heat, sparks and open flame. **10.5. Incompatible materials** Caustics. Acids. Oxidizers. **10.6. Hazardous decomposition products** Oxides of Carbon

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Methanol - (67-56-1)	1,187 – 2,769,	17,100.00,	128.20, Rat -	No data	No data
	Rat	Rabbit	Category: NA	available	available
Potassium hydroxide (1310-58-3)	365.00, Rat -	No data	No data	No data	No data
	Category: 4	available	available	available	available
Ethylene glycol - (107-21-1)	4,700, Rat	10,626.00, Rabbit	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	3	Toxic if swallowed
Acute toxicity (dermal)	3	Toxic in contact with skin
Acute toxicity (inhalation)	3	Toxic if inhaled
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure	1	Causes damage to organs.
STOT-repeated exposure	2	May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methanol - (67-56-1)	15,400.00, Lepomis macrochirus	>10,000.00, Daphnia magna	22,000.00 (96 hr), Scenedesmus capricornutum
Ethylene glycol - (107-21-1)	18,500.00, Oncorhynchus mykiss	24,000 41,000., Daphnia magna	Not Available
Potassium hydroxide (1310-58-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	
14.1. UN number	UN2924	
14.2. UN proper shipping name	UN2924, Flammable Liquid, Corrosive N.O.S., (Methanol, Potassium Hydroxide), 3, II	
14.3. Transport hazard class(es)	DOT Hazard Class: 3	
14.4. Packing group	II	
14.5. Environmental hazards		
IMDG Marine	e Pollutant: No	
14.6. Special precautions for user		
No fur	ther information	

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D2B
US EPA Tier II Hazards	Fire: Yes

Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

Potassium hydroxide. (1,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethylene glycol

Methanol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Methanol

Proposition 65 - Female Repro Toxins (>0.0%): Methanol

Proposition 65 - Male Repro Toxins (>0.0%): Methanol

New Jersey RTK Substances (>1%):

Ethylene glycol

Methanol

Potassium hydroxide

Pennsylvania RTK Substances (>1%):

Ethylene glycol

Methanol

Potassium hydroxide

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our

products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H301: Toxic if swallowed

H302 Harmful if swallowed.

H311: Toxic in contact with skin

H314: Causes severe skin burns and eye damage

H331: Toxic if inhaled

H370: Causes damage to organs

H373: May cause damage to organs through prolonged or repeated exposure

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information herein is presented in good faith and believed to be correct as of the date hereof. However, Diamond Products, Inc., makes no representation as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purposes prior to use. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature with respect to the product or the information herein is made hereunder. Diamond Products, Inc., shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication or use of or reliance upon information contained herein.

End of Document