

Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 1 / 12

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

1

1

Code: CERA FLUIDA CLASSIC Product name CERA FLUIDA CLASSIC

Chemical name and synonym RESINS AND WAXES IN SOLUTION

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use BRIGHTENER WAX FOR NATURAL STONES

| Identified Uses | Industrial | Professi | onal | Consumer | | |
|---|---|-----------------|------|----------|--|--|
| ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR | - 7 | | | | | |
| SECTOR | \checkmark | ✓ | | - | | |
| 1.3. Details of the supplier of the safety data sheet | | | | | | |
| Name | Tenax Spa | | | | | |
| Full address | Via I Maggio | , 226 | | | | |
| District and Country | 37020 | Volargne | (VR) | | | |
| | | Italy | | | | |
| | Tel. | +39 045 6887593 | | | | |
| | Fax | +39 045 6862456 | | | | |
| e-mail address of the competent person | | | | | | |
| responsible for the Safety Data Sheet | msds@tenax.it | | | | | |
| Supplier: | Tenax Usa | | | | | |
| | 7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US | | | | | |
| | Tel. 001 7045831173 - Fax 001 7045833166 | | | | | |
| | info@tenax | | | | | |
| 1.4. Emergency telephone number | | | | | | |
| For urgent inquiries refer to | Infotrac | | | | | |
| • | US and Canada: 1-800-535-5053 | | | | | |
| | Int'l: 1-352-323-3500 | | | | | |

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

info@infotrac.net

Classification and Hazard Statement

Carcinogenicity, category 2
Eye irritation, category 2
Skin irritation, category 2
Skin sensitization, category 1

Specific target organ toxicity - single exposure,

category 3
Hazard pictograms:



Signal words: Warning

Suspected of causing cancer. Causes serious eye irritation. Causes skin irritation.

May cause an allergic skin reaction. May cause drowsiness or dizziness.



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 2 / 12

2. Hazards identification/>>

Hazard statements:

H351 Suspected of causing cancer.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P202 Do not handle until all safety precautions have been read and understood.

P201 Obtain special instructions before use.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P271 Use only outdoors or in a well-ventilated area.
P264 Wash the hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.
P312 Call a POISON CENTER / doctor / . . . / if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: wash with plenty of water / . . .

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents / container according to applicable law.

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 2

Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Hazard statements:

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

--

Disposal:

P501 Dispose of contents / container according to applicable law.

Additional hazards Information not available



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 3 / 12

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification:

TETRACHLOROETHYLENE

CAS 127-18-4 $92 \le x < 94$

Carcinogenicity, category 2 H351, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317, Specific target organ toxicity - single exposure, category 3 H336, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

EC 204-825-9 INDEX 602-028-00-4 REACH Reg. 01-2119475329-28

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

^{*} There is a batch to batch variation.



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 4 / 12

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).

EU OEL EU Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU)

2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2021

| | TETRACHLOROETHYLENE | | | | | | | | |
|-----------------------|---------------------|--------|-----|---------|----------|------------------------|--|--|--|
| Threshold Limit Value | | | | | | | | | |
| Type | Country | TWA/8h | | STEL/15 | min | Remarks / Observations | | | |
| | | mg/m3 | ppm | mg/m3 | ppm | | | | |
| TLV-ACGIH | - | 170 | 25 | 678 | 100 | | | | |
| OEL | EU | 138 | 20 | 275 | 40 | SKIN | | | |
| OSHA | USA | | 100 | | 200 (C) | | | | |
| CAL/OSHA | USA | 170 | 25 | 685 (C) | 3000 (C) | | | | |

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.



Revision nr.1 Dated 6/6/2022 First compilation Page n. 5 / 12

Exposure controls/personal protection

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HAND PROTECTION: Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time> 480 minutes.

Material thickness:

NITRII F short contact> 0.38 mm prolonged contact> 0.55 mm **FLUOROELASTOMER** short contact> 0.50 mm prolonged contact> 1.50 mm

Auto-ignition temperature

Decomposition temperature

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties Appearance Colour Odour Odour threshold | Value liquid colourless typical Not available | | Information |
|--|---|------------|---|
| pН | Not available | | Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture) |
| Melting point / freezing point | Not available | | |
| Initial boiling point | Not available | | |
| Boiling range | Not available | | |
| Flash point | > 93 °C | (199,4 °F) | |
| Evaporation rate | Not available | | |
| Flammability (solid, gas) | Not available | | |
| Lower inflammability limit | Not available | | |
| Upper inflammability limit | Not available | | |
| Lower explosive limit | Not available | | |
| Upper explosive limit | Not available | | |
| Vapour pressure | 13 mmHg | | |
| Vapour density | Not available | | |
| Relative density | 1.51 g/cm3 | | |
| Solubility | insoluble in water | | |
| Partition coefficient: n-octanol/water | Not available | | |

Not available

Not available





Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 6 / 12

9. Physical and chemical properties .../>>

Viscosity Not available
Explosive properties Not available
Oxidising properties Not available

9.2. Other information

VOC: 92,00 % - 1.389,20 g/litre

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

TETRACHLOROETHYLENE

Decomposes at temperatures above 150°C/302°F.Decomposes if exposed to: UV rays,moisture.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

TETRACHI OROETHYI ENE

Risk of explosion on contact with: alkaline metals, aluminium, alkaline hydroxides, sodium amides. May react violently with: strong bases, strong oxidising agents, alkaline earth metals, light metals, metal powders, zinc oxide.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

TETRACHLOROETHYLENE

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TETRACHLOROETHYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TETRACHLOROETHYLENE

Has a toxic effect on the central and peripheral nervous system, liver, kidneys and heart; the mucous membranes and the skin are irritated.

Interactive effects

Information not available

ACUTE TOXICITY





Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 7 / 12

11. Toxicological information .../>>

TETRACHLOROETHYLENE LD50 (Oral):

LD50 (Dermal):

LC50 (Inhalation vapours):

3000 mg/kg 10000 mg/kg 4000 ppm/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:

127-18-4 TETRACHLOROETHYLENE

ACGIH:: A3 IARC:2A

NTP: Reasonably Anticipated

TETRACHLOROETHYLENE

Classified in Group 2A (probable human carcinogen) by the International Agency for Research on Cancer (IARC).

Epidemiological studies show evidence of association between exposure to the substance and presence of various types of cancers:

bladder cancer, non-Hodgkin's lymphomas and multiple myeloma (US EPA, 2014).

Classified as a "probable carcinogen" by the US National Toxicology Program (NTP).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

TETRACHLOROETHYLENE

LC50 - for Fish 5 mg/l/96h Limanda limanda

EC50 - for Crustacea 8.5 mg/l/48h Daphnia magna



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 8 / 12

12. Ecological information .../>>

EC50 - for Algae / Aquatic Plants 3.62 mg/l/72h

12.2. Persistence and degradability

TETRACHLOROETHYLENE

Solubility in water 150 mg/l

NOT rapidly degradable

12.3. Bioaccumulative potential

TETRACHLOROETHYLENE

Partition coefficient: n-octanol/water 2.53

BCF 49

12.4. Mobility in soil

TETRACHLOROETHYLENE

Partition coefficient: soil/water 2.15

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1897

14.2. UN proper shipping name

ADR / RID: TETRACHLOROETHYLENE SOLUTION IMDG: TETRACHLOROETHYLENE SOLUTION IATA: TETRACHLOROETHYLENE SOLUTION



Revision nr.1 Dated 6/6/2022 First compilation Page n. 9 / 12

Transport information

14.3. Transport hazard class(es)

ADR / RID: Label: 6.1 Class: 6.1

IMDG: Class: 6.1 Label: 6.1

Class: 6.1 Label: 6.1 IATA:



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

Environmentally Hazardous ADR / RID:

IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID: Limited Quantities: 5 L HIN - Kemler: 60 Tunnel restriction code: (E)

EMS: F-A, S-A IMDG: Limited Quantities: 5 L

IATA: Cargo: Maximum quantity: 220 L Packaging instructions: 663 Pass.:

Maximum quantity: 60 L Packaging instructions: 655

Special provision:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Special provision: -

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

127-18-4 TETRACHLOROETHYLENE

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act - Priority Pollutants:

TETRACHLOROETHYLENE 127-18-4



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 10 / 12

15. Regulatory information .../>

Clean Water Act - Toxic Pollutants:

127-18-4 TETRACHLOROETHYLENE

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

127-18-4 TETRACHLOROETHYLENE

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

127-18-4 TETRACHLOROETHYLENE

EPCRA 313 TRI:

127-18-4 TETRACHLOROETHYLENE

RCRA Code:

127-18-4 TETRACHLOROETHYLENE

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachussetts:

127-18-4 TETRACHLOROETHYLENE

Minnesota:

127-18-4 TETRACHLOROETHYLENE

New Jersey: 127-18-4

127-18-4 TETRACHLOROETHYLENE

New York:

127-18-4 TETRACHLOROETHYLENE

Pennsylvania:

127-18-4 TETRACHLOROETHYLENE

California:

127-18-4 TETRACHLOROETHYLENE

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

127-18-4 TETRACHLOROETHYLENE

NSRL / MADL (µg/day)

Hazard type Oral Dermal Inhalation Intravenous Note

Carcinogenicity 14

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

Vone

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None



Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 11 / 12

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H351 Suspected of causing cancer.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin rea

H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H444 Toxio to caustio life with long leating of

H411 Toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".





Revision nr.1 Dated 6/6/2022 First compilation Printed on 6/6/2022 Page n. 12 / 12

16. Other information .../>>

- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.