

LEAD STABILIZER

Deutschopan E-70558

Deutschopan E-70558 is Lead based complex stabilizer.

Window profile, board, etc. High working stability, good processability and thermal stability.



Handling

Wear a suitable mask, protective clothing, gloves and eye/face protection.

Avoid release to the environment. Refer to the special instructions/safety data sheet. A material safety data sheet for the safe handling of this product is available on request.

This technical data sheet is not dispensing with the responsibility of the user to follow appropriate legal directives such as regulations regarding foodstuff, dangerous substances and safety at working places.

Nothing in this technical data sheet can be constructed as the freedom to infringe on patents of 3rd parties or to breach regulations and laws.

Definition

Complex Lead stabilizer-lubricant one-pack.

Chemical and Physical properties

Appearance	Flakes
Color	Off-white
Bulk Density	1.20 g/cm ³
Solubility in water	In-soluble

Application

Regular grade for window profile, board, etc. Good thermal stability and processability.

Recommended Dosage

Depending on formulations, process conditions and product types; 4.1 ~ 4.8 Phr.

Standard Packing

25 kg net, in multi-fold polypropylene bags.

Mixing

A minimum temperature of 120°C is recommended for optimal dispersion in dry-blend.

Storage

Store in a cool and dry area, away from rain, snow and direct sunlight.

Shelf life

12 months.

