

# MV2400-R

**New Revolutionary  
MITSUBISHI M800  
Series Control**

**ADVANCE PLUS M800**



**Next Generation Control Functions  
and Advanced Pendant Reduce  
Setup Time and Improve Productivity**

## Features:


- **New M800 Series Control Enhances Operator Ergonomics** The M800 uses a new 19" cell phone like touch screen display with pinch, flick and tap operation. The all new mounting system provides the ability to tilt and swivel the unit to best suit the operator. The advance pendant with 3.5" touch screen along with new software features reduce setup time.
- **Powerful Support Functions Improve Productivity** The M800 Advance series control uses Windows 8 Embedded operating system with many levels of automated machine functions to allow even an inexperienced operator to cut parts with confidence.
- **Linear Shaft Motor Drive with 10-Year Positioning Guarantee** and Glass Scale Feedback ensure friction free, highly accurate column movement throughout the entire X Y U V Axes machining range.
- **Highly Rigid Machine Structure** incorporates a fixed table meehanite base casting with the X, Y, Z axes traveling column mounted, a stainless steel work tank, seal plate and hardened stainless steel machine table to provide high accuracy machining.
- **V350-V Full Time AE II (Anti-Electrolysis) Power Supply** suppresses electrolytic corrosion to prevent surface oxidation, edge softening and cobalt depletion in carbide.
- **DMX-S (Digital Matrix Sensor)** combined with the V350-V generator specifically shapes the spark pulse to reduce electrode wear. This allows for a lower wire speed which reduces wire cost by as much as 60%.
- **New Intelligent Auto-Threading System** has been redesigned to anneal up to 17" of wire reducing the curl ratio to less than 10% improving tall part threading as well as submerged threading and re-threading through the gap after a wire break.



# MV-R Series *Revolutionary* Productivity Improvements





Intelligent AT





Advanced wire annealing at over 17" in length reduces wire curl to less than 10% improving tall part threading and reinsert through the gap while submerged.

The new Advance Plus M800 control combined with the Optical Drive System provides 4 times the communication speed between the servo system and the XYUV axes Linear Shaft Motor drives.




The V350-V power supply and DMX-S, Super Digital Control sensor, specifically shape each spark to improve surface finish, reduce vibration and minimize electrode wear. This reduction in wear allows up to a 60% reduction in wire consumption.




The Precision Finish Circuit uses a ceramic insulator between the table base casting and the new hardened SS work table reducing impedance which improves PF surface finish.

MV2400-R Front View




MV2400-R Layout Drawing

(unit:mm(in))



Machine Unit	Machine Specifications		MV2400-R
	Max Workpiece Dimensions (WxDxH)	in	41.3 x 32.3 x 12.0
	Max Workpiece Weight	lb.	3307
	Table Dimensions	in	33.0 x 25.2
	Machining Range (XxYxZ)	in	23.6 x 15.7 x 12.2
	Wire Dia. by AT Device	in	.004 ~ .012
	Wire Tension	g	200 ~ 2550
	Automatic Wire Threader		Standard
	Min. Start Hole Dia.	in	0.02
	Taper Machining Unit		Standard
	Taper Unit Travel (U x V)	in	±3.0 x ±3.0
	Max. Taper Angle	deg	15 deg @ 10.25" Thickness
Fluid System	Overall Machine Dimensions (WxDxH)	in	105.8 x 119.3 x 84.6
	Machine Weight	lb.	7716
	Tank Capacity	gal.	227
	Filtered Particle Size	µm	3
	Filter Elements		2 / Paper
	Ion Exchange Resin	cu/ft	1
	Overall Dimensions	in	34.6 x 82.1 x 52.6
	Dry Weight	lb.	880



**MITSUBISHI EDM**

MC Machinery Systems Inc.  
85 NorthWest Point Blvd.  
Elk Grove Village, IL 60007  
Phone: (630) 616-5920  
Fax: (630) 616-4068  
www.mcmachinery.com

**THE MITSUBISHI EXPERIENCE**