

www.renyson.com

RENYSON CULTIPACKER

High efficiency in land preparation

Advantages:

- Streamline operations
- Reduces soil compactation
- Breaks clods
- Improves soil-seed contact
- Eliminates air pockets
- Prevents moisture lost
- Pushes down small stones
 Allows shallow seed placement

Our Cultipacker is a heavy duty and versatile machine excellent for field preparation, thanks to its advanced design and to it efficient steel rings. The rings are made of the same steel used in disc blades, highly resistant to abrasion and flexible to impacts, they have a long crest sharp enough to penetrate into the soil, thus increasing traction to prevent them from dragging instead of rolling as it happens with cast rings, which also can break when hitting a solid object.

For more information visit www.renyson.com or contact us at info@renyson.com and 915-261-0796

Features


• High resistance and flexible boron steel rings


- Reinforced heavy-duty frame
- High-Tensile steel in bushings and pins
- Triple seal bearings
- Water filling option for more weight
- It can be attached directly to the threepoint hitch if tongue is removed





www.renyson.com






SPECS/MODEL	CDDN10	CDDN12	CDDN14	CDDN16
SPECS/MODEL	CPRN10	CPRN12	CPRN14	CPRN16
А	134.25"	158.25"	182.25"	206.25"
В	120.63"	144.63	168.63"	192.63"
С	39.70"	39.70"	39.70"	39.70"
D	58.03"	58.03"	58.03"	58.03
Е	44.13"	44.13	44.13"	44.13"
F	73.87"	73.87"	73.87"	73.87"
Weight	3300 lbs	3550 lbs	3,800 lbs	4050 lbs
Weight / Water	3580 lbs	3930 lbs	4280 lbs	4630 lbs
Ring Type	Boron Steel	Boron Steel	Boron Steel	Boron Steel
Ring Dia.	16"/24"	16"/24"	16"/24"	16"/24"
Pipe Dia.	12"	12"	12"	12"
Triple Seal Bearings	Timken-TCJ2	Timken-TCJ2	Timken-TCJ2	Timken-TCJ2
Water Capacity	34 gal	46 gal	58 gal	70 gal
Three-Point Option	Yes/CAT3	Yes/CAT3	Yes/CAT3	Yes/CAT3
Tire Size	11L-15 I-1	11L-15 I-1	11L-15 I-1	11L-15 I-1
No. Tires	2	2	2	2
Frame	4"x4" SQ TUB	4"x4" SQ TUB	4"x4" SQ TUB	4"x4" SQ TUB

Exclusive Steel Rings

- Made of hardened boron steel
- Highly resistant to abrasion
- Flexible for impacts
- Long crest for better soil penetration and traction



Renyson LLC 1305 Henry Brennan Dr El Paso, TX 79936 Tel: 915-261-0796 Info@renyson.com